

CURLOPT\_ACCEPTTIMEOUT\_MS(3)      curl\_easy\_setopt options      CURLOPT\_ACCEPTTIMEOUT\_MS(3)

## NAME

CURLOPT\_ACCEPTTIMEOUT\_MS – timeout waiting for FTP server to connect back

## SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_ACCEPTTIMEOUT_MS, long ms);
```

## DESCRIPTION

Pass a long telling libcurl the maximum number of milliseconds to wait for a server to connect back to libcurl when an active FTP connection is used.

## DEFAULT

60000 milliseconds

## PROTOCOLS

FTP

## EXAMPLE

```
CURL *curl = curl_easy_init();
if(curl) {
    curl_easy_setopt(curl, CURLOPT_URL, "ftp://example.com/path/file");

    /* wait no more than 5 seconds for FTP server responses */
    curl_easy_setopt(curl, CURLOPT_ACCEPTTIMEOUT_MS, 5000L);

    curl_easy_perform(curl);
}
```

## AVAILABILITY

Added in 7.24.0

## RETURN VALUE

Returns CURLE\_OK if the option is supported, and CURLE\_UNKNOWN\_OPTION if not.

## SEE ALSO

CURLOPT\_STDERR(3), CURLOPT\_DEBUGFUNCTION(3),