#### UNIX PROGRAMMER'S MANUAL

(

Second Edition

K. Thompson

D. M. Ritchie

June 12, 1972

i

## Copyright <sup>©</sup> 1972 Bell Telephone Laboratories, Inc.

×.

No part of this document may be reproduced, or distributed outside the Laboratories, without the written permission of Bell Telephone Laboratories.

#### PREFACE to the Second Edition

In the months since this manual first appeared, many changes have occurred both in the system itself and in the way it is used.

Perhaps most obviously, there have been additions, deletions, and modifications to the system and its software. It is these changes, of course, that caused the appearance of this revised manual.

Second, the number of people spending an appreciable amount of time writing UNIX software has increased. Credit is due to L. L. Cherry, M. D. McIlroy, L. E. McMahon, R. Morris, and J. F. Ossanna for their contributions.

(

ţ

Finally, the number of UNIX installations has grown to 10, with more expected. None of these has exactly the same complement of hardware or software. Therefore, at any particular installation, it is quite possible that this manual will give inappropriate information. One area to watch concerns commands which deal with special files (I/O devices). Another is places which talk about such things as absolute core locations which are likely to vary with the memory configuration and existence of protection hardware. Also, not all installations have the latest versions of all the software. In particular, the assembler and loader have just undergone major reorganizations in anticipation of a UNIX for the PDP-11/45.

#### INTRODUCT ION

This manual gives descriptions of the publicly available features of UNIX. It provides neither a general overview (see "The UNIX Time-sharing System" for that) nor details of the implementation of the system (which remain to be disclosed).

Within the area it surveys, this manual attempts to be as complete and timely as possible. A conscious decision was made to describe each program in exactly the state it was in at the time its manual section was prepared. In particular, the desire to describe something as it should be, not as it is, was resisted. Inevitably, this means that many sections will soon be out of date. (The rate of change of the system is so great that a dismayingly large number of early sections had to be modified while the rest were being written. The unbounded effort required to stay up-to-date is best indicated by the fact that several of the programs described were written specifically to aid in preparation of this manual!)

This manual is divided into seven sections:

I. Commands

(

(

(

- II. System calls
- III. Subroutines
- IV. Special files
- V. File formats
- VI. User-maintained programs
- VII. Miscellaneous

Commands are programs intended to be invoked directly by the user, in contradistinction to subroutines, which are intended to be called by the user's programs. Commands generally reside in directory <u>/bin</u> (for <u>bin</u>ary programs). This directory is searched automatically by the command line interpreter. Some programs classified as commands are located elsewhere; this fact is indicated in the appropriate sections.

System calls are entries into the UNIX supervisor. In assembly language, they are coded with the use of the opcode "sys", a synonym for the <u>trap</u> instruction.

A small assortment of subroutines is available; they are described in section III. The binary form of most of them is kept in the system library /usr/lib/liba.a.

The special files section IV discusses the characteristics of each system "file" which actually refers to an I/O device.

The file formats section V documents the structure of particular kinds of files; for example, the form of the output of the loader and assembler is given. Excluded are files used by only one command, for example the assembler's intermediate files. User-maintained programs (section VI) are not considered part of the UNIX system, and the principal reason for listing them is to indicate their existence without necessarily giving a complete description. The author should be consulted for information.

The miscellaneous section (VII) gathers odds and ends.

Each section consists of a number of independent entries of a page or so each. The name of the entry is in the upper right corner of its pages, its preparation date in the upper left. Entries within each section are alphabetized. It was thought better to avoid running page numbers, since it is hoped that the manual will be updated frequently. Therefore each entry is numbered starting at page 1.

All entries have a common format.

ĺ

- 1

t

The <u>name</u> section repeats the entry name and gives a very short description of its purpose.

The <u>synopsis</u> summarizes the use of the program being described. A few conventions are used, particularly in the Commands section:

Underlined words are considered literals, and are typed just as they appear.

Square brackets ([]) around an argument indicate that the argument is optional. When an argument is given as "name", it always refers to a file name.

Ellipses "..." are used to show that the previous argument-prototype may be repeated.

A final convention is used by the commands themselves. An argument beginning with a minus sign "-" is often taken to mean some sort of flag argument even if it appears in a position where a file name could appear. Therefore, it is unwise to have files whose names begin with "-".

The <u>description</u> section discusses in detail the subject at hand.

The <u>files</u> section gives the names of files which are built into the program.

A see also section gives pointers to related information.

A <u>diagnostics</u> section discusses the diagnostics that may be produced. This section tends to be as terse as the diagnostics themselves.

The <u>bugs</u> section gives known bugs and sometimes deficiencies. Occasionally also the suggested fix is described. The <u>owner</u> section gives the name of the person or persons to be consulted in case of difficulty. The rule has been that the last one to modify something owns it, so the owner is not necessarily the author. The owner's nicknames stand for:

ken	K. Thompson
dmr	D. M. Ritchie
jfo	J. F. Ossanna
rhm	R. Morris
doug	M. D. McIlroy
lem	L. E. McMahon
llc	L. L. Cherry
csr	C. S. Roberts

i

1

ŧ.

These nicknames also happen to be UNIX user ID's, so messages may be transmitted by the <u>mail</u> command or, if the addressee is logged in, by <u>write</u>.

At the beginning of this document is a table of contents, organized by section and alphabetically within each section. There is also a permuted index derived from the table of contents. Within each index entry, the title of the writeup to which it refers is followed by the appropriate section number in parentheses. This fact is important because there is considerable name duplication among the sections, arising principally from commands which exist only to exercise a particular system call.

This manual was prepared using the UNIX text editor <u>ed</u> and the formatting program <u>roff</u>.

- v -

# TABLE OF CONTENTS

## I. COMMANDS

(

í

(

ť

	place label
	act connect-time accounting
	archive (combine) files
ar	archive (combiner =
as	assembler
as	BASIC dialect
bas	concatenate (or print) files
Cat	
CC	compile C program
	change working directory
chdir	all age don sistency of the block
check	change access mode of files
chmod	Change accept met
chown	change owner of files
CNOWII	compare file contents
Cmp	conv file
	get date and time of day
date	get date and erme of a
db	symbolic debugger
	desk calculator
dc	find free disk space
Af	spawn data-phone daemon
drd	spawn uala-phone alerarchy
ds	verify directory hierarchy
ds	delete files interactively
dsw	find disk usage
An	print command arguments
echo	print command argument
ed	text editor
ea	end command sequence
exit	
fo	comprate a series of itor
fed	IOIM-LELLEI Editor
find	find file with given name
fina	generate form letter
form	
	contraction of a second
if	Conditional comments
istat	file status by i-number
1stat	
ld	
login	
ls	list contents of directory
15	send mail to another user
mail	
man	a const messages
mkdir	create directory
MKQ11	mount detachable file system
mount	
mt	· Suve, recommon file
m6	
	print namelist
nm	format text for printing
nroff	• Lorman af file
	• Occur any
opr	print file off-line
opr	page overlay file princ
OV	
DT	
Y 657	· · · · · · · · · · · · · · · · · · ·
I.W	remove (delete) file

.

# II. SYSTEM CALLS

Ń

i

ĺ

(

TT. DIDIM: OTHER	
	set program break
break	
	change working directory
	change mode of file
chmod	change mode of file
chown	change owner of file
chown	close open file
close	create file
creat	execute program file
exec	terminate execution
	create new process
	status of open file
getuid	get user ID
gtty	get typewriter mode
gtty	set low-priority status
hog	
make	, set date moullied of the
mount	
mount	open file
open	
	moloace processor
	• zor write pointer
setuid	set user ID
sleep	delay execution
steeb	get file status
stat	sot system time
stime	
stry	
-	

sync assu tell find time get umount dism unlink wait write write	time of year nount file system ove (delete) file t for process
---	---

## III. SUBROUTINES

ļ

ĺ

atan conversion conversion atof conversion c	angent ert ASCII to floating ert ASCII to integer ting-point constants ert time to ASCII nential function ting-point simulator ert floating to ASCII unicate with GCOS character ute hypotenuse ert integer to ASCII rithm base e t string on typewriter name list t time t time c character or word exer sort age allocator
--	---

IV. SPECIAL FILES

	801 ACU
dn0	201 Dataphone
dp0	line printer
mt0 ppt rf0	punched paper tape RF disk RK disk
rk0 rp0 tap0 tty tty0	DECtape console typewriter

V. FILE FORMATS

a.out .....assembler and loader output archive .....archive file core .....core image file

3

directory file system ident passwd tap uids utmp wtmp	GCOS ident cards password file DECtape format map names to user ID's logged-in user information
--	---

VI. USER MAINTAINED PROGRAMS

.

l

1

(

í

basic	DEC supplied BASIC
basicbc	compile b program
bc	the game of brack juck
	print calendar
bj	prepare symbol table
chash	cross-reference table
cref	disassembler
das	hand DEC binary paper tapes
dli	DEC ASCIT paper tapes
dot	read DEC ADCII POPOL
dpt	the game or MOU
	permuted index
moo ptx tmg	compile tmgl program
tmg	the game of tic-tac-toe
tmg	Life game of the

# VII. MISCELLANEOUS

ascii	map of ASCII
ascii	boot procedure
asciibproc	adapt to typewriter
getty	argument expander
qlob	initializer process
init	man of TTY 37 keyboard
kbd	how to log onto system
login	Lini Chall
msh	set tab stops on typewriter
mshtabs	act cap cost -

•

INDEX

. 1

(

:(I): place label a.out( $\overline{V}$ ): assembler and loader output access mode of files chmod(I): change accounting files wtmp(V): accounting acct(I): get connect-time accounting tacct(I): connect\_time acct(I): get connect-time accounting ACU dn0(IV): 801 adapt to typewriter getty(VII): allocator salloc(III): storage another user mail(I): send mail to another user write(I): write to archive (combine) files ar(I): archive file archive(V): archive(V): archive file arctangent atan(III): argument expander glob(VII): arguments echo(I): print command ar(I): archive (combine) files ASCII file sort(I): sort ASCII paper tapes dpt(VI): read DEC ASCII to floating atof(III): convert ASCII to integer atoi(III): convert ascii(VII): map of ASCII ASCII ascii(VII): map of ctime(III): convert time to ASCII ASCII...ftoa(III): convert floating to itoa(III): convert integer to ASCII as(I): assembler assembler and loader output  $a_out(V)$ : assembler as(I): assure synchronization sync(II): atan(III): arctangent atof(III): convert ASCII to floating atoi(III): convert ASCII to integer B program bc(VI): compile base e log(III): logarithm bas(I): BASIC dialect BASIC dialect bas(I): basic(VI): DEC supplied BASIC basic(VI): DEC supplied BASIC bc(VI): compile B program become super-user su(I): binary paper tapes dli(VI): load DEC bits...strip(I): remove symbols, relocation bj(VI): the game of black jack black jack bj(VI): the game of boot procedure bproc(VII): bproc(VII): boot procedure break(II): set program break break(II): set program br eak by i-number istat(I): file status

```
– x –
```

C program cc(I): compile calculator dc(I): desk calendar cal(VI): print cal(VI): print calendar cards ident(V): GCOS ident catch EMT traps cemt(II): catch illegal instruction trap ilqins(II): catch or inhibit interrupts intr(II): catch or inhibit quits quit(II): cat(I): concatenate (or print) files cc(I): compile C program cemt(II): catch EMT traps change access mode of files chmod(I): change mode of file chmod(II): change owner of files chown(I): change owner of file chown(II): change working directory chdir(I): change working directory chdir(II): character or word putc(III): write character getc(III): get chash(VI): prepare symbol table chdir(I): change working directory chdir(II): change working directory check consistency of file system check(I): check(I): check consistency of file system chmod(I): change access mode of files chmod(II): change mode of file chown(I): change owner of files chown(II): change owner of file close open file close(II): close(II): close open file cmp(I): compare file contents (combine) files ar(I): archive command arguments echo(I): print command interpreter sh(I): command sequence exit(I): end command transfer goto(I): command if(I): conditional communicate with GCOS gerts(III): communicate with MH-TSS (GCOS) tss(I): compare file contents cmp(I): compile B program bc(VI): compile C program cc(I): compile Fortran program fc(I): compile tmgl program tmg(VI): compute hypotenuse hypot(III): concatenate (or print) files cat(I): conditional command if(I): connect-time accounting acct(I): get connect-time accounting tacct(I): consistency of file system check(I): check console typewriter tty(IV): constants const(III): floating-point const(III): floating-point constants contents of directory ls(I): list cont ent s cmp(I): compare file

ŧ.

£

Ę

convert ASCII to floating atof(III): convert ASCII to integer atoi(III): convert floating to ASCII ftoa(III): convert integer to ASCII itoa(III): convert time to ASCII ctime(III): copy file cp(I): core image file core(V): core memory mem(IV): core(V): core image file cosine sin(III): sine, count wc(I): get (English) word cp(I): copy file create directory makdir(II): create directory mkdir(I): create file creat(II): create new process fork(II): creat(II): create file cref(VI): cross-reference table cross-reference table cref(VI): ctime(III): convert time to ASCII daemon dpd(I): spawn data-phone damaged file system salv(I): repair das(VI): disassembler data-phone daemon dpd(I): spawn Dataphone dp0(IV): 201 date and time of day date(I): get date modified of file mdate(II): set date(I): get date and time of day date(I): get date and time of day db(I): symbolic debugger dc(I): desk calculator debugger db(I): symbolic DEC ASCII paper tapes dpt(VI): read DEC binary paper tapes dli(VI): load DEC supplied BASIC basic(VI): DECtape format tap(V): DECt ape rew(I): rewind tap(I): manipulate DECtape DECtape tap0(IV): delay execution sleep(II): (delete) directory rmdir(I): remove delete files interactively dsw(I): (delete) file rm(I): remove (delete) file unlink(II): remove deny messages mesg(I): permit or depending on value switch(III): transfer desk calculator dc(I): destroy process kill(II): detachable file system mount(I): mount df(I): find free disk space bas(I): BASIC dialect directory format directory(V): directory hierarchy ds(I): verify directory(V): directory format directory chdir(I): change working direc(ory chdir(II): change working

1

(

```
ls(I): list contents of
                             directory
                             directory
         makdir(II): create
           mkdir(I): create directory
  rmdir(I): remove (delete)
                             directory
                             disassembler
                   das(VI):
                             disk space
           df(I): find free
                             disk usage
                du(I): find
                rf0(IV): RF
                             disk
                rkO(IV): RK
                             disk
                             disk
                rp0(IV): RP
                             dismount file system
                umount(II):
                             dismount removable file system
                 umount(I):
                             dli(VI): load DEC binary paper tapes
                             dn0(IV): 801 ACU
                              dpd(I): spawn data-phone daemon
                              dpt(VI): read DEC ASCII paper tapes
                              dp0(IV): 201 Dataphone
                              ds(I): verify directory hierarchy
                              dsw(I): delete files interactively
                              du(I): find disk usage
                              dump of file
               od(I): octal
                              echo(I): print command arguments
                              ed(I): text editor
                              editor (loader)
                 ld(I): link
                 ed(I): text
                              editor
        fed(I): form-letter
                              editor
             cemt(II): catch EMT traps
                              end command sequence
                    exit(I):
                              (English) word count
                  wc(I): get
                              exec(II): execute program file
                              execute program file
                   exec(II):
                              execution
         exit(II): terminate
                              execution
            sleep(II): delay
                              exit(I): end command sequence
                              exit(II): terminate execution
                              expander
         glob(VII): argument
                              exp(III): exponential function
                              exponential function
                   exp(III):
    log(III): logarithm base
                              fc(I): compile Fortran program
                               fed(I): form-letter editor
                               file contents
             cmp(I): compare
                               file off-line
               opr(I): print
                               file page-by-page
              type(I): print
                               file print
         ov(I): page overlay
                               file status by i-number
                   istat(I):
                               file status
                stat(I): get
                               file status
               stat(II): get
                               file system format
             file system(V):
                               file system(V): file system format
                               file system...check(I):
        check consistency of
  mount(I): mount detachable
                               file system
                               file system
            mount(II): mount
                               file system
     salv(I): repair damaged
                               file system
umount(I): dismount removable
                               file system
        umount(II): dismount
```

(

(

file with given name find(I): find file with headings pr(I): print files interactively dsw(I): delete files on magtape mt(I): save/restore ar(I): archive (combine) files files...cat(I): concatenate (or print) files...chmod(I): change access mode of files chown(I): change owner of files wtmp(V): accounting archive(V): archive file chmod(II): change mode of file chown(II): change owner of file close(II): close open file core(V): core image file file cp(I): copy file creat(II): create file exec(II): execute program fstat(II): status of open file link(II): link to file file ln(I): link to file...mdate(II): set date modified of file mv(I): move or rename od(I): octal dump of file open(II): open file passwd(V): password file file read(II): read file rm(I): remove (delete) file sort(I): sort ASCII sum(I): súm file unlink(II): remove (delete) file file write(II): write find disk usage du(I):find file with given name find(I): find free disk space df(I): find name of terminal tty(I): find read or write pointer tell(II): find undefined symbols un(I):find(I): find file with given name floating to ASCII ftoa(III): convert floating-point constants const(III): floating-point simulator fptrap(III): floating atof(III): convert ASCII to fork(II): create new process form letter form(I): generate form-letter editor fed(I): format text for printing nroff(I): format text for printing roff(I): format directory(V): directory file system(v): file system format format tap(V): DECtape form(I): generate form letter Fortran program fptrap(III): floating-point simulator fc(I): compile free disk space df(I): find fstat(II): status of open file ftoa(III): convert floating to ASCII

1

function exp(III): exponential game of black jack bj(VI): the moo(VI): the game of MOO game of tic-tac-toe ttt(VI): the GCOS ident cards ident(V): gerts(III): communicate with GCOS (GCOS)...tss(I): communicate with MH-TSS generate form letter form(I): gerts(III): communicate with GCOS get character getc(III): get connect-time accounting acct(I): date(I): get date and time of day wc(I): get (English) word count stat(I): get file status get file status stat(II): get time information tm(I): get time of year time(II): get typewriter mode gtty(II): get user ID getuid(II): getc(III): get character getty(VII): adapt to typewriter getuid(II): get user ID given name find(I): find file with glob(VII): argument expander goto(I): command transfer gtty(II): get typewriter mode pr(I): print file with headings hierarchy ds(I): verify directory hog(II): set low-priority status how to log onto system login(VII): hypot(III): compute hypotenuse hypot(III): compute hypotenuse i-number istat(I): file status by uids(V): map names to user TD'S ident cards ident(V): GCOS ident(V): GCOS ident cards getuid(II): get user ID setuid(II): set user ID if(I): conditional command ilgins(II): catch illegal instruction trap illegal instruction trap ilgins(II): catch image file core(V): core index ptx(VI): permuted tm(I): get time information utmp(V): logged-in user information inhibit interrupts intr(II): catch or quit(II): catch or inhibit quits initializer process init(VII): init(VII): initializer process instruction trap ilgins(II): catch illegal integer to ASCII itoa(III): convert atoi(III): convert ASCII to integer interactively dsw(I): delete files interpreter sh(I): command intr(II): catch or inhibit interrupts intr(II): catch or inhibit interrupts

ł

istat(I): file status by i-number itoa(III): convert integer to ASCII jack bj(VI): the game of black kbd(VII): map of TTY 37 keyboard kbd(VII): map of TTY 37 keyboard kill(II): destroy process :(I): place label ld(I): link editor (loader) letter form(I): generate form line printer lpr(IV): link editor (loader) 1d(I): link to file link(II): link to file ln(I):link(II): link to file list contents of directory ls(I): list nlist(III): read name ln(I): link to file load DEC binary paper tapes dli(VI): loader output a.out(V): assembler and (loader) ld(I): link editor log on to system login(I): log onto system login(VII): how to logarithm base e log(III): logged-in user information utmp(V): log(III): logarithm base e login(I): log on to system login(VII): how to log onto system low-priority status hog(II): set lpr(IV): line printer ls(I): list contents of directory macroprocessor m6(I): mt(I): save/restore files on magtape magtape mtO(IV): mail to another user mail(I): send mail(I): send mail to another user makdir(II): create directory man(I): run off manual section manipulate DECtape tap(I): manual section man(I): run off map names to user ID's uids(V): map of ASCII ascii(VII): map of TTY 37 keyboard kbd(VII): mdate(II): set date modified of file mem(IV): core memory mem(IV): core memory mesg(I): permit or deny messages mesg(III): print string on typewriter mesg(I): permit or deny messages MH-TSS (GCOS) tss(I): communicate with mini Shell msh(VII): mkdir(I): create directory mode of files chmod(I): change access chmod(II): change mode of file mode of typewriter stty(II): set stty(I): set typewriter modes mode gtty(II): get typewriter

ί

ł

1

modified of file mdate(II): set date moo(VI): the game of MOO moo(VI): the game of MOO mount detachable file system mount(I): mount file system mount(II): mount(I): mount detachable file system mount(II): mount file system move or rename file mv(I):move read or write pointer seek(II): msh(VII): mini Shell mt(I): save/restore files on magtape mtO(IV): magtape mv(I): move or rename file m6(I): macroprocessor name list nlist(III): read name of terminal tty(I): find namelist nm(I): print names to user ID's uids(V): map find(I): find file with given name new process fork(II): create nlist(III): read name list nm(I): print namelist nroff(I): format text for printing octal dump of file od(I): od(I): octal dump of file off manual section man(I): run off-line opr(I): print file login(VII): how to log onto system open file close(II): close open file fstat(II): status of open file open(II): open(II): open file opr(I): print file off-line (or print) files. cat(I): concatenate output...a.out(V): assembler and loader overlay file print ov(I): page ov(I): page overlay file print chown(I): change owner of files chown(II): change owner of file page overlay file print ov(I): type(I): print file page-by-page dli(VI): load DEC binary paper tapes paper tapes dpt(VI): read DEC ASCII ppt(IV): punched paper tape passwd(V): password file password file passwd(V): permit or deny messages mesg(I): permuted index ptx(VI): place label :(I): seek(II): move read or write pointer tell(II): find read or write pointer ppt(IV): punched paper tape prepare symbol table chash(VI): pr(I): print file with headings print calendar cal(VI): print command arguments echo(I):

1

ŧ

(

ĺ

print file off-line opr(I): print file page-by-page type(I): print file with headings pr(1): print) files cat(I): concatenate (or print namelist nm(I): mesg(III): print string on typewriter print time ptime(III): printer lpr(IV): line printing nroff(I): format text for roff(I): format text for printing ov(I): page overlay file print procedure bproc(VII): boot rele(II): release processor fork(II): create new process process init(VII): initializer kill(II): destroy process process wait(II): wait for break(II): set program break exec(II): execute program file program bc(VI): compile B program cc(I): compile C fc(I): compile Fortran program tmg(VI): compile tmgl program ptime(III): print time ptx(VI): permuted index punched paper tape ppt(IV): putc(III): write character or word qsort(III): quicker sort quicker sort qsort(III): quit(II): catch or inhibit quits quit(II): catch or inhibit quits read DEC ASCII paper tapes dpt(VI): read file read(II): read name list nlist(III): read or write pointer seek(II): move read or write pointer tell(II): find read(II): read file release processor rele(II): rele(II): release processor relocation bits strip(I): remove symbols, remote typewriter tty0(IV): removable file system umount(I): dismount remove (delete) directory rmdir(I): remove (delete) file rm(I):remove (delete) file unlink(II): remove symbols, relocation bits strip(I): rename file mv(I): move or repair damaged file system salv(I): rew(I): rewind DECtape rewind DECtape rew(I): rf0(IV): RF disk rfO(IV): RF disk RK disk rk0(IV): rkO(IV): RK disk rmdir(I): remove (delete) directory rm(I): remove (delete) file

{

(

ł

roff(I): format text for printing root sqrt(III): square RP disk rp0(IV): rpO(IV): RP disk run off manual section man(I): salloc(III): storage allocator salv(I): repair damaged file system save/restore files on magtape mt(I):man(I): run off manual section seek(II): move read or write pointer send mail to another user mail(I): exit(I): end command sequence set date modified of file mdate(II): set low-priority status hog(II): set mode of typewriter stty(II): break(II): set program break set system time stime(II): set tab stops on typewriter tabs(VII): set typewriter modes stty(I): setuid(II): set user ID setuid(II): set user ID Shell msh(VII): mini sh(I): command interpreter simulator fptrap(III): floating-point sine, cosine sin(III): sin(III): sine, cosine sleep(II): delay execution sort ASCII file sort(I): sort(I): sort ASCII file sort qsort(III): quicker df(I): find free disk space spawn data-phone daemon dpd(I): sqrt(III): square root sqrt(III): square root stat(I): get file status stat(II): get file status status by i-number istat(I): file fstat(II): status of open file hog(II): set low-priority status stat(I): get file status stat(II): get file status stime(II): set system time stops on typewriter tabs(VII): set tab storage allocator salloc(III): string on typewriter mesg(III): print strip(I): remove symbols, relocation bits stty(I): set typewriter modes stty(II): set mode of typewriter su(I): become super-user sum(I): sum file sum(I): sum file super-user su(I): become supplied BASIC basic(VI): DEC switch(III): transfer depending on value chash(VI): prepare symbol table db(I): symbolic debugger

L

ĺ

(

symbols, relocation bits strip(I): remove symbols un(I): find undefined synchronization sync(II): assure sync(II): assure synchronization system format file system(V): file system time stime(II): set system(V): file system format file system...check(I): check consistency of file login(I): log on to system system login(VII): how to log onto system...mount(I): mount detachable file mount(II): mount file system salv(I): repair damaged file system system...umount(I): dismount removable file system umount(II): dismount file who(I): who is on the system tab stops on typewriter tabs(VII): set chash(VI): prepare symbol table cref(VI): cross-reference table tabs(VII): set tab stops on typewriter tacct(I): connect-time accounting tapes...dli(VI): load DEC binary paper tapes dpt(VI): read DEC ASCII paper ppt(IV): punched paper tape tap(I): manipulate DECtape tap(V): DECtape format tap0(IV): DECtape tell(II): find read or write pointer terminal tty(I): find name of terminate execution exit(II): text editor ed(I):text for printing nroff(I): format text for printing roff(I): format tic-tac-toe ttt(VI): the game of time information tm(I): get date(I): get date and time of day time of year time(II): get time to ASCII ctime(III): convert time(II): get time of year time ptime(III): print stime(II): set system time tmgl program tmg(VI): compile tmg(VI): compile tmgl program tm(I): get time information transfer depending on value switch(III): goto(I): command transfer cemt(II): catch EMT traps trap...ilgins(II): catch illegal instruction tss(I): communicate with MH-TSS (GCOS) ttt(VI): the game of tic-tac-toe TTY 37 keyboard kbd(VII): map of tty(I): find name of terminal tty(IV): console typewriter tty0(IV): remote typewriter type(I): print file page-by-page stty(I): set typewriter modes

(

ţ

1

typewriter mode gtty(II): get typewriter getty(VII): adapt to typewriter mesg(III): print string on typewriter stty(II): set mode of typewriter tabs(VII): set tab stops on typewriter tty(IV): console typewriter tty0(IV): remote uids(V): map names to user ID's umount(I): dismount removable file system umount(II): dismount file system undefined symbols un(I): find un(I): find undefined symbols unlink(II): remove (delete) file du(I): find disk usage user ID's uids(V): map names to user ID getuid(II): get setuid(II): set user ID user information utmp(V): logged\_in mail(I): send mail to another user write(I): write to another user utmp(V): logged-in user information value...switch(III): transfer depending on verify directory hierarchy ds(I): wait for process wait(II): wait(II): wait for process wc(I): get (English) word count who is on the system who(I): who(I): who is on the system with GCOS gerts(III): communicate with given name find(I): find file with headings pr(I): print file tss(I): communicate with MH-TSS (GCOS) wc(I): get (English) word count putc(III): write character or word chdir(I): change working directory chdir(II): change working directory putc(III): write character or word write(II): write file seek(II): move read or write pointer write pointer tell(II): find read or write to another user write(I): write(I): write to another user write(II): write file wtmp(V): accounting files time(II): get time of year 801 ACU dn0(IV): 201 Dataphone dp0(IV): kbd(VII): map of TTY 37 keyboard

į

ĺ

3/15/72

ĺ

ŧ

Ċ

i

NAME	: place a label
SYNOPSIS	: [ label ]
DESCR IPT ION	: does nothing. Its only function is to place a label for the <u>goto</u> command. : is a command so the Shell doesn't have to be fixed to ignore lines with :'s.
FILES	
SEE ALSO	goto(I)
D IAGNOST ICS	<b></b>
BUGS	
OWNER	dmr

•

•

3/15/72

ţ

١

ł

ţ

•

NAME	acct login accounting
SYNOPSIS	acct [ wtmp ]
DESCRIPTION	<u>acct</u> produces a printout giving connect time and total number of connects for each user who has logged in during the life of the current <u>wtmp</u> file. A total is also produced. If no wtmp file is given, <u>/tmp/wtmp</u> is used.
FILES	/tmp/wtmp
SEE ALSO	<pre>init(VII), tacct(I), login(I), wtmp(V).</pre>
DIAGNOST ICS	"Cannot open 'wtmp' if argument is unreadable.
BUGS	
OWNER	dmr, ken

ţ

ŝ

ł

NAME ar -- archive

SYNOPSIS <u>ar</u> key afile name<sub>1</sub> ...

DESCR IPT ION

<u>ar</u> maintains groups of files combined into a single archive file. Its main use is to create and update library files as used by the loader. It can be used, though, for any similar purpose.

<u>key</u> is one character from the set <u>drtux</u>, optionally concatenated with <u>v</u>. <u>afile</u> is the archive file. The <u>names</u> are constituent files in the archive file. The meanings of the <u>key</u> characters are:

d means delete the named files from the archive file.

<u>r</u> means replace the named files in the archive file. If the archive file does not exist, <u>r</u> will create it. If the named files are not in the archive file, they are appended.

t prints a table of contents of the archive file. If no names are given, all files in the archive are tabled. If names are given, only those files are tabled.

<u>u</u> is similar to <u>r</u> except that only those files that have been modified are replaced. If no names are given, all files in the archive that have been modified will be replaced by the modified version.

<u>x</u> will extract the named files. If no names are given, all files in the archive are extracted. In neither case does <u>x</u> alter the archive file.

<u>v</u> means verbose. Under the verbose option, <u>ar</u> gives a file-by-file description of the making of a new archive file from the old archive and the constituent files. The following abbreviations are used:

<u>c</u> copy <u>a</u> append <u>d</u> delete <u>r</u> replace <u>x</u> extract

FILES /tmp/vtm? temporary

SEE ALSO ld(I), archive(V)

DIAGNOSTICS "Bad usage", "afile -- not in archive format", "cannot open temp file", "name -- cannot open", (

í

l

1

"name -- phase error", "name -- cannot create", "no archive file", "cannot create archive file", "name -- not found".

BUGS Option <u>vt</u> should be implemented as a table with more information.

There should be a way to specify the placement of a new file in an archive. Currently, it is placed at the end.

OWNER ken, dmr

,

Ę

ł.

1

NAME	as		assembler
------	----	--	-----------

SYNOPSIS <u>as</u> [ \_ ] name<sub>1</sub> ...

DESCRIPTION <u>as</u> assembles the concatenation of name, .... <u>as</u> is based on the DEC-provided assembler PAL-11R [1], although it was coded locally. Therefore, only the differences will be recorded.

> If the optional first argument <u>-</u> is used, all undefined symbols in the assembly are treated as global.

Character changes are:

for	use
0	*
#	\$
;	/

In <u>as</u>, the character ";" is a logical new line; several operations may appear on one line if separated by ";". Several new expression operators have been provided:

$\mathbf{i}$	right shift (logical)
ŇČ	left shift
*	multiplication
\∕ %	division remainder (no longer means "register")
1	one's complement
۲٦	parentheses for grouping result has value of left, type of right

For example location 0 (relocatable) can be written "0°."; another way to denote register 2 is "2°r0".

All of the preceding operators are binary; if a left operand is missing, it is taken to be 0. The "!" operator adds its left operand to the one's complement of its right operand.

There is a conditional assembly operation code different from that of PAL-11R (whose conditionals are not provided):

.if expression

•••

.endif

If the <u>expression</u> evaluates to non-zero, the section of code between the ".if" and the ".endif" is assembled; otherwise it is ignored. ".if"s may be nested. 1

Temporary labels like those introduced by Knuth [2] may be employed. A temporary label is defined as follows:

n:

where <u>n</u> is a digit 0 ... 9. Symbols of the form "<u>nf</u>" refer to the first label <u>n</u>: following the use of the symbol; those of the form <u>"nb</u>" refer to the last <u>n</u>: . The same <u>n</u> may be used many times. Labels of this form are less taxing both on the imagination of the programmer and on the symbol table space of the assembler.

The PAL-11R opcodes ".word", ".eot" and ".end" are redundant and are omitted.

The symbols

• •

r0 ... r5
fr0 ... fr5 (floating-point registers)
sp
pc
ac
mq
div
mul
lsh
ash
nor
csw

are predefined with appropriate values. The symbol "csw" refers to the console switches. .. is the relocation constant and is added to each relocatable reference. On a PDP-11 with relocation hardware, its value is 0; on most systems without protection, its value is 40000(8).

The new opcode "sys" is used to specify system calls. Names for system calls are predefined. See section (II).

The opcodes "bes" (branch on error set) and "bec" (branch on error clear) are defined to test the error status bit set on return from system calls.

Strings of characters may be assembled in a way more convenient than PAL-11's ".ascii" operation (which is, therefore, omitted). Strings are included between the string quotes < " and ">":

<here is a string>

Escape sequences exist to enter non graphic and

í

ì

(

other difficult characters. These sequences are also effective in single and double character constants introduced by single (') and double (") quotes respectively.

```
for
use
      newline (012)
\n
      NULL (000)
\0
      >
\langle \rangle
      TAB (011)
\t
      ACK (006)
\a
      CR (015)
\r
      ESC (033)
 \p
      \ (134)
```

<u>as</u> provides a primitive segmentation facility. There are three segments: <u>text</u>, <u>data</u> and <u>bss</u>. The text segment is ordinarily used for code. The data segment is provided for initialized but variable data. The bss segment cannot be initialized, but symbols may be defined to lie within this segment. In the future, it is expected that the text segment will be writeprotected and sharable. Assembly begins in the text segment. The pseudo-operations

.text .data .bss

cause the assembler to switch to the text, data, or bss segment respectively. Segmentation is useful at present for two reasons: Noninitialized tables and variables, if placed in the bss segment, occupy no space in the output file. Also, alternative use of the text and data segments provides a primitive dual locationcounter feature.

In the output file, all text-segment information comes first, followed by all data-segment information, and finally bss information. Within each segment, information appears in the order written.

Note: since nothing explicit can be assembled into the bss segment, the usual appearance of this segment is in the following style:

```
.bss
var1: .=.+2
tab1: .=.+100.
```

That is, space is reserved but nothing explicit is placed in it.

(

ŧ

Ę

{

As is evident from the example, it is legal to assign to the location counter ".". It is also permissible in segments other than ".bss". The restriction is made, however, that the value so assigned must be defined in the first pass and it must be a value associated with the same segment as ...

The pseudo-op

.comm symbol, expression

makes <u>symbol</u> an undefined global symbol, and places the value of the expression in the value field of the symbol's definition. Thus the above declaration is equivalent to

> .globl symbol symbol = expression ^ symbol

The treatment of such a symbol by the loader ld(I) is as follows: If another routine in the same load defines the symbol to be an ordinary text, data, bss, or absolute symbol, that definition takes precedence and the symbol acts like a normal undefined external. If however no other routine defines the symbol, the loader defines it as an external bss-segment symbol and reserves <u>n</u> bytes after its location, where <u>n</u> is the value of the expression in the .comm operation. Thus ".comm x,100" effectively declares x to be a common region 100 bytes long. Note: all such declarations for the same symbol in various routines should request the same amount of space.

The binary output of the assembler is placed on the file "a.out" in the current directory. <u>a.out</u> also contains the symbol table from the assembly and relocation bits. The output of the assembler is executable immediately if the assembly was error-free and if there were no unresolved external references. The link editor <u>ld</u> may be used to combine several assembly outputs and resolve global symbols.

The assembler does not produce a listing of the source program. This is not a serious drawback; the debugger <u>db</u> discussed below is sufficiently powerful to render a printed octal translation of the source unnecessary.

On the last pages of this section is a list of all the assembler's built-in symbols. In the case of instructions, the addressing modes are as follows:

- 4 -

ŧ

ł

Ĺ

(

	r fsrc,fdst fr exp	source, destination general register floating source, destination floating register expression
	from those in the 11/45 to avoid conflict with E to draw analogies with e tions.	·
FILES	/tmp/atm1? temporar /tmp/atm2? temporar /tmp/atm3? temporar a.out object	су су
SEE ALSO	D, [2] Knuth, <u>Ine Arc</u> D. Vol. I; Fundamental Alg	f <u>Computer</u> <u>Programming</u> , orithms.
D IAGNOST ICS	lowed by a question mar ceases. When syntactic a single-character diag gether with the line nu	ot be read, its name fol- k is typed and assembly or semantic errors occur, nostic is typed out to- mber and the file name in ors in pass 1 cause can- The possible errors are:
	P Phase error u R Relocation error U Undefined symbol X syntaX error	is odd or too remote or "b") type symbol haracter an <u>If</u> mbol as label assembled at odd address ifferent in pass 1 and 2
BUGS	Symbol table overflow	ards by an odd number of
	bytes, relocation bits	s are corrupted.
OWNER	dmr	

.

Ĺ

1

(

ŧ,

Special variables:	tell	
Special Variabiest	mount	
	umount	
•	setuid	
	getuid stime	
Register:		
Regiscer.	quit intr	
rO	fstat	
r1	cemt	
r2	mdate	
r3	stty	
r4	gtty	
r5	ilgins	
sp	hog	
pc	109	
fr0	Double operand:	
fr1	DO GDI O OF	
fr2	mov src,dst	
fr3	movb "	
fr4	cmp "	
fr5	cmpb "	
	bit	
Eae & switches:	bitb .	
	bic "	
CSW	bicb "	
div	bis "	
aC	bisb "	
mq	add "	
mul	sub	
sC		
sr	Branch:	
nor		
lsh	br	
ash	bne	
	beq	
System calls:	bge	
	bĺt	
exit	bgt	
fork	ble	
read	bpl	
write	bmi	
open	bhi	
close	blos	
wait	bvc	
creat	bvs	
link	bhis	、
unlink	bec (= bcc)	)
exec	bcc	
chdir	blo	
time	bcs	١
makdir	bes (= bcs	)
chmod		
chown		
break		
stat		
seek		

- 6 -

a l

.

(

ŧ

(

(

ł

Single opera	nd :		tstf movf	fsrc fsrc,fr fr,fdst	(= 1df) (= stf)
clr	dst		movf	src,fr	(= 1dcif)
clrb			movif	fr,dst	(= stcfi)
com	**		movfi	fsrc,fr	(= 1 dc df)
comb	<b>91</b>		movof	ISIC,II	(= stcfd)
inc	**		movfo	fr,fdst	(- 00020)
incb	**		addf	fsrc,fr	
dec	90		subf	fsrc,fr	
decb	64		mulf	fscr,fr	
	••		divf	fsrc,fr	
neg	<b>9</b> 9		cmpf	fsrc,fr	
negb adc	**		modf	fsrc,fr	
	41			•	
adcb	*1		11/45 operat	ions	
sbc	••				(-ach)
sbcb	99		als	src,r	(= ash)
ror	**		alsc	src,r	(= ashc)
rorb			mpy	src,r	(= mul)
rol			dvd	src,r	(= div)
rolb			xor	src,r	
asr			sxt	dst	
asrb	**		mark	exp	
asl	**		sob	r,exp	
aslb	**				
jmp			Specials		
swab			opecia		
tst	src		.byte		
tstb	src		.even		
			.if		
Miscellaneo	us:		.endif		
			.globl		
jsr	r,dst		text		
rts	r	(- +)	data		
sys	exp	(= trap)	.bss		
			, comm		
Flag-settin	g :		• • • • • • • • • • • • • • • • • • • •		
_					
clc					
clv					
clz					
cln					
sec					
sev					
sez					
sen					
Floating po	oint ops:				
cfcc					
setf					
setd					
seta					
setl					
clrf	fdst				
	fdst				
negf absf	fdst				
absi	1000				

1

t

NAME	bas	فتته مین	basic
------	-----	----------	-------

bas [ file ] SYNOPSIS

bas is a dialect of basic [1]. If a file argument is provided, the file is used for input DESCRIPTION before the console is read.

bas accepts lines of the form:

statement integer statement

Integer numbered statements (known as internal statements) are stored for later execution. They are stored in sorted ascending order. Nonnumbered statements are immediately executed. The result of an immediate expression statement (that does not have '=' as its highest operator) is printed.

Statements have the following syntax: (<u>expr</u> is short for expression)

expr

The expression is executed for its side effects (assignment or function call) or for printing as described above.

done

Return to system level.

for name = expr expr statement for name = expr expr

### . . .

The for statement repetitively executes a statement (first form) or a group of statements (second form) under control of a named variable. The variable takes on the value of the first expression, then is incremented by one on each loop, not to exceed the value of the second expression.

#### <u>goto</u> expr

The expression is evaluated, truncated to an integer and execution goes to the corresponding integer numbered statment. If executed from immediate mode, the internal statements are compiled first.

<u>if</u> expr statement The statement is executed if the expression evaluates to non-zero.

<u>list</u> [expr [expr]]

1

1

(

1

list is used to print out the stored internal statements. If no arguments are given, all internal statements are printed. one argument is given, only that internal statement is listed. If two arguments are given, all internal statements inclusively between the arguments are printed.

print expr

The expression is evaluated and printed.

return expr

The expression is evaluated and the result is passed back as the value of a function call.

The internal statements are compiled. run The The random symbol table is re-initialized. number generator is re-set. Control is passed to the lowest numbered internal statement.

Expressions have the following syntax:

name

A name is used to specify a variable. Names are composed of a letter ('a' - 'z') followed by letters and digits. The first four characters of a name are significant.

number

A number is used to represent a constant value. A number is composed of digits, at most one decimal point ('.') and possibly a scale factor of the form <u>e</u> digits or <u>e-</u> digits.

Parentheses are used to alter normal order ( expr )

of evaluation.

expr op expr

Common functions of two arguments are abbreviated by the two arguments separated by an operator denoting the function. A complete list of operators is given below.

expr ( [expr [, expr ...]] ) Functions of an arbitrary number of arguments can be called by an expression followed by the arguments in parentheses separated by commas. The expression evaluates to the line number of the entry of the function in the internally stored statements. This causes the internal statements

- 2 -

j

ertt<sup>ere</sup>

(

to be compiled. If the expression evaluates negative, a builtin function is called. The list of builtin functions appears below.

name [ expr [, expr ...] ]
Arrays are not yet implemented.

The following is the list of operators:

is the assignment operator. The left
 operand must be a name or an array element.
 The result is the right operand. Assign ment binds right to left, all other opera tors bind left to right.

- & | <u>&</u> (logical and) has result zero if either of its arguments are zero. It has result one if both its arguments are non-zero. <u>|</u> (logical or) has result zero if both of its arguments are zero. It has result one if either of its arguments are non-zero.
- < <= > >= == <>
  The relational operators (< less than, <=
  less than or equal, > greater than, >=
  greater than or equal, == equal to, <> not
  equal to) return one if their arguments are
  in the specified relation. They return
  zero otherwise. Relational operators at
  the same level extend as follows: a>b>c is
  the same as a>b&b>c.

Add and subtract.

Multiply and divide.

~

=

Exponentiation.

The following is a list of builtin functions:

arg
Arg(i) is the value of the <u>i</u>th actual
parameter on the current level of function
call.

exp Exp(x) is the exponential function of x.

log Log(x) is the logarithm base e of x.

- 3 -

ł

ł

Sin(x) is the sine of x (radians). sin  $\cos(x)$  is the cosine of x (radians). cos Atn(x) is the arctangent of x. (Not impleatn mented.) Rnd() is a uniformly distributed random rnd number between zero and one. Expr() is the only form of program input. expr A line is read from the input and evaluated as an expression. The resultant value is returned. Int(x) returns x truncated to an integer. int temporary /tmp/btm? FILES [1] DEC-11-AJPB-D SEE ALSO Syntax errors cause the incorrect line to be typed with an underscore where the parse failed. DIAGNOSTICS All other diagnostics are self explanatory. Arrays [] are not yet implemented. In general, program sizes, recursion, etc are not checked, and cause trouble. ken

OWNER

BUGS

- 4 -

ł

ţ

Í

ţ

)

cat -- concatenate and print NAME cat file ... SYNOPSIS cat reads each file in sequence and writes it on the standard output stream. Thus: DESCRIPTION <u>cat file</u> is about the easiest way to print a file. Also: <u>cat file1 file2 >file3</u> is about the easiest way to concatenate files. If no input file is given cat reads from the standard input file. ----FILES pr(I), cp(I) SEE ALSO none; if a file cannot be found it is ignored. DIAGNOSTICS \_ BUGS ken, dmr OWNER

į

- 1 -

------

រ

(

Ĺ

)

e
co Le ier ded
, S
2.
ry.

L

(

(

NAME chdir -- change working directory

SYNOPSIS <u>chdir</u> directory

DESCRIPTION <u>directory</u> becomes the new working directory.

Because a new process is created to execute each command, <u>chdir</u> would be ineffective if it were written as a normal command. It is therefore recognized and executed by the Shell.

FILES --

SEE ALSO sh(I)

DIAGNOSTICS "Bad directory" if the directory cannot be changed to.

BUGS --

OWNER ken, dmr

ł

NAME check -- file system consistency check

SYNOPSIS <u>check</u> [filesystem [blockno<sub>1</sub> ... ]]

DESCRIPTION <u>check</u> will examine a file system, build a bit map of used blocks, and compare this bit map against the bit map maintained on the file system. If the file system is not specified, a check of all of the normally mounted file systems is performed. Output includes the number of files on the file system, the number of these that are 'large', the number of used blocks, and the number of free blocks.

FILES /dev/rf?, /dev/rk?, /dev/rp?

SEE ALSO find(I), ds(I)

- DIAGNOSTICS Diagnostics are produced for blocks missing, duplicated, and bad block addresses. Diagnostics are also produced for block numbers passed as parameters. In each case, the block number, i-number, and block class ( $\underline{i}$  = inode,  $\underline{x}$  indirect, f free) is printed.
- BUGS The checking process is two pass in nature. If checking is done on an active file system, extraneous diagnostics may occur.

The swap space on the RF file system is not accounted for and will therefore show up as 'missing'.

OWNER ken, dmr

- 1 -

ŧ

i

ĺ

NAME	chmod change mode
SYNOPSIS	chmod octal file,
DESCRIPTION	The octal mode replaces the mode of each of the files. The mode is constructed from the OR of the following modes:
	01 write for non-owner 02 read for non-owner 04 write for owner 10 read for owner 20 executable 40 set-UID
	Only the owner of a file may change its mode.
FILES	<b></b>
SEE ALSO	<pre>stat(I), ls(I)</pre>
DIAGNOST ICS	"?"
BUGS	
OWN ER	ken, dmr

۰

l

ţ

۰.

NAME	chown change owner
SYNOPSIS	chown owner file,
DESCR IPT ION	<u>owner</u> becomes the new owner of the files. The owner may be either a decimal UID or a name found in /etc/uids.
	Only the owner of a file is allowed to change the owner. It is illegal to change the owner of a file with the set-user-ID mode.
FILES	/etc/uids
SEE ALSO	stat(I)
D IAGNOST ICS	"Who?" if owner cannot be found, "file?" if file cannot be found.
BUGS	

.

OWNER ken, dmr

(

ĺ

1

NAME cmp -- compare two files

SYNOPSIS <u>cmp</u> file<sub>1</sub> file<sub>2</sub>

DESCRIPTION The two files are compared for identical contents. Discrepancies are noted by giving the offset and the differing words.

FILES --

SEE ALSO --

DIAGNOSTICS Messages are given for inability to open either argument, premature EOF on either argument, and incorrect usage.

BUGS If the two files differ in length by one byte, the extra byte does not enter into the comparison.

OWNER dmr

- 1 -

í

i

(

Í

NAME	cp copy
SYNOPSIS	<u>cp</u> file <sub>1</sub> file <sub>2</sub>
DESCR IPT ION	The first file is opened for reading, the second created mode 17. Then the first is copied into the second.
FILES	
SEE ALSO	cat(I), pr(I)
D IAGNOST ICS	Error returns are checked at every system call, and appropriate diagnostics are produced.
BUGS	The second file should be created in the mode of the first.
	A directory convention as used in <u>mv</u> should be adopted for <u>CP</u> .
OWNER	ken, dmr

Ę

i.

NAME date -- print and set the date

SYNOPSIS <u>date</u> [ mmddhhmm ]

----

----

dmr

DESCRIPTION If no argument is given, the current date is printed to the second. If an argument is given, the current date is set. <u>mm</u> is the month number; <u>dd</u> is the day number in the month; <u>hh</u> is the hour number (24 hour system); <u>mm</u> is the minute number. For example:

date 10080045

sets the date to Oct 8, 12:45 AM.

FILES

SEE ALSO

DIAGNOSTICS "?" if the argument is syntactically incorrect.

BUGS

-

OWNER

Į.

Ê

Ĺ

1

# NAME db -- debug

SYNOPSIS <u>db</u> [ core [ namelist ] ] [ = ]

DESCRIPTION Unlike many debugging packages (including DEC's ODT, on which <u>db</u> is loosely based) <u>db</u> is not loaded as part of the core image which it is used to examine; instead it examines files. Typically, the file will be either a core image produced after a fault or the binary output of the assembler. <u>Core</u> is the file being debugged; if omitted core is assumed. <u>namelist</u> is a file containing a symbol table. If it is omitted, the symbol table is obtained from the file being debugged, or if not there from <u>a.out</u>. If no appropriate name list file can be found, <u>db</u> can still be used but some of its symbolic facilities become unavailable.

For the meaning of the optional third argument, see the last paragraph below.

The format for most <u>db</u> requests is an address followed by a one character command.

Addresses are expressions built up as follows:

- A name has the value assigned to it when the input file was assembled. It may be relocatable or not depending on the use of the name during the assembly.
- An octal number is an absolute quantity with the appropriate value.
- 3. An octal number immediately followed by "r" is a relocatable quantity with the appropriate value.
- 4. The symbol "." indicates the current pointer of <u>db</u>. The current pointer is set by many <u>db</u> requests.
- 5. Expressions separated by "+" or "" (blank) are expressions with value equal to the sum of the components. At most one of the components may be relocatable.
- 6. Expressions separated by "-" form an expression with value equal to the difference to the components. If the right component is relocatable, the left component must be relocatable.
- 7. Expressions are evaluated left to right.

1

ť

. ۲

{

1

Names for registers are built in:

```
r0 ... r5
sp
pc
ac
mq
```

These may be examined. Their values are deduced from the contents of the stack in a core image file. They are meaningless in a file that is not a core image.

If no address is given for a command, the current address (also specified by .) is assumed. In general, . points to the last word or byte printed by <u>db</u>.

There are <u>db</u> commands for examining locations interpreted as octal numbers, machine instructions, ASCII characters, and addresses. For numbers and characters, either bytes or words may be examined. The following commands are used to examine the specified file.

- / The addressed word is printed in octal.
- $\setminus$  The addressed byte is printed in octal.
- " The addressed word is printed as two ASCII characters.
- The addressed byte is printed as an ASCII character.
- The addressed word is multiplied by 2, then printed in octal (used with B programs, whose addresses are word addresses).
- ? The addressed word is interpreted as a machine instruction and a symbolic form of the instruction, including symbolic addresses, is printed. Often, the result will appear exactly as it was written in the source program.
- & The addressed word is interpreted as a symbolic address and is printed as the name of the symbol whose value is closest to the addressed word, possibly followed by a signed offset.

<nl> (i. e., the character "new line") This
 command advances the current location
 counter "." and prints the resulting loca tion in the mode last specified by one of

ŧ

the above requests.

- This character decrements "." and prints the resulting location in the mode last selected one of the above requests. It is a converse to <nl>.
- % Exit.

It is illegal for the word-oriented commands to have odd addresses. The incrementing and decrementing of "." done by the <nl> and " requests is by one or two depending on whether the last command was word or byte oriented.

The address portion of any of the above commands may be followed by a comma and then by an expression. In this case that number of sequential words or bytes specified by the expression is printed. . is advanced so that it points at the last thing printed.

There are two commands to interpret the value of expressions.

- When preceded by an expression, the value of the expression is typed in octal. When not preceded by an expression, the value of . is indicated. This command does not change the value of . .
- : An attempt is made to print the given expression as a symbolic address. If the expression is relocatable, that symbol is found whose value is nearest that of the expression, and the symbol is typed, followed by a sign and the appropriate offset. If the value of the expression is absolute, a symbol with exactly the indicated value is sought and printed if found; if no matching symbol is discovered, the octal value of the expression is given.

The following command may be used to patch the file being debugged.

I This command must be preceded by an expression. The value of the expression is stored at the location addressed by the current value of ".". The opcodes do not appear in the symbol table, so the user must assemble them by hand.

The following command is used after a fault has caused a core image file to be produced.

í

Į.

i

\$ causes the fault type and the contents of the general registers and several other registers to be printed both in octal and symbolic format. The values are as they were at the time of the fault.

 $\underline{Db}$  should not be used to examine special files, for example disks and tapes, since it reads one byte at a time. Use od(I) instead.

For some purposes, it is important to know how addresses typed by the user correspond with locations in the file being debugged. The mapping algorithm employed by <u>db</u> is non-trivial for two reasons: First, in an <u>a.out</u> file, there is a 20(8) byte header which will not appear when the file is loaded into core for execution. Therefore, apparent location 0 should correspond with actual file offset 20. Second, some systems cause a "squashed" core image to be written. In such a core image, addresses in the stack must be mapped according to the degree of squashing which has been employed. <u>Db</u> obeys the following rules:

If exactly one argument is given, and if it appears to be an <u>a.out</u> file, the 20-byte header is skipped during addressing, i.e., 20 is added to all addresses typed. As a consequence, the header can be examined beginning at location -20.

If exactly one argument is given and if the file does not appear to be an <u>a.out</u> file, no mapping is done.

If zero or two arguments are given, the mapping appropriate to a core image file is employed. This means that locations above the program break and below the stack effectively do not exist (and are not, in fact, recorded in the core file). Locations above the user's stack pointer are mapped, in looking at the core file, to the place where they are really stored. The per-process data kept by the system, which is stored in the last 512(10) bytes of the core file, can be addressed at apparent locations 160000-160777.

If one wants to examine a file which has an associated name list, but is not a core image file, the last argument "-" can be used (actually the only purpose of the last argument is to make the number of arguments not equal to two). This feature is used most frequently in examining the memory file /dev/mem.

Ć

ţ

ł

١,

SEE ALSO as(I), core(V), a.out(V), od(I)

DIAGNOSTICS "File not found" if the first argument cannot be read; otherwise "?".

BUGS The "?" request always decrements "." by 2, even in byte mode.

OWNER dmr

Ę

(

.

,

(

NAME	dc desk calculator
SYNOPSIS	dc
DESCRIPTION	<u>dc</u> is an arbitrary precision integer arithmetic package. The overall structure of dc is a stack- ing (reverse Polish) calculator. The following constructions are recognized by the calculator:
,	number The value of the number is pushed on the stack. If the number starts with a zero, it is taken to be octal, otherwise it is decimal.
	$\pm - \pm / \frac{\kappa}{2}$ The top two values on the stack are added $(\pm)$ , subtracted $(-)$ , multiplied $(\pm)$ , divided $(/)$ , or remaindered $(\frac{\kappa}{2})$ . The two entries are poppped off of the stack, the result is pushed on the stack in their place.
	SX The top of the stack is popped and stored into a register named x, where x may be any charac- ter.
	<u>lx</u> The value in register x is pushed on the stack. The register x is not altered.
	<u>d</u> The top value on the stack is pushed on the stack. Thus the top value is duplicated.
	P The top value on the stack is printed in de- cimal. The top value remains unchanged.
	f All values on the stack are popped off and printed in decimal.
	g exits the program
	x treats the top element of the stack as a char- acter string and executes it as a string of dc commands
	I interprets the rest of the line as a UNIX com- mand.
	r All values on the stack are popped.

1

1

.

ĺ

nk A scale factor of 10<sup>n</sup> is set for all subsequent multiplication and division. new-line space ignored. An example to calculate the monthly, weekly and hourly rates for a \$10,000/year salary. 10000 (now in cents) 100\* (non-destructive store) dsa (pennies per month) 12/ (pennies per week) 1a52/(deci-pennies per week) d10\* (pennies per hour) 375/ (print all results) f (3) 512 (2) 19230 (1) 83333 FILES SEE ALSO (x) ? for unrecognized character x. (x) ? for not enough elements on the stack to do DIAGNOSTICS what was asked. "Out of space" when the free list is exhausted. . f is not implemented BUGS % is not implemented rhm OWNER

- 2 -

(

.

ł

{

(

NAME	df disk free
SYNOPSIS	<u>df</u> [_filesystem ]
DESCR IPT ION	<u>df</u> prints out the number of free blocks available on a file system. If the file system is unspeci- fied, the free space on all of the normally mounted file systems is printed.
FILES	/dev/rf?, /dev/rk?, /dev/rp?
SEE ALSO	check(I)
DIAGNOST ICS	
BUGS	
OWNER	ken, dmr

NAME

ł

ł

dpd -- spawn data phone daemon

SYNOPSIS /etc/dpd

DESCRIPTION <u>dpd</u> is the 201 data phone daemon. It is designed to submit jobs to the Honeywell 6070 computer via the gerts interface.

<u>dpd</u> uses the directory <u>/usr/dpd</u>. The file <u>lock</u> in that directory is used to prevent two daemons from becoming active. After the daemon has successfully set the lock, it forks and the main path exits, thus spawning the daemon. <u>/usr/dpd</u> is scanned for any file beginning with <u>df</u>. Each such file is submitted as a job. Each line of a job file must begin with a key character to specify what to do with the remainder of the line

S directs dpd to generate a unique snumb card. This card is generated by incrementing the first word of the file <u>/usr/dpd/snumb</u> and converting that to decimal concatenated with the station ID.

L specifies that the remainder of the line is to be sent as a literal.

<u>B</u> specifies that the rest of the line is a file name. That file is to be sent as binary cards.

 $\underline{F}$  is the same as  $\underline{B}$  except the file is prepended with a form feed.

U specifies that the rest of the line is a file name. After the job has been transmitted, the file is unlinked.

Any error encountered will cause the daemon to drop the call, wait up to 20 minutes and start over. This means that an improperly constructed <u>df</u> file may cause the same job to be submitted every 20 minutes.

While waiting, the daemon checks to see that the <u>lock</u> file still exists. If the <u>lock</u> is gone, the daemon will exit.

FILES /dev/dn0, /dev/dp0, /usr/dpd/\*

SEE ALSO opr(I)

DIAGNOSTICS

BUGS

(

Ś

L-----

( .

OWNER ken

.

.

- 2 -

1

i

++2:-

(

NAME ds -- directory consistency check

SYNOPSIS <u>ds</u> [output ]

DESCRIPTION <u>ds</u> will walk the directory tree from the root keeping a list of every file encountered. The second pass will read the i-list and compare the number of links there with the actual number found. All discrepancies are noted.

If an argument is given, a complete printout of file names by i-number is output on the argument.

FILES /, /dev/rk0, /tmp/dstmp

SEE ALSO check(I)

DIAGNOSTICS inconsistent i-numbers

ken

BUGS the root is noted as inconsistent due to the fact that / exists in no directory. (Its i-number is 41.)

ds should take an alternate file system argument.

OWNER

- 1 -

•

ŧ

Ì

(

Ĺ

4

NAME	dsw delete interactively
SYNOPSIS	<u>dsw</u> [directory]
DESCRIPTION	For each file in the given directory ("." if not specified) <u>dsw</u> types its name. If "y" is typed, the file is deleted; if "x", <u>dsw</u> exits; if any- thing else, the file is not removed.
FILES	
SEE ALSO	rm(I)
DIAGNOSTICS	"?"
BUGS	The name "dsw" is a carryover from the ancient past. Its etymology is amusing but the name is nonetheless ill-advised.
OWNER	dmr, ken

ļ

(

NAME	du — summarize disk usage
SYNOPSIS	<u>du</u> [ <u>-s</u> ][ <u>-a</u> ][name]
DESCRIPTION	<u>du</u> gives the number of blocks contained in all files and (recursively) directories within each specified directory or file <u>name</u> . If <u>name</u> is missing, <u>.</u> is used.
	The optional argument <u>-s</u> causes only the grand total to be given. The optional argument <u>-a</u> causes an entry to be generated for each file. Absence of either causes an entry to be generated for each directory only.
	A file which has two links to it is only counted once.
FILES	•
SEE ALSO	
DIAGNOSTICS	
BUGS	Non-directories given as arguments (not under -a option) are not listed.
	Removable file systems do not work correctly since i-numbers may be repeated while the corresponding files are distinct. Du should maintain an i-number list per root directory encountered.

OWNER

dmr

- 1 -

(

ł

ł

ţ

NAME	echo echo arguments
SYNOPSIS	echo [arg <sub>1</sub> ]
DESCR IPT ION	<u>echo</u> writes all its arguments in order as a line on the standard output file. It is mainly useful for producing diagnostics in command files.
FILES	
SEE ALSO	
DIAGNOSTICS	
BUGS	
OWNER	doug

- 1 -

6/12/72

(

١

ed		editor
	ed	ed —

SYNOPSIS ed [ name ]

DESCRIPTION ed is the standard text editor.

If the optional argument is given, <u>ed</u> simulates an <u>e</u> command on the named file; that is to say, the file is read into <u>ed</u>'s buffer so that it can be edited.

ed operates on a copy of any file it is editing; changes made in the copy have no effect on the file until an explicit write ( $\underline{w}$ ) command is given. The copy of the text being edited resides in a temporary file called the <u>buffer</u>. There is only one buffer.

Commands to <u>ed</u> have a simple and regular structure: zero or more <u>addresses</u> followed by a single character <u>command</u>, possibly followed by parameters to the command. These addresses specify one or more lines in the buffer. Every command which requires addresses has default addresses, so that the addresses can often be omitted.

In general only one command may appear on a line. Certain commands allow the input of text. This text is placed in the appropriate place in the buffer. While ed is accepting text, it is said to be in <u>input mode</u>. In this mode, no commands are recognized; all input is merely collected. Input mode is left by typing a period (.) alone at the beginning of a line.

ed supports a limited form of <u>regular expression</u> notation. A regular expression is an expression which specifies a set of strings of characters. A member of this set of strings is said to be <u>matched</u> by the regular expression. The regular expressions allowed by <u>ed</u> are constructed as follows:

- An ordinary character (not one of those discussed below) is a regular expression and matches that character.
- A circumflex (<sup>^</sup>) at the beginning of a regular expression matches the null character at the beginning of a line.
- 3. A currency symbol (\$) at the end of a regular expression matches the null character at the end of a line.

1

ţ

٠

(

- A period (.) matches any character but a new-line character.
- 5. A regular expression followed by an asterisk (\*) matches any number of adjacent occurrences (including zero) of the regular expression it follows.
- 6. A string of characters enclosed in square brackets ([]) matches any character in the string but no others. If, however, the first character of the string is a circumflex (^) the regular expression matches any character but new-line and the characters in the string.
- 7. The concatenation of regular expressions is a regular expression which matches the concatenation of the strings matched by the components of the regular expression.
- 8. The null regular expression standing alone is equivalent to the last regular expression encountered.

Regular expressions are used in addresses to specify lines and in one command ( $\underline{s}$ , see below) to specify a portion of a line which is to be replaced.

If it is desired to use one of the regular expression metacharacters as an ordinary character, that character may be preceded by "\". This also applies to the character bounding the regular expression (often "/") and to "\" itself.

Addresses are constructed as follows. To understand addressing in <u>ed</u> it is necessary to know that at any time there is a <u>current line</u>. Generally speaking, the current line is the last line affected by a command; however, the exact effect on the current line by each command is discussed under the description of the command.

- 1. The character "." addresses the current line.
- 2. The character "^" addresses the line immediately before the current line.
- 3. The character "\$" addresses the last line of the buffer.
- 4. A decimal number <u>n</u> addresses the <u>n</u>th line of the buffer.

l

. (

- 6. A regular expression enclosed in slashes "/" addresses the first line found by searching toward the end of the buffer and stopping at the first line containing a string matching the regular expression. If necessary the search wraps around to the beginning of the buffer.
- 5. A regular expression enclosed in queries "?" addresses the first line found by searching toward the beginning of the buffer and stopping at the first line found containing a string matching the regular expression. If necessary the search wraps around to the end of the buffer.
- 7. An address followed by a plus sign "+" or a minus sign "-" followed by a decimal number specifies that address plus (resp. minus) the indicated number of lines. The plus sign may be omitted.
- 8. "'x" addresses the line associated (marked) with the mark name character "x" which must be a printable character. Lines may be marked with the "k" command described below.

Commands may require zero, one, or two addresses. Commands which require no addresses regard the presence of an address as an error. Commands which accept one or two addresses assume default addresses when insufficient are given. If more addresses are given than such a command requires, the last one or two (depending on what is accepted) are used.

Addresses are separated from each other typically by a comma (,). They may also be separated by a semicolon (;). In this case the current line ". is set to the the previous address before the next address is interpreted. This feature can be used to determine the starting line for forward and backward searches ("/", "?"). The second address of any two-address sequence must correspond to a line following the line corresponding to the first address.

In the following list of <u>ed</u> commands, the default addresses are shown in parentheses. The parentheses are not part of the address, but are used to show that the given addresses are the default.

As mentioned, it is generally illegal for more than one command to appear on a line. However,

- 3 -

ţ

1

any command may be suffixed by "p" (for "print"). In that case, the current line is printed after the command is complete.

(.)a <text>

> The <u>append</u> command reads the given text and appends it after the addressed line. . is left on the last line input, if there were any, otherwise at the addressed line. Address 0 is legal for this command; text is placed at the beginning of the buffer.

#### (.,.)c <text>

The <u>change</u> command deletes the addressed lines, then accepts input text which replaces these lines. "." is left at the last line input; if there were none, it is left at the first line not changed.

### (.,.)d

The <u>d</u>elete command deletes the addressed lines from the buffer. The line originally after the last line deleted becomes the current line; if the lines deleted were originally at the end, the new last line becomes the current line.

#### e filename

The edit command causes the entire contents of the buffer to be deleted, and then the named file to be read in. . is set to the last line of the buffer. The number of characters read is typed. "filename" is remembered for possible use as a default file name in a subsequent  $\underline{r}$  or  $\underline{w}$  command.

#### f filename

The filename command prints the currently remembered file name. If "filename" is given, the currently remembered file name is changed to "filename".

(1,\$)g/regular expression/command list In the global command, the first step is to mark every line which matches the given regular expression. Then for every such line, the given command list is executed with "." initially set to that line. A single command or the first of multiple commands appears on the same line with the global command. All lines of a multi-line list except the last line must be ended

- 4 -

i

۹.,

with "\". a, i, and c commands and associated input are permitted; the "." terminat-ing input mode may be omitted if it would be on the last line of the command list. The (global) commands, g and v, are not permitted in the command list. (.)i <text> This command inserts the given text before the addressed line. . is left at the

last line input; if there were none, at the addressed line. This command differs from the <u>a</u> command only in the placement of the text.

#### (,) kx

- The mark command associates or marks the addressed line with the single character mark name "x". The ten most recent mark names are remembered. The current mark names may be printed with the <u>n</u> command.
- (.,.)1 The list command prints the addressed lines in an unambiguous way. Non-printing char-'acters are over-struck as follows: 1'
  - char prints bs 7 4 - 1

tap	7
ret	€
SI	Ŧ
SO	θ

All characters preceded by a prefix (ESC) character are printed over-struck with without the prefix. Long lines are folded with the sequence \newline.

(.,.)mA

- The move command will reposition the addressed lines after the line addressed by A". The line originally after the last line moved becomes the current line; if the lines moved were originally at the end, the new last line becomes the current line.
- n
- The marknames command will print the current mark names.

(.,.)p

The print command prints the addressed lines. "." is left at the last line printed. The p command may be placed on the same line after any command.

į

. {

ť

NAME SYNOPSIS DESCRIPTION	<pre>od octal dump od name [ origin ] od dumps a file in octal, eight words per line with the origin of the line on the left. If an octal origin is given it is truncated to 0 mod 16 and dumping starts from there, otherwise from 0. Printing continues until an end-of-file condition or until halted by sending an interrupt signal. Since od does not seek, but reads to the desired starting point, od (rather than db) should be used to dump special files.</pre>
FILES SEE ALSO DIAGNOSTICS	 db(I) "?"
BUGS	 ken, dmr

١.

د

i

g

- The guit command causes <u>ed</u> to exit. No automatic write of a file is done.
- (\$)r filename

The <u>read</u> command reads in the given file after the addressed line. If no file name is given, the remembered file name, if any, is used (see <u>e</u> and <u>f</u> commands). The remembered file name is not changed unless "filename" is the very first file name mentioned. Address "0" is legal for <u>r</u> and causes the file to be read at the beginning of the buffer. If the read is successful, the number of characters read is typed. "is left at the last line read in from the file.

(.,.)s/regular expression/replacement/ or. (.,.)s/regular expression/replacement/g The substitute command searches each addressed line for an occurrence of the specified regular expression. On each line in which a match is found, all matched strings are replaced by the replacement specified, if the global replacement indicator "g" appears after the command. Τf the global indicator does not appear, only the first occurrence of the matched string is replaced. It is an error for the substitution to fail on all addressed lines. Any character other than space or new-line may be used instead of "/" to delimit the regular expression and the replacement. is left at the last line substituted.

The ampersand "&" appearing in the replacement is replaced by the regular expression that was matched. The special meaning of "&" in this context may be suppressed by preceding it by "\".

(1,\$)v/regular expression/command list
This command is the same as the global command except that the command list is executed with "." initially set to every line
except those matching the regular expression

## (1,\$)w filename

The write command writes the addressed lines onto the given file. If the file does not exist, it is created mode 17 (readable and writeable by everyone). The remembered file name is <u>not</u> changed unless "filename" is the very first file name Į.

mentioned. If no file name is given, the remembered file name, if any, is used (see  $\underline{e}$  and  $\underline{f}$  commands). . . . . is unchanged. If the command is successful, the number of characters written is typed.

(\$)=

The line number of the addressed line is typed. " is unchanged by this command.

!UNIX command The remainder of the line after the "!" is sent to UNIX to be interpreted as a command. "." is unchanged.

(.+1)<newline>

An address alone on a line causes that line to be printed. A blank line alone is equivalent to ".+1p"; it is useful for stepping through text.

If an interrupt signal (ASCII DEL) is sent, <u>ed</u> will print a "?" and return to its command level.

If invoked with the command name '-', (see <u>init</u>) ed will sign on with the message "Editing system and print "\*" as the command level prompt character.

Ed has size limitations on the maximum number of lines that can be edited, and on the maximum number of characters in a line, in a global's command list, and in a remembered file name. These limitations vary with the physical core size of the PDP11 computer on which <u>ed</u> is being used. The range of limiting sizes for the above mentioned items is; 1300 - 4000 lines per file, 256 - 512 characters per line, 63 - 256 characters per global command list, and 64 characters per file name.

FILES /tmp/etm? temporary /etc/msh to implement the "!" command.

SEE ALSO

DIAGNOSTICS "?" for any error

BUGS

OWNER ken, dmr, jfo

Į.

ţ

(

ļ

. .

· · · ·

NAME	exit terminate command file
SYNOPSIS	<u>exit</u>
DESCR IPT ION	exit performs a <u>seek</u> to the end of its standard input file. Thus, if it is invoked inside a file of commands, upon return from <u>exit</u> the shell will discover an end-of-file and terminate.
FILES	
SEE ALSO	if(I), goto(I), sh(I)
D IAGNOST ICS	
BUGS	
OWNER	dmr

NAME

١

fc -- fortran compiler

SYNOPSIS  $\underline{fc} [-\underline{c}] \text{ sfile}_{1} \cdot \underline{f} \cdot \dots \text{ of ile}_{1} \cdot \dots$ 

DESCRIPTION <u>fc</u> is the UNIX Fortran compiler. It accepts three types of arguments:

Arguments whose names end with ".f" are assumed to be Fortran source programs; they are compiled, and the object program is left on the file sfile...o (i.e. the file whose name is that of the source with ".o" substituted for ".f").

Other arguments (except for "-c") are assumed to be either loader flags, or object programs, typically produced by an earlier <u>fc</u> run, or perhaps libraries of Fortran-compatible routines. These programs, together with the results of any compilations specified, are loaded (in the order given) to produce an executable program with name a,out.

The "-c" argument suppresses the loading phase, as does any syntax error in any of the routines being compiled.

The following is a list of differences between <u>fc</u> and ANSI standard Fortran (also see the BUGS section):

- Arbitrary combination of types is allowed in expressions. Not all combinations are expected to be supported at runtime. All of the normal conversions involving integer, real, double precision and complex are allowed.
- The 'standard' implicit statement is recognized.
- The types doublecomplex, logical\*1, integer\*2 and real\*8 (doubleprecision) are supported.
- 4. <u>&</u> as the first character of a line signals a continuation card.
- 5. <u>c</u> as the first character of a line signals a comment.
- 6. All keywords are recognized in lower case.
- 7. The notion of 'column 7' is not implemented.
- 8. G-format input is free form-- leading blanks are ignored, the first blank after the start of the number terminates the field.

- 1 -

FILES

<

4

1

9. A comma in any numeric or logical input field terminates the field.

10. There is no carriage control on output.

In I/O statements, only unit numbers 0-19 are supported. Unit number <u>nn</u> corresponds to file "fort<u>nn</u>;" (e.g. unit 9 is file "fort09"). For input, the file must exist; for output, it will be created.

input file file.f loaded output a.out temporary (deleted) f.tmp[123] compilation phases /usr/fort/fc[1234] runtime startoff /usr/lib/fr0.0 interpreter library /usr/lib/filib.a builtin functions, etc. /usr/lib/libf.a system library /usr/lib/liba.a

SEE ALSO ANSI standard

DIAGNOSTICS Compile-time diagnostics are given by number. If the source code is available, it is printed with an underline at the current character pointer. Errors possible are:

1	statement too long
2	syntax error in type statement
3	redeclaration
3 4 5	missing ( in array declarator
5	syntax error in dimension statement
6	inappropriate or gratuitous array de-
-	clarator
7	syntax error in subscript bound
8	illegal character
9	common variable is a parameter or already
2	in common
10	common syntax error
11	subroutine/blockdata/function not first
	statement
12	subroutine/function syntax error
13	block data syntax error
	redeclaration in external
14	external syntax error
15	
16	implicit syntax error
17	subscript on non-array
18	incorrect subscript count
19	subscript out of range
20	subscript syntax error
23	equivalence inconsistency
24	equivalence syntax error
25	separate common blocks equivalenced
26	common block illegally extended by
	equivalence
27	common inconsistency created by

•

í

ł

(

i

	equivalence
29	() imbalance in expression
30	expression syntax error
30	illegal variable in equivalence
	non array/function used with
33	subscripts/arguments
	subscripts/arguments
35	goto syntax error
37	illegal return
38	continue, return, stop, call, end, or
	pause syntax error
39	assign syntax error
40	if syntax error
41	I/O syntax error
42	do or I/O iteration error
43	do end missing
50	illegal statement in block data
51	multiply defined labels
52	undefined label
53	dimension mismatch
54	expression syntax error
55	end of statement in hollerith constant
56	array too large
99	β table overflow
101	unrecognized statement
Runtime	diagnostics:
1	invalid log argument
2	bad arg count to amod
3	bad arg count to atan2
2 3 4 5 6	excessive argument to cabs
5	exp too large in cexp
6	bad arg count to cmplx
7	bad arg count to dim
8	excessive argument to exp
9	bad arg count to idim
10	bad arg count to isign
11	bad arg count to mod
12	bad arg count to sign
13	illegal argument to sqrt
14	assigned/computed goto out of range
15	subscript out of range
100	illegal I/O unit number
101	inconsistent use of I/O unit
102	cannot create output file
103	cannot open input file
104	EOF on input file
105	illegal character in format
106	format does not begin with (
107	no conversion in format but non-empty
	list
108	excessive parenthesis depth in format
109	illegal format specification
110	illegal character in input field
111	end of format in hollerith specification

999 unimplemented input conversion The following is a list of those features not yet BUGS implemented: loading of common (a BLOCK DATA program must be written to allocate common). arithmetic statement functions data statements backspace, endfile, rewind runtime binary I/O no scale factors on input dmr, ken

OWNER

(

4

Í

1

1

i

NAME fed -- edit associative memory for form letter

SYNOPSIS <u>fed</u>

DESCRIPTION fed is used to edit a form letter associative memory file, form.m, which consists of named strings. Commands consist of single letters followed by a list of string names separated by a single space and ending with a new line. The conventions of the Shell with respect to '\*' and '?' hold for all commands but <u>e</u> and <u>m</u> where literal string names are expected. The commands are:

e name<sub>1</sub> ...

edit writes the string whose name is name onto a temporary file and executes the system editor <u>ed</u>. On exit from the system editor the temporary file is copied back into the associative memory. Each argument is operated on separately. The sequence of commands to add the string from 'file' to memory with name 'newname' is as follows:

> e newname 0 (printed by ed) r file w q (get out of ed) q (get out of fe)

To dump a string onto a file:

e name 200 (printed by ed) w filename q (get out of ed) q (get out of fe)

d [ name, ... ]

deletes a string and its name from the memory. When called with no arguments <u>d</u> operates in a verbose mode typing each string name and deleting only if a 'y' is typed. A 'q' response returns to command level. Any other response does nothing.

m name, name, ...

(move) changes the name of name, to name, and removes previous string name, if one exists. Several pairs of arguments may be ţ

ť

ĺ

· '.

```
given.
               n [ name<sub>1</sub> ... ]
                    (names) lists the string names in the
                    memory. If called with the optional argu-
                    ments, it just lists those requested.
               p name<sub>1</sub> ...
                     prints the contents of the strings with
                     names given by the arguments.
               q (quit) returns to the system.
                c [p] [f]
                     checks the associative memory file for con-
                                 The optional arguments do the
                     sistency.
                     following:
                        p causes any unaccounted for string to be
                           printed
                         f fixes broken memories by adding
                           unaccounted-for headers to free storage
                           and removing references to released
                           headers from associative memory.
                                 temporary
                 /tmp/ftmp?
FILES
                 form.m associative memory
                 form(I), ed(I), sh(I)
SEE ALSO
                 '?' unknown command
                 'Cannot open temp, file' -- cannot create a tem-
DIAGNOSTICS
                 porary file for ed command
                 'name not in memory.' if string 'name' is not in
                 the associative memory and is used as an argument
                 for <u>d</u> or <u>m</u>.
BUGS
                 rhm,llc
OWNER
```

ţ

(

-

NAME	find find file with given name
SYNOPSIS	find name or number
DESCR IPT ION	find searches the entire file system hierarchy and gives the path names of all files with the specified names or (decimal) i-numbers.
FILES	L
SEE ALSO	
D IAGNOST ICS	
BUGS	
OWNER	dmr

NAME

í

form -- form letter generator

SYNOPSIS form proto arg ...

DESCRIPTION

¥

form generates a form letter from a prototype letter, an associative memory, arguments and in a special case, the current date.

If form is invoked with the proto argument 'x', the associative memory is searched for an entry with name 'x' and the contents filed under that name are used as the prototype. If the search fails, the message "[x]:" is typed on the console and whatever text is typed in from the console, terminated by two new lines, is used as the prototype.

If the prototype argument is missing, '{letter}' is assumed.

Basically, form is a copy process from the prototype to the output file. If an element of the form [n] (where <u>n</u> is a digit from 1 to 9) is encountered, the <u>n</u>th argument <u>arg</u> is inserted in its place, and that argument is then rescanned. If [0] is encountered, the current date is inserted. If the desired argument has not been given, a message of the form "[n]:" is typed. The response typed in then is used for that argument.

If an element of the form [name] or {name} is encountered, the name is looked up in the associative memory. If it is found, the contents of the memory under this name replaces the original element (again rescanned). If the name is not found, a message of the form "[name]:" is typed. The response typed in is used for that element. The response is entered in the memory under the name if the name is enclosed in []. The response is not entered in the memory but is remembered for the duration of the letter if the name is enclosed in {}.

In both of the above cases, the response is typed in by entering arbitrary text terminated by two new lines. Only the first of the two new lines is passed with the text.

If one of the special characters  $[{}] \$  is preceded by a  $\$ , it loses its special character.

If a filE named "forma" already exists in the users directory, "formb" is used as the output file and so forth to "formz".

ł

ĺ

1

è

The file "form.m" is created if none exists. Because form.m is operated on by the disc allocater, it should only be changed by using <u>fed</u>, the form letter editor, or <u>form</u>.

FILES form.m associative memory form? output file (read only)

.

SEE ALSO fed(I), type(I), roff(I)

DIAGNOSTICS "cannot open output file" "cannot open memory file" when the appropriate files cannot be located or created.

BUGS An unbalanced ] or } acts as an end of file but may add a few strange entries to the associative memory.

OWNER rhm,llc

NAME

١

. С,

goto -- command transfer

SYNOPSIS goto label

DESCRIPTION <u>goto</u> is only allowed when the Shell is taking commands from a file. The file is searched (from the beginning) for a line beginning with ": followed by one or more spaces followed by the <u>label</u>. If such a line is found, the <u>goto</u> command returns. Since the read pointer in the command file points to the line after the label, the effect is to cause the Shell to transfer to the labelled line.

":" is a do-nothing command that only serves to place a label.

FILES

SEE ALSO sh(I), :(I)

ميريد بنجين

dmr

DIAGNOST ICS

"goto error", if the input file is a typewriter; "label not found".

BUGS

OWNER

;

ł

{

1 S

if -- conditional command NAME <u>if</u> expr command [ arg<sub>1</sub> ... ] SYNOPSIS if evaluates the expression expr, and if its value is true, executes the given command with DESCRIPTION the given arguments. The following primitives are used to construct the expr: <u>-r</u> file true if the file exists and is readable. true if the file exists and is writable <u>-w</u> file <u>-c</u>file true if the file either exists and is writable, or does not exist and is creatable. true if the strings <u>s1</u> and <u>s2</u> are equal. s1 <u>=</u> s2 true if the strings <u>s1</u> and <u>s2</u> are not s1 != s2 equal. These primaries may be combined with the following operators: 1 unary negation operator <u>-a</u> binary <u>and</u> operator <u>\_\_</u> binary <u>or</u> operator (expr) parentheses for grouping. <u>-a</u> has higher precedence than <u>-0</u>. Notice that all the operators and flags are separate arguments to if and hence must be surrounded by spaces. FILES sh(I) SEE ALSO "if error", if the expression has the wrong syntax; "command not found." DIAGNOSTICS

٠

{

ś

l

i

BUGS "-c" always indicates the file is creatable, even if it isn't.

OWNER dmr

6/12/72

ł

,

} ;

١

4

NAME	istat get inode status
SYNOPSIS	istat inumber
DESCRIPTION	istat gives information about one or more remained in the system /dev/rk0.
	The information is basically in the same for de that for stat(I). All information is self- explanatory except the mode. The mode is a seven-character string whose characters mean the following:
	<pre>1 a: i-node is allocated     u: i-node is free (no file) 2 s: file is small (smaller than 4096 bytes) 1: file is large</pre>
	3 d: file is a directory x: file is executable u: set user ID on execution -: none of the above
	4 r: owner can read -: owner cannot read
	5 w: owner can write -: owner cannot write
	6 r: non-owner can read -: non-owner cannot read
	7 w: non-owner can write -: non-owner cannot write
	The owner is almost always given in symbolic form; however if he cannot be found in "/etc/uids" a number is given.
	<pre>/etc/uids d norm If the number of arguments to stat is not exactly 1 a header is generated identifying the fields of the status information.</pre>
FILES	/etc/uids, /dev/rk0
SEE ALSO	<pre>stat(I) ls(I) (-1 option)</pre>
	"name?" for any error.
D IAGNOST ICS BUGS	<u>istat</u> should take an optional alternate filesys- tem argument.
OWNER	dmr

ŧ

{

ţ

NAME	1d		link editor
	_	~	

SYNOPSIS <u>ld</u> [<u>-usaol</u>] name<sub>1</sub> ···

DESCRIPTION

<u>ld</u> combines several object programs into one; resolves external references; and searches libraries. In the simplest case the names of several object programs are given, and <u>ld</u> combines them, producing an object module which can be either executed or become the input for a further <u>ld</u> run. In the latter case, the "-r" option must be given to preserve the relocation bits.

The argument routines are concatenated in the order specified. The entry point of the output is the beginning of the first routine.

If any argument is a library, it is searched exactly once. Only those routines defining an unresolved external reference are loaded. If a routine from a library references another routine in the library, the referenced routine must appear after the referencing routine in the library. Thus the order of libraries is important.

ld understands several flag arguments which are
written preceded by a -:

- -s "squash" the output, that is, remove the symbol table and relocation bits to save space (but impair the usefulness of the debugger). This information can also be removed by <u>strip</u>.
- -u take the following argument as a symbol and enter it as undefined in the symbol table. This is useful for loading wholly from a library, since initially the symbol table is empty and an unresolved reference is needed to force the loading of the first routine.
- -1 This option is an abbreviation for a library name. "-1" alone stands for "/usr/lib/liba.a", which is the standard system library for assembly language programs. "-1x" stands for "/usr/lib/libx.a" where x is any character. There are libraries for Fortran (x="f"), C (x="c"), Explor (x="e") and B (x="b").
- -x Do not preserve local (non-.globl) symbols in the output symbol table; only enter external symbols. This option saves some space in the output file.

٢

ł

ŧ

1

-r generate relocation bits in the output file so that it can be the subject of another <u>ld</u> run. This file is The output of <u>ld</u> is left on <u>a.out</u>. executable only if no errors occurred during the load. /usr/lib/lib?.a libraries FILES output file a.out as(I), ar(I) SEE ALSO "file not found" -- bad argument DIAGNOSTICS "bad format" -- bad argument "relocation error" -- bad argument (relocation bits corrupted) "multiply defined" -- same symbol defined twice in same load "un" -- stands for "undefined symbol" "symbol not found"-- loader bug "can't move output file"-- can't move temporary to a out file "no relocation bits" -- and input file lacks relocation information "too many symbols" -- too many references to external symbols in a given routine "premature EOF" "can't create l.out"-- cannot make temporary file "multiple entry point"-- more than one entry point specified (not possible yet). Instructions in the data segment are not relocat-BUGS ed properly. dmr OWNER

• - 2 -

4

NAME	ln	 make	a	link

Y.

J,

SYNOPSIS <u>ln</u> name<sub>1</sub> [ name<sub>2</sub> ]

"?"

DESCRIPTION <u>ln</u> creates a link to an existing file name. If name, is given, the link has that name; otherwise it is placed in the current directory and its name is the last component of name.

It is forbidden to link to a directory or to link across file systems.

FILES

1

- {

SEE ALSO rm(I)

DIAGNOSTICS

BUGS

There is nothing particularly wrong with <u>ln</u>, but links don't work right with respect to the backup system: one copy is backed up for each link, and (more serious) in case of a file system reload both copies are restored and the information that a link was involved is lost.

OWNER

ken, dmr

- - -

ĺ

ţ

١

1

NAME	login sign o	onto UNIX					
SYNOPSIS	login [username	e [ password ] ]					
DESCRIPTION	change from one w is the one summar See <u>login</u> (VII) f	I is used when a user initially or it may be used at any time to user to another. The latter case rized above and described here. For how to dial up initially.					
	ask for a user new word. Echoing is the typing of th on the written r	ked without an argument, it will ame, and, if appropriate, a pass- s turned off (if possible) during e password, so it will not appear ecord of the session.					
	After a successful login, accounting files ar updated and the user is informed of the exist of mailbox and message-of-the-day files.						
	Login is recognized by the Shell and executed directly (without forking).						
FILES	/tmp/wtmp mailbox /etc/motd	accounting accounting mail message-of-the-day					
SEE ALSO	login(VII), init	t(VII), getty(VII), mail(I)					
D IAGNOST ICS	"login incorrect bad. "No Shell "no directory:" cilor.	t", if the name or the password is , "cannot open password file," consult a UNIX programming coun-					
BUGS							
OWNER	dmr, ken						

(

ł

ł

J

NAME	ls list contents of directory
SYNOPSIS	<u>ls [ -ltasd</u> ] name <sub>1</sub>
DESCR IPT ION	<u>ls</u> lists the contents of one or more directories under control of several options:
	<pre>l list in long format, giving i-number, mode, owner, size in bytes, and time of last modification for each file. (see stat for format of the mode)</pre>
	t sort by time modified (latest first) instead of by name, as is normal
	a list all entries; usually those beginning with ". are suppressed
	s give size in blocks for each entry
	<pre>d if argument is a directory, list only its     name, not its contents (mostly used with     "-1" to get status on directory)</pre>
	If no argument is given, "." is listed. If an argument is not a directory, its name is given.
FILES	/etc/uids to get user ID's for ls 📲
SEE ALSO	stat(I)
D IAGNOST ICS	"name nonexistent"; "name unreadable"; "name unstatable."
BUGS	

OWNER dmr, ken

(

ţ

(

			•			another	user
	mail	فحلته حيبي	send	mail	το	another	4002
NAME							

SYNOPSIS <u>mail</u> [letter person ... ]

DESCRIPTION <u>mail</u> without an argument searches for a file called <u>mailbox</u>, prints it if present, and asks if it should be saved. If the answer is "y", the mail is renamed <u>mbox</u>, otherwise it is deleted. The answer to the above question may be supplied in the <u>letter</u> argument.

When followed by the names of a letter and one or more people, the letter is appended to each person's <u>mailbox</u>. Each letter is preceded by the sender's name and a postmark.

A <u>person</u> is either the name of an entry in the directory <u>/usr</u>, in which case the mail is sent to  $\frac{usr}{person}/\frac{mailbox}{mailbox}$ , or the path name of a directory, in which case <u>mailbox</u> in that directory is used.

When a user logs in he is informed of the presence of mail.

FILES	/etc/uids mailbox mbox	to map uids input mail saved mail
	MDOX	

SEE ALSO login(I)

DIAGNOSTICS "Who are you?" if the user cannot be identifed for some reason (a bug). "Cannot send to user" if <u>mailbox</u> cannot be opened.

BUGS --

OWNER ken

1

ì

1

 ĺ

NAME	man run off section of UNIX manual
SYNOPSIS	<pre>man title [ section ]</pre>
DESCRIPTION	<u>man</u> is a shell command file that will locate and run off a particular section of this manual. Title is the the desired part of the manual. Section is the section number of the manual. (In Arabic, not Roman numerals.) If section is miss- ing, <u>1</u> is assumed. For example,
	man man
	would reproduce this page.
FILES	/sys/man/man?/*
SEE ALSO	sh(I), roff(I)
DIAGNOSTICS	"File not found", "Usage"
BUGS	
OWNER	ken

. .

l

{

, ,

ı

(

NAME	mesg permit or deny messages				
SYNOPSIS	<u>mesq</u> [ <u>n</u> ][ <u>y</u> ]				
DESCRIPTION	<u>mesq n</u> forbids messages via <u>write</u> by revoking non-user write permission on the user's typewrit- er. <u>mesq</u> y reinstates permission. <u>mesq</u> with no argument reverses the current permission. In all cases the previous state is reported.				
FILES	/dev/tty?				
SEE ALSO	write(I)				
DIAGNOSTICS	"?" if the standard input file is not a typewrit- er				
BUGS	<b></b>				
OWNER	dmr, ken				

•

•

ł

ł

ĺ

1

NAME	mkdir make a directory
SYNOPSIS	<u>mkdir</u> dirname
DESCRIPTION	mkdir creates specified directories in mode 17.
	The standard entries "." and "" are made au- tomatically.
FILES	
SEE ALSO	rmdir(I)
DIAGNOSTICS	"dirname ?"
BUGS	·
OWNER	ken, dmr

į

NAME mount	mount	file	system
------------	-------	------	--------

SYNOPSIS /etc/mount special dir

DESCRIPTION <u>mount</u> announces to the system that a removable file system has been mounted on the device corresponding to special file <u>special</u>. Directory <u>dir</u> (which must exist already) becomes the name of the root of the newly mounted file system.

FILES --

SEE ALSO umount(I)

DIAGNOSTICS "?", if the special file is already in use, cannot be read, or if <u>dir</u> does not exist.

BUGS Should be usable only by the super-user.

It is possilbe to mount the same file system pack twice. This is a very efficient way to destroy a pack.

OWNER ken, dmr

{

2

NAME	mt	 manipulate	magtape
NAME			

SYNOPSIS <u>mt</u> [key] [name ...]

DESCRIPTION <u>mt</u> saves and restores selected portions of the file system hierarchy on magtape. Its actions are controlled by the <u>key</u> argument. The key is a string of characters containing at most one function letter and possibly one or more function modifiers. Other arguments to the command are file or directory names specifying which files are to be dumped, restored, or tabled.

The function portion of the key is specified by one of the following letters:

- r The indicated files and directories, together with all subdirectories, are dumped onto the tape. The old contents of the tape are lost.
- x extracts the named files from the tape to the file system. The owner, mode, and date-modified are restored to what they were when the file was dumped. If no file argument is given, the entire contents of the tape are extracted.
- t lists the names of all files stored on the tape which are the same as or are hierarchically below the file arguments. If no file argument is given, the entire contents of the tape are tabled.
- 1 is the same as <u>t</u> except that an expanded listing is produced giving all the available information about the listed files.

The following characters may be used in addition to the letter which selects the function desired.

- 0, ..., 7 This modifier selects the drive on which the tape is mounted. "0" is the default.
- v Normally <u>mt</u> does its work silently. The <u>v</u> (verbose) option causes it to type the name of each file it treats preceded by a letter to indicate what is happening.

a file is being added x file is being extracted

The  $\underline{v}$  option can be used with  $\underline{r}$  and  $\underline{x}$  only.

f causes new entries copied on tape to be

ş

١

'fake' in that only the entries, not the data associated with the entries are updated. Such fake entries cannot be extracted. Usable only with <u>r</u>.

- w causes <u>mt</u> to pause before treating each file, type the indicative letter and the file name (as with <u>v</u>) and await the user's response. Response <u>y</u> means <u>yes</u>, so the file is treated. Null response means no, and the file does not take part in whatever is being done. Response <u>x</u> means <u>exit</u>; the <u>mt</u> command terminates immediately. In the <u>x</u> function, files previously asked about have been extracted already. With <u>r</u>, no change has been made to the tape.
- m make (create) directories during an x if
  necessary.
- i ignore tape errors. It is suggested that this option be used with caution to read damaged tapes.

FILES /dev/mt?

SEE ALSO tap(I), tap(V)

- DIAGNOSTICS Tape open error Tape read error Tape write error Directory checksum Directory overflow Tape overflow Phase error (a file has changed after it was selected for dumping but before it was dumped)
- BUGS The <u>m</u> option does not work correctly. The <u>i</u> option is not yet implemented.

OWNER ken

-- move or rename a file mν NAME

mv name1 name2 SYNOPSIS

my changes the name of name, by linking to it under the name name, and then unlinking name. If the new name is a directory, the file is moved to that directory under its old name. Direc-DESCRIPTION tories may only be moved within the same parent directory (just renamed).

-FILES

SEE ALSO

DIAGNOSTICS

ł

Since <u>mv</u> is implemented by combinations of <u>link</u> and unlink, it cannot be used to move between BUGS file systems.

ken, dmr OWNER

٩.,

Í

(

l

NAME m6 --- general purpose macro processor

SYNOPSIS <u>m6</u> [ <u>-d</u> arg1 ] [ arg2 [ arg3 ] ]

DESCRIPTION <u>m6</u> takes input from file arg2 (or standard input if arg2 is missing) and places output on file arg3 (or standard output). A working file of definitions, "m.def", is initialized from file arg1 if that is supplied. M6 differs from the standard [1] in these respects:

#trace:, #source: and #end: are not defined.

#meta,arg1,arg2: transfers the role of metacharacter arg1 to character arg2. If two metacharacters become identical thereby, the outcome of further processing is not guaranteed. For example, to make [] {} play the roles of #:<> type

\#meta, <\#>,[:
[meta, <:>,]:
[meta, [substr, <<>>,1,1;, []
[meta, [substr, {{>>,2,1;,}]]

#del,arg1: deletes the definition of macro arg1.

#save: and #rest: save and restore the definition table together with the current metacharacters on file <u>m.def</u>.

#def,arg1,arg2,arg3: works as in the standard with the extension that an integer may be supplied to arg3 to cause the new macro to perform the action of a specified builtin before its replacement text is evaluated. Thus all bultins except #def: can be retrieved even after deletion. Codes for arg3 are:

```
0 - no function
1,2,3,4,5,6 - gt,eq,ge,lt,ne,le
7,8 - seq,sne
9,10,11,12,13 - add,sub,mpy,div,exp
20 - if
21,22 - def,copy'
23 - meta
24 - size
25 - substr
26,27 - go,gobk
28 - del
29 - dnl
30,31 - save,rest
```

FILES

m.def--working file of definitions /sys/lang/mdir/m6a--m6 processor proper (/bin/m6 is only an initializer) /sys/lang/mdir/m6b--default initialization for

i

í

(

,

m.def

SEE ALSO [1] M6 reference

SEE ALSO	[1] MO TELETONOO
DIAGNOSTICS	"err" a bug, an unknown builtin or a bad de- finition table "oprd"can't open input or initial definitions "opwr"can't open output "ovc" overflow of nested calls "ova" overflow of nested arguments "ovd" overflow of definitions "rdd" can't read definition table "wrd" can't write definition table, either on #save: or on garbage collection
BUGS	Characters in internal tables are stored one per word. They really should be packed to improve capacity. For want of space (and because of unpacked formats) no file arguments have been provided to #save: or #rest: Again to save space, garbage collection makes calls on #save: and #rest: and so overwrites m.def.
OWNER	doug

- 2 -

,

i

ł

i

.

NAME	nm print name list
SYNOPSIS	<u>nm</u> [name]
DESCRIPTION	<u>nm</u> prints the symbol table from the output file of an assembler or loader run. Each symbol name is preceded by its value (blanks if undefined) and one of the letters "U" (undefined) "A" (abso- lute) "T" (text segment symbol), "D" (data seg- ment symbol), or "B" (bss segment symbol). Glo- bal symbols have their first character under- lined. The output is sorted alphabetically. If no file is given, the symbols in <u>a,out</u> are listed.
FILES	a.out
SEE ALSO	as(I), ld(I)
DIAGNOSTICS	، ن
BUGS	
OWNER	dmr, ken

NAME od octal o	aump
-----------------	------

od name [ origin ] SYNOPSIS

od dumps a file in octal, eight words per line with the origin of the line on the left. If an DESCRIPTION octal origin is given it is truncated to 0 mod 16 and dumping starts from there, otherwise from 0. Printing continues until an end-of-file condition or until halted by sending an interrupt signal. Since od does not seek, but reads to the desired starting point, od (rather than db) should be

used to dump special files.

FILES

ţ

i

db(I)SEE ALSO

"?" DIAGNOSTICS

BUGS

ken, dmr OWNER

!

ſ

ì

## NAME opr -- off line print

SYNOPSIS <u>opr</u> file<sub>1</sub> ...

DESCRIPTION Opr will arrange to have the 201 data phone daemon submit a job to the Honeywell 6070 to print the file arguments. Normally, each file is printed in the state it is found when the data phone daemon reads it. If a particular file argument is preceded by <u>+</u> then <u>opr</u> will make a copy for the daemon to print. If the file argument is preceded by <u>-</u> then opr will unlink the file.

FILES	/usr/dpd/* /etc/ident /etc/dpd	spool area personal ident cards daemon
-------	--------------------------------------	--

SEE ALSO dpd(I), ident(V)

DIAGNOSTICS

BUGS Since all but the <u>+</u> option in <u>opr</u> is implemented with <u>links</u>, one cannot use these options for files not in <u>/usr</u>.

<u>opr</u> should recognize <u>+</u> and <u>-</u> alone and apply them to all subsequent arguments.

OWNER ken

## 6/12/72

ţ

~ {

١ 1

1

NAME	ov		overlay	pages
------	----	--	---------	-------

jfo

<u>ov</u> filename SYNOPSIS

ov is a postprocessor for producing double column formatted text when using nroff(I). ov assumes DESCRIPTION that the named file contains an even number of 66 line pages and literally overlays successive pairs of pages.

FILES	none

nroff(I) SEE ALSO

DIAGNOSTICS none

Other page lengths should be permitted. BUGS

OWNER

\_ 1 \_

{

9 1

(

(

NAME	pr print file
SYNOPSIS	pr [ -lcm ] name,
DESCR IPT ION	<u>pr</u> produces a printed listing of one or more files. The output is separated into pages headed by the name of the file, a date, and the page number.
	The optional flag <u>-l</u> causes each page to contain 78 lines instead of the standard 66 to accommo- date legal size paper.
	The optional flags $\underline{-c}$ (current date) and $\underline{-m}$ (modified date) specify which date will head all subsequent files. $\underline{-m}$ is default.
	Interconsole messages via $write(I)$ are forbidden during a <u>pr</u> .
FILES	/dev/tty? to suspend messages.
SEE ALSO	<pre>cat(I), cp(I), mesg(I)</pre>
DIAGNOSTICS	<pre> (files not found are ignored)</pre>
BUGS	none
OWNER	ken, dmr

· .

٠

3/15/72

*.*'

ł

(

NAME	rew rewind tape
SYNOPSIS	<u>rew</u> [ digit ]
DESCR IPT ION	<u>rew</u> rewinds DECtape drives. The digit is the logical tape number, and should range from 0 to 7. A missing digit indicates drive 0.
FILES	/dev/tap?
SEE ALSO	
DIAGNOSTICS	"?" if there is no tape mounted on the indicated drive or if the file cannot be opened.
BUGS	
OWNER	ken, dmr

NAME

Ç

Į

ļ

١

Ą

1

rm -- remove (unlink) files

SYNOPSIS <u>rm</u> name<sub>1</sub> ····

DESCRIPTION <u>rm</u> removes the entries for one or more files from a directory. If an entry was the last link to the file, the file is destroyed. Removal of a file requires write permission in its directory, but neither read nor write permission on the file itself.

Directories cannot be removed by <u>rm</u>; cf. <u>rmdir</u>.

FILES none

SEE ALSO rmdir(I)

DIAGNOSTICS If the file cannot be removed or does not exist, the name of the file followed by a question mark is typed.

BUGS <u>rm</u> probably should ask whether a read-only file is really to be removed.

OWNER ken, dmr

(

Į

ï

(

ł

)

\$

NAME	rmdir remove directory
SYNOPSIS	<u>rmdir</u> dir <sub>1</sub>
DESCR IPT ION	<u>rmdir</u> removes (deletes) directories. The direc- tory must be empty (except for the standard en- tries "." and "", which <u>rmdir</u> itself removes). Write permission is required in the directory in which the directory appears.
FILES	none
SEE ALSO	
DIAGNOSTICS	"dir?" is printed if directory <u>dir</u> cannot be found, is not a directory, or is not removable.
	"dir directory not empty" is printed if <u>dir</u> has entries other than ". or
BUGS	
OWNER	ken, dmr

- 1 -

J

.

Ć

Į

•

(

ļ

NAME	roff format text
SYNOPSIS	<u>roff</u> [ <u>+</u> number1 ] [ <u>-</u> number2 ] [ <u>-stop</u> ] name <sub>1</sub>
DESCRIPTION	<u>roff</u> formats text according to control lines embedded in the text in files name, Encountering a nonexistent file terminates print- ing. The optional argument "+number1" causes printing to begin at the first page numbered number1; the optional argument "-number2" stops printing after the page numbered number2. The optional argument "-stop" or "-S" causes printing to stop before each page including the first to allow paper manipulation; printing is resumed upon receipt of an interrupt signal. An inter- rupt signal received during printing terminates all printing. Incoming interconsole messages are turned off during printing, and the original mes- sage acceptance state is restored upon termina- tion.
	the state that the second s
FILES	<pre>/etc/suftab suffix hyphenation tables /tmp/rtm? temporary</pre>
SEE ALSO	[1] (See J. F. Ossanna)
DIAGNOSTICS	none
BUGS	
OWNER	jfo

NAME

- 1

ł

salv -- file system salvage

<u>/etc/salv</u> SYNOPSIS

salv will reconstruct the file system /dev/rk0 to a consistent state. This is the first step in DESCR IPT ION putting things together after a bad crash. Salv performs the following functions:

A valid free list is constructed.

All bad pointers in the file system are zeroed.

All duplicate pointers to the same block are resolved by changing one of the pointers to point at a new block containing a copy of the data.

After a salv, a warm boot must be performed instantly to effect the change made. (Because the salv works on the disk copy of the file system super-block, and the core copy is unaffected.)

After a salv, files may be safely created and removed without causing more trouble. However, it is more likely than not that directories are corrupted as well, so a <u>ds</u> should be performed.

/dev/rk0 FILES

check(I), ds(I) SEE ALSO

\_

DIAGNOSTICS

The file system to be salvaged should be an argu-BUGS ment.

ken OWNER

í

NAME sh -- shell (command interpreter)

SYNOPSIS <u>sh</u> [name [ arg<sub>1</sub> ... [ arg<sub>9</sub> ] ] ]

DESCR IPT ION

<u>sh</u> is the standard command interpreter. It is the program which reads and arranges the execution of the command lines typed by most users. It may itself be called as a command to interpret files of commands. Before discussing the arguments to the shell used as a command, the structure of command lines themselves will be given.

### Command lines

Command lines are sequences of commands separated by command delimiters. Each command is a sequence of non-blank command arguments separated by blanks. The first argument specifies the name of a command to be executed. Except for certain types of special arguments discussed below, the arguments other than the command name are simply passed to the invoked command.

If the first argument is the name of an executable file, it is invoked; otherwise the string "/bin/" is prepended to the argument. (In this way the standard commands, which reside in "/bin", are found.) If the "/bin" file exists, but is not executable, it is used by the shell as a command file. That is to say it is executed as input as though it were typed from the console. If all attempts fail, a diagnostic is printed.

The remaining non-special arguments are simply passed to the command without further interpretation by the shell.

### Command delimiters

There are three command delimiters: the newline, ";", and "&". The semicolon ";" specifies sequential execution of the commands so separated; that is,

coma; comb

causes the execution first of command <u>coma</u>, then of <u>comb</u>. The ampersand & causes simultaneous execution:

### coma & comb

- 1 -

causes <u>coma</u> to be called, followed immediately by <u>comb</u> without waiting for <u>coma</u> to finish. Thus <u>coma</u> and <u>comb</u> execute simultaneously. As a special case,

١.

ţ

ĺ

#### coma &

causes <u>coma</u> to be executed and the shell immediately to request another command without waiting for <u>coma</u>.

### Termination Reporting

If a command (not followed by "&") terminates abnormally, a message is printed. (All terminations other than exit and interrupt are considered abnormal.) The following is a list of the abnormal termination messages:

```
Bus error
Trace trap
Illegal instruction
IOT trap
Power fail trap
EMT trap
Bad system call
Quit
Error
```

If a core image is produced, " -- Core dumped" is appended to the appropriate message.

Redirection of I/O

Three character sequences cause the immediately following string to be interpreted as a special argument to the shell itself, not passed to the command.

An argument of the form "<arg" causes the file arg to be used as the standard input file of the given command.

An argument of the form ">arg" causes file "arg" to be used as the standard output file for the given command. "Arg" is created if it did not exist, and in any case is truncated at the outset.

An argument of the form ">>arg" causes file "arg" to be used as the standard output for the given command. If "arg" did not exist, it is created; if it did exist, the command output is appended to the file.

## Generation of argument lists

If any argument contains any of the characters "?", "\*" or '[', it is treated specially as follows. The current directory is searched for files which <u>match</u> the given argument. í

ŧ

í

1

The character "\*" in an argument matches any string of characters in a file name (including the null string).

The character "?" matches any single character in a file name.

Each "[" must be paired with a matching "]". The characters between "[" and "]" specify a class of characters. It matches any single character in a file name which is in the class. An ordinary character in the brackets specifies that character to be in the class. A pair of characters separated by "-" specifies each character lexically greater than or equal to the first and less than or equal to the second member of the pair is to be included in the class. If the first member of the pair lexically exceeds the second, the second member is the sole character specified.

Other characters match only the same character in the file name.

For example, "\*" matches all file names; "?" matches all one-character file names; "[ab]\*.s" matches all file names beginning with "a" or "b" and ending with ".s"; ?[zi-m]" matches all twocharacter file names ending with "z" or the letters "i" through "m".

If the argument with "\*" or "?" also contains a "/", a slightly different procedure is used: instead of the current directory, the directory used is the one obtained by taking the argument up to the last "/" before a "\*" or "?". The matching process matches the remainder of the argument after this "/" against the files in the derived directory. For example: "/usr/dmr/a\*.s" matches all files in directory "/usr/dmr" which begin with "a" and end with ".s".

In any event, a list of names is obtained which match the argument. This list is sorted into alphabetical order, and the resulting sequence of arguments replaces the single argument containing the "\*", "[", or "?". The same process is carried out for each argument (the resulting lists are <u>not</u> merged) and finally the command is called with the resulting list of arguments.

For example: directory /usr/dmr contains the files a1.s, a2.s, ..., a9.s. From any directory, the command

as /usr/dmr/a?.s

1

i

calls <u>as</u> with arguments /usr/dmr/a1.s, /usr/dmr/a2.s, ... /usr/dmr/a9.s in that order.

#### Quoting

The character "\" causes the immediately following character to lose any special meaning it may have to the shell; in this way "<", ">", and other characters meaningful to the shell may be passed as part of arguments. A special case of this feature allows the continuation of commands onto more than one line: a new-line preceded by "\" is translated into a blank.

Sequences of characters enclosed in double (") or single (') quotes are also taken literally.

### Argument passing

When the shell is invoked as a command, it has additional string processing capabilities. Recall that the form in which the shell is invoked is

sh [ name [ arg<sub>1</sub> ... [ arg<sub>9</sub> ] ] ]

The <u>name</u> is the name of a file which will be read and interpreted. If not given, this subinstance of the shell will continue to read the standard input file.

In the file, character sequences of the form "\$n", where <u>n</u> is a digit 0, ..., 9, are replaced by the <u>n</u>th argument to the invocation of the shell (arg<sub>n</sub>). "\$0" is replaced by <u>name</u>.

#### End of file

An end-of-file in the shell's input causes it to exit. A side effect of this fact means that the way to log out from UNIX is to type an end of file.

### Special commands

Two commands are treated specially by the shell.

"Chdir" is done without spawning a new process by executing the sys chdir primitive.

"Login" is done by executing /bin/login without creating a new process.

These peculiarities are inexorably imposed upon the shell by the basic structure of the UNIX process control system. It is a rewarding exercise {

to work out why.

Command file errors

Any shell-detected error in a file of commands causes that shell to cease executing that file. /etc/glob, which interprets "\*", "?", and "[". FILES "The UNIX Time-sharing System", which gives the SEE ALSO theory of operation of the shell. "Input not found", when a command file is speci-DIAGNOSTICS fied which cannot be read; Arg count", if the number of arguments to the chdir pseudo-command is not exactly 1, or if "\*" ?", or "[" is used in appropriately; "Bad directory", if the directory given in "chdir" cannot be switched to; "Try again", if no new process can be created to execute the specified command; ""' imbalance", if single or double quotes are not matched; Input file", if an argument after "<" cannot be read; Output file", if an argument after ">" or ">>" cannot be written (or created); No command", if the specified command cannot be executed. "No match", if no arguments are generated for a command which contains "\*", "?", or "[". Termination messages described above. If any argument contains a quoted "\*", "?", or [", then all instances of these characters must BUGS . be quoted. This is because sh calls the glob routine whenever an unquoted "\*". "?", or "[" is noticed; the fact that other instances of these characters occurred quoted is not noticed by glob.

OWNER

dmr, ken

ţ

į

ĺ

sort -- sort a file NAME

----

----

sort input output SYNOPSIS

sort will sort the input file and write the sorted file on the output file. The sort is line-DESCR IPT ION by-line in increasing ASCII collating sequence.

Space required is 6\*number-of-lines in bytes.

/tmp/stm? FILES

SEE ALSO

DIAGNOSTICS

Sort does not put a maximum on the size of file that it sorts. Thus a bus error will occur if BUGS too large an input file is supplied.

·

The input is copied to a temporary file. Thus the maximum file that can be sorted is the maximum non-special file (currently 64K bytes.)

dmr, ken OWNER

1

ł

1

stat -- get file status NAME stat name, ... SYNOPSIS stat gives several kinds of information about one DESCR IPT ION or more files: i-number access mode number of links owner size in bytes date and time of last modification name (useful when several files are named) All information is self-explanatory except the mode. The mode is a six-character string whose characters mean the following: 1 s: file is small (smaller than 4096 bytes) 1: file is large 2 d: file is a directory x: file is executable u: set user ID on execution -: none of the above 3 r: owner can read -: owner cannot read 4 w: owner can write -: owner cannot write 5 r: non-owner can read -: non-owner cannot read 6 w: non-owner can write -: non-owner cannot write The owner is almost always given in symbolic form; however if he cannot be found in /etc/uids" a number is given. If the number of arguments to stat is not exactly 1 a header is generated identifying the fields of the status information. /etc/uids FILES istat(I), ls(I) (-l option) SEE ALSO "name?" for any error. DIAGNOSTICS dmr OWNER

۸

3/15/72

Ę

1

ł

strip -- remove symbols and relocation bits NAME

strip name ... SYNOPSIS

strip removes the symbol table and relocation bits ordinarily attached to the output of the DESCRIPTION assembler and loader. This is useful to save space after a program has been debugged.

The effect of strip is the same as use of the -s option of <u>ld</u>.

temporary file /tmp/stm? FILES

ld(I), as(I) SEE ALSO

\_\_\_\_

Diagnostics are given for: non-existent argument; inability to create temporary file; DIAGNOSTICS improper format (not an object file); inability to re-read temporary file.

BUGS

dmr OWNER

6/12/72

(

ŧ

ł

)

1

ł

ł

(

NAME	stty set teletype options
SYNOPSIS	stty option
DESCR IPT ION	Stty will set certain I/O options on the current output teletype. The option strings are selected from the following set:
	evenallow even parityevendisallow even parity.oddallow odd parity-odddisallow odd parityrawraw input (no erase/kill)-canonnegate raw mode (erase/kill)canonallow (and echo) cr for lf.nlnegate cr modecrecho back every character typed.full"-halfdo not echo characters as typeducaseanot map case-lcasemap tabs-spacecalculate cr and tab delaysdelayno cr/tab delaysebcdicebcdic ball conversion (2741 only)-correscorrespondence ball conversion (2741 only)
FILES	standard output.
SEE ALSO	stty(II)
DIAGNOSTICS	"Bad options"
BUGS	
OWNER	jfo

1

NAME su -- become privileged user

SYNOPSIS <u>su</u> password

DESCRIPTION su allows one to become the super-user, who has all sorts of marvelous powers. In order for su to do its magic, the user must pass as an argument a password. If the password is correct, su will execute the shell with the UID set to that of the super-user. To restore normal UID privileges, type an end-of-file to the super-user shell.

FILES

SEE ALSO sh(I)

\_\_\_\_

DIAGNOSTICS "Sorry" if password is wrong

BUGS

OWNER dmr, ken

i

1

NAME	sum	 sum	file

-----

SYNOPSIS <u>sum</u> name<sub>1</sub> ...

DESCRIPTION <u>sum</u> sums the contents of one or more files. A separate sum is printed for each file specified, along with the number of whole or partial 512word blocks read.

In practice, <u>sum</u> is often used to verify that all of a special file can be read without error.

FILES none

SEE ALSO

- DIAGNOSTICS "oprd" if the file cannot opened; "?" if if an error is discovered during the read.
- BUGS none
- OWNER ken

2

6/12/72

,

.

•

(

l

(

NAME	tacct login accounting by date
SYNOPSIS	tacct [ wtmp ]
DESCR IPT ION	tacct will produce a printout giving daily con- nect time and total number of connects for all transactions found in the <u>wtmp</u> file. If no wtmp file is given, <u>/tmp/wtmp</u> is used.
FILES	/tmp/wtmp
SEE ALSO	<pre>init(VII), acct(I), login(I), wtmp(V)</pre>
DIAGNOSTICS	"Cannot open 'wtmp'"
BUGS	acct(I) and tacct(I) should be compined
OWNER	dmr, ken
	•

.

Ý

NAME	tap		manipulate	DECtap
NAME	tap	مرور مرور	manipulate	DECta

SYNOPSIS <u>tap</u> [key] [name ...]

DESCR IPTION

tap saves and restores selected portions of the file system hierarchy on DECtape. Its actions are controlled by the <u>key</u> argument. The key is a string of characters containing at most one function letter and possibly one or more function modifiers. Other arguments to the command are file or directory names specifying which files are to be dumped, restored, or tabled.

The function portion of the key is specified by one of the following letters:

- r The indicated files and directories, together with all subdirectories, are dumped onto the tape. If files with the same names already exist, they are replaced (hence the "r"). "Same" is determined by string comparison, so "./abc" can never be the same as "/usr/dmr/abc" even if "/usr/dmr" is the current directory. If no file argument is given, "." is the default.
- u updates the tape. <u>u</u> is the same as <u>r</u>, but a file is replaced only if its modification date is later than the date stored on the tape; that is to say, if it has changed since it was dumped. <u>u</u> is the default command if none is given.
- d deletes the named files and directories from the tape. At least one file argument must be given.
- x extracts the named files from the tape to the file system. The owner, mode, and date-modified are restored to what they were when the file was dumped. If no file argument is given, the entire contents of the tape are extracted.
- t lists the names of all files stored on the tape which are the same as or are hierarchically below the file arguments. If no file argument is given, the entire contents of the tape are tabled.
- 1 is the same as <u>t</u> except that an expanded listing is produced giving all the available information about the listed files.

The following characters may be used in addition to the letter which selects the function desired. 1

- 0, ..., 7 This modifier selects the drive on which the tape is mounted. "0" is the default.
- v Normally <u>tap</u> does its work silently. The <u>v</u> (verbose) option causes it to type the name of each file it treats preceded by a letter to indicate what is happening.
  - r file is being replaced
    a file is being added (not there before)
    x file is being extracted
    d file is being deleted

The  $\underline{v}$  option can be used with  $\underline{r}$ ,  $\underline{u}$ ,  $\underline{d}$ , and  $\underline{x}$  only.

- c means a fresh dump is being created; the tape directory will be zeroed before beginning. Usable only with <u>r</u> and <u>u</u>.
- f causes new entries copied on tape to be 'fake' in that only the entries, not the data associated with the entries are updated. Such fake entries cannot be extracted. Usable only with <u>r</u> and <u>u</u>.
- w causes tap to pause before treating each file, type the indicative letter and the file name (as with v) and await the user's response. Response "y" means "yes", so the file is treated. Null response means "no", and the file does not take part in whatever is being done. Response "x" means "exit"; the tap command terminates immediately. In the x function, files previously asked about have been extracted already. With r, u, and d no change has been made to the tape.
- m make (create) directories during an <u>x</u> if necessary.
- i ignore tape errors. It is suggested that this option be used with caution to read damaged tapes.

/dev/tap?

SEE ALSO mt(I)

FILES

DIAGNOSTICS Tape open error Tape read error Tape write erro

Tape read error Tape write error Directory checksum Directory overflow

- 2 -:

1

í

1

1

Tape overflow Phase error (a file has changed after it was selected for dumping but before it was dumped)

BUGS The <u>m</u> option does not work correctly. The <u>i</u> option is not yet implemented.

OWNER ken

ţ

NAME	tm provide time information
SYNOPSIS	<u>tm</u> [ command arg <sub>1</sub> ]
DESCR IPT ION	tm is used to provide timing information. When used without an argument, output like the follow- ing is given:

tim	371:51:09	2:00.8
ovh	20:00:33	17.0
	13:43:20	4.6
dsk	27:14:35	4.5
idl	533:08:03	1:33.3
usr	24:53:50	1.2
$\mathtt{der}$	0, 54	0, 0

The first column of numbers gives totals in the named categories since the last time the system was cold-booted; the second column gives the changes since the last time <u>tm</u> was invoked. The <u>tim</u> row is total real time (hours:minutes: seconds); unlike the other times, its origin is the creation date of <u>tm</u>'s temporary file. <u>ovh</u> is time spent executing in the system; <u>swp</u> is time waiting for swap I/O; <u>dsk</u> is time spent waiting for file system disk I/O; <u>idl</u> is idle time; <u>usr</u> is user execution time; <u>der</u> is RF disk error count (left number) and RK disk error count (right number).

tm can be invoked with arguments which are assumed to constitute a command to be timed. In this case the output is as follows:

tim	2.7
ovh	0.3
swp	0.5
dsk	1.8
idl	0.0
usr	0.0

The given times represent the number of seconds spent in each category during execution of the command.

FILES /tmp/ttmp, /dev/rf0 (for absolute times) contains the information used to calculate the differential times.

SEE ALSO file system(V)

DIAGNOSTICS "?" if the command cannot be executed; "can't creat temp file" if trouble with <u>ttmp</u>; "cant read super-block" if times cannot be read from system.

(1) when invoked with a command argument,

BUGS

1

•

**ا**مع

everything going on at the moment is counted, not just the command itself. (2) Two users doing  $\underline{tm}$  simultaneously interfere with each other's use of the temporary file.

OWNER

(

~ 1

1

1

ken, dmr

•

Í

i.

1

NAME	tss interface to Honeywell TSS			
SYNOPSIS	tss			
DESCRIPTION	tss will call the Honeywell 6070 on the 201 data phone. It will then go into direct access with TSS. Output generated by TSS is typed on the standard output and input requested by TSS is read from the standard input with UNIX typing conventions.			
	An interrupt signal (ASCII DEL) is transmitted as a "break" to TSS.			
	Input lines beginning with <u>!</u> are interpreted as UNIX commands. Input lines beginning with <u>are</u> interpreted as commands to the interface routine.			
	<pre>~<file file<="" from="" input="" insert="" named="" pre="" unix=""></file></pre>			
	>file deliver tss output to named UNIX file			
	~p pop the output file			
	q disconnect from tss (quit)			
	r file receive from HIS routine CSR/DACCOPY			
	s file send file to HIS routine CSR/DACCOPY			
	Ascii files may be most efficiently transmitted using the HIS routine CSR/DACCOPY in this fashion. Underlined text comes from TSS. AFTname is the 6070 file to be dealt with.			
	SYSTEM? CSR/DACCOPY (s) AFTname Send Encoded File s file			
	SYSTEM? CSR/DACCOPY (r) AFTname Receive Encoded File r file			
FILES	/dev/dn0, /dev/dp0			
SEE ALSO				
DIAGNOSTICS	DONE when communication is broken.			
BUGS	When diagnostic problems occur, <u>tss</u> exits rather abruptly.			
OWNER	csr			

- 1 -

-

Ç

(

ł

1

NAME	tty get tty name
SYNOPSIS	tty
DESCRIPTION	tty gives the name of the user's typewriter in the form "ttyn" for <u>n</u> a digit. The actual path name is then "/dev/ttyn".
FILES	
SEE ALSO	
DIAGNOSTICS	"not a tty" if the standard input file is not a typewriter.
BUGS	
OWNER	dmr, ken

# NAME type --- type on single sheet paper

SYNOPSIS type name ...

DESCRIPTION <u>type</u> copys its input files to the standard output. After every 66 lines, type stops and reads the standard input for a new line character before continuing. This allows time for insertion of single sheet paper.

FILES

ł

ť

ł

١

SEE ALSO

DIAGNOSTICS .

BUGS --

OWNER dmr

(

į

(

{

NAME SYNOPSIS DESCR IPTION	umount dismount file system <u>/etc/umount</u> special <u>umount</u> announces to the system that the removable file system previously mounted on special file
	<u>special</u> is to be removed. Only the super-user may issue this command.
FILES	
SEE ALSO	mount(I)
DIAGNOSTICS	"?"
BUGS	This command is not, in fact, restricted to the super-user.
OWNER	ken, dmr

t

.

1

(

(

ļ

NAME	un undefined symbols
SYNOPSIS	<u>un</u> [ name ]
DESCR IPT ION	un prints a list of undefined symbols from an assembly or loader run. If the file argument is not specified, <u>a.out</u> is the default. Names are listed alphabetically except that non-global sym- bols come first. Undefined global symbols (un- resolved external references) have their first character underlined.
FILES	a.out
SEE ALSO	as(I), ld(I)
DIAGNOSTICS	"?" if the file cannot be found.
BUGS	
OWN ER	dmr, ken

10		get	(English)	word	count
Ň	IC	1C	ıc get	vc get (English)	vc get (English) word

SYNOPSIS wc name ...

DESCRIPTION wc provides a count of the words, text lines, and roff control lines for each argument file.

A text line is a sequence of characters not beginning with "." and ended by a new-line. A <u>roff</u> control line is a line beginning with ". A word is a sequence of characters bounded by the beginning of a line, by the end of a line, or by a blank or a tab.

FILES

ĺ

(

Į.

SEE ALSO roff(I)

----

DIAGNOSTICS none; arguments not found are ignored.

BUGS

OWNER jfo

(

à

1

NAME who -- who is on the system

SYNOPSIS who [ who-file ]

· 24

DESCRIPTION who, without an argument, lists the name, typewriter channel, and login time for each current UNIX user.

Without an argument, who examines the /tmp/utmp file to obtain its information. If a file is given, that file is examined. Typically the given file will be /tmp/wtmp, which contains a record of all the logins since it was created. Then who will list all logins and logouts since the creation of the wtmp file.

FILES /tmp/utmp

SEE ALSO login(I), init(VII)

DIAGNOSTICS "?" if a named file cannot be read.

BUGS -

OWNER dmr, ken

- 1 -

1

write -- write to another user NAME

write user SYNOPSIS

DESCRIPTION

write copies lines from your typewriter to that of another user. When first called, write sends the message

message from yourname...

The recipient of the message should write back at this point. Communication continues until an end of file is read from the typewriter or an interrupt is sent. At that point write writes "EOT" on the other terminal.

Permission to write may be denied or granted by use of the mesq command. At the outset writing is allowed. Certain commands, in particular roff and pr, disallow messages in order to prevent messy output.

If the character "!" is found at the beginning of a line, write calls the mini-shell msh to execute the rest of the line as a command.

The following protocol is suggested for using write: When you first write to another user, wait for him to write back before starting to send. Each party should end each message with a dis-tinctive signal ("(o)" for "over" is convention-al) that the other may reply. "(oo)" (for "over al) that the other may reply. "(oo)" (for "over and out") is suggested when conversation is about to be terminated.

FILES	/tmp/utmp	to find user
L TUPO	/etc/msh	to execute !

mesg(I), msh(VII) SEE ALSO

"user not logged in"; "permission denied".

DIAGNOSTICS

BUGS

dmr, ken OWNER

NAME break -- set program break

SYNOPSIS sys break; addr / break = 17.

DESCRIPTION <u>break</u> sets the system's idea of the highest location used by the program to <u>addr</u>. Locations greater than <u>addr</u> and below the stack pointer are not swapped and are thus liable to unexpected modification.

> An argument of 0 is taken to mean 8K words. If the argument is higher than the stack pointer the entire user core area is swapped.

When a program begins execution via <u>exec</u> the break is set at the highest location defined by the program and data storage areas. Ordinarily, therefore, only programs with growing data areas need to use <u>break</u>.

FILES

SEE ALSO exec(II)

DIAGNOSTICS none; strange addresses cause the break to be set to include all of core.

BUGS -

ð

1

)

)

OWNER ken, dmr

ł

)

1

NAME	cemt		catch	emt	traps	
------	------	--	-------	-----	-------	--

SYNOPSIS sys cemt; arg / cemt = 29.

DESCRIPTION This call allows one to catch traps resulting from the <u>emt</u> instruction. Arg is a location within the program; <u>emt</u> traps are sent to that location. The normal effect of <u>emt</u> traps may be restored by giving an <u>arg</u> equal to 0.

Prior to the use of this call, the result of an  $\underline{emt}$  instruction is a simulated  $\underline{rts}$  instruction. The operand field is interpreted as a register, and an  $\underline{rts}$  instruction is simulated for that register (after verifying that various registers have appropriate values). This feature is useful for debugging, since the most dangerous program bugs usually involve an  $\underline{rts}$  with bad data on the stack or in a register.

FILES ---SEE ALSO ---DIAGNOSTICS ---BUGS ---OWNER ken, dmr

NAME	chdir	هې وي	change	working	directory	
T/1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						

SYNOPSIS sys chdir; dirname / chdir = 12.

DESCRIPTION <u>dirname</u> is address of the pathname of a directory, terminated by a 0 byte. <u>chdir</u> causes this directory to become the current working directory.

FILES

{

ţ

É

SEE ALSO chdir(I)

-

----

DIAGNOSTICS The error bit (c-bit) is set if the given name is not that of a directory.

BUGS

OWN ER	ken,	dmr
OWNER	<i></i> ,	

- 1 -

.

NAME	chmod	حک میں	change	mode	of	file	

SYNOPSIS sys chmod; name; mode / chmod = 15.

DESCRIPTION The file whose name is given as the nullterminated string pointed to by <u>name</u> has its mode changed to <u>mode</u>. Modes are constructed by <u>or</u>ing together some combination of the following:

> 01 write, non-owner 02 read, non-owner 04 write, owner 10 read, owner 20 executable 40 set user ID on execution

Only the owner of a file (or the super-user) may change the mode.

FILES

ĺ

ş

SEE ALSO chmod(I)

DIAGNOSTICS Error bit (c-bit) set if <u>name</u> cannot be found or if current user is neither the owner of the file nor the super-user.

BUGS

OWNER ken, dmr

\_\_\_\_

NAME chown -- change owner of file

SYNOPSIS sys chown; name; owner / chown = 16.

DESCRIPTION The file whose name is given by the nullterminated string pointed to by <u>name</u> has its owner changed to <u>owner</u>. Only the present owner of a file (or the super-user) may donate the file to another user. Also, one may not change the owner of a file with the set-user-ID bit on, otherwise one could create Trojan Horses able to misuse other's files.

FILES

i

SEE ALSO chown(I), uids(V)

----

DIAGNOSTICS The error bit (c-bit) is set on illegal owner changes.

BUGS --

OWNER ken, dmr

NAME close -- close a file

SYNOPSIS (file descriptor in r0) sys close / close = 6.

DESCRIPTION Given a file descriptor such as returned from an open or creat call, <u>close</u> closes the associated file. A close of all files is automatic on exit, but since processes are limited to 10 simultaneously open files, <u>close</u> is necessary to programs which deal with many files.

FILES

Ĭ.

(

SEE ALSO creat(II), open(II)

DIAGNOSTICS The error bit (c-bit) is set for an unknown file descriptor.

BUGS

OWNER ken, dmr

(

í.

NAME creat -- create a new file

SYNOPSIS sys creat; name; mode / creat = 8. (file descriptor in r0)

DESCRIPTION <u>creat</u> creates a new file or prepares to rewrite an existing file called <u>name</u>; <u>name</u> is the address of a null-terminated string. If the file did not exist, it is given mode <u>mode</u>; if it did exist, its mode and owner remain unchanged but it is truncated to 0 length.

The file is also opened for writing, and its file descriptor is returned in r0.

The mode given is arbitrary; it need not allow writing. This feature is used by programs which deal with temporary files of fixed names. The creation is done with a mode that forbids writing. Then if a second instance of the program attempts a <u>creat</u>, an error is returned and the program knows that the name is unusable for the moment.

If the last link to an open file is removed, the file is not destroyed until the file is closed.

FILES

SEE ALSO write(II), close(II)

----

DIAGNOSTICS The error bit (c-bit) may be set if: a needed directory is not readable; the file does not exist and the directory in which it is to be created is not writable; the file does exist and is unwritable; the file is a directory.

BUGS

OWNER ken, dmr

(

í

NAME exec -- execute a file

DESCRIPTION <u>exec</u> overlays the calling process with the named file, then transfers to the beginning of the core image of the file. The first argument to <u>exec</u> is a pointer to the name of the file to be executed. The second is the address of a list of pointers to arguments to be passed to the file. Conventionally, the first argument is the name of the file. Each pointer addresses a string terminated by a null byte.

There can be no return from the file; the calling core image is lost.

The program break is set from the executed file; see the format of a.out.

Once the called file starts execution, the arguments are passed as follows. The stack pointer points to the number of arguments. Just above this number is a list of pointers to the argument strings.

sp-> nargs
arg1
arg1
arg1: <arg1\0>

argn: <argn\0>

The arguments are placed as high as possible in core: just below 60000(8).

Files remain open across <u>exec</u> calls. However, the illegal instruction, <u>emt</u>, quit, and interrupt trap specifications are reset to the standard values. (See <u>ilgins</u>, <u>cemt</u>, <u>quit</u>, <u>intr</u>.)

Each user has a <u>real</u> user ID and an <u>effective</u> user ID (The real ID identifies the person using the system; the effective ID determines his access privileges.) <u>exec</u> changes the effective user ID to the owner of the executed file if the file has the set-user-ID mode. The real user ID is not affected. ţ

ſ

í

FIL	ES		

SEE ALSO fork(II)

\_

DIAGNOSTICS If the file cannot be read or if it is not executable, a return from <u>exec</u> constitutes the diagnostic. The error bit (c-bit) is set.

BUGS

OWNER ken, dmr

NAME exit -- terminate process

SYNOPSIS (status in r0) sys exit / exit = 1

-----

----

DESCRIPTION <u>exit</u> is the normal means of terminating a process. All files are closed and the parent process is notified if it is executing a <u>wait</u>. The low byte of r0 is available as status to the parent process.

This call can never return.

FILES

L

1

SEE ALSO wait(II)

DIAGNOSTICS

BUGS --

OWNER ken, dmr

NAME fork -- spawn new process

SYNOPSIS sys fork / fork = 2. (new process return) (old process return)

DESCRIPTION fork is the only way new processes are created. The new process's core image is a copy of that of the caller of fork; the only distinction is the return location and the fact that r0 in the old process contains the process ID of the new process. This process ID is used by wait.

FILES

ł

Ĺ

SEE ALSO wait(II), exec(II)

----

DIAGNOSTICS The error bit (c-bit) is set in the old process if a new process could not be created because of lack of process space.

BUGS See wait(II) for a subtle bug in process destruction.

OWNER ken, dmr

ł

1

ĺ

NAME fstat -- get status of open file

SYNOPSIS (file descriptor in r0) sys fstat; buf / fstat = 28.

DESCRIPTION This call is identical to <u>stat</u>, except that it operates on open files instead of files given by name. It is most often used to get the status of the standard input and output files, whose names are unknown.

FILES -- I

SEE ALSO stat(II)

DIAGNOSTICS The error bit (c-bit) is set if the file descriptor is unknown.

BUGS --

OWNER ken, dmr

t

ł,

l

NAME getuid -- get user identification

SYNOPSIS sys getuid / getuid = 24. (user ID in r0)

DESCRIPTION <u>qetuid</u> returns the real user ID of the current process. The real user ID identifies the person who is logged in, in contradistinction to the effective user ID, which determines his access permission at each moment. It is thus useful to programs which operate using the "set user ID" mode, to find out who invoked them.

FILES /etc/uids can be used to map the user ID number into a name.

SEE ALSO setuid(II)

DIAGNOSTICS

BUGS --

OWNER ken, dmr

NAME gtty -- get typewriter status

SYNOPSIS (file descriptor in r0)

sys gtty; arg / gtty = 32.

arg: .=.+6

. . .

-

DESCRIPTION <u>gtty</u> stores in the three words addressed by <u>arg</u> the status of the typewriter whose file descriptor is given in r0. The format is the same as that passed by <u>stty</u>.

FILES

Į

ł

SEE ALSO stty(II)

DIAGNOSTICS Error bit (c-bit) is set if the file descriptor does not refer to a typewriter.

BUGS

OWNER ken, dmr

(

ţ

ĺ

NAME hog -- set program in low priority

SYNOPSIS sys hog / hog = 34.

DESCRIPTION The currently executing process is set into the lowest priority execution queue. Background jobs that execute a very long time should do this. A higher priority will be reinstituted as soon as the process is dismissed for any reason other than quantum overflow.

- FILES --
- SEE ALSO ---
- DIAGNOSTICS ---
- BUGS --
- OWNER ken, dmr

NAME ilgins -- catch illegal instruction trap

SYNOPSIS sys ilgins; arg / ilgins = 33.

DESCRIPTION <u>ilgins</u> allows a program to catch illegal instruction traps. If <u>arg</u> is zero, the normal instruction trap handling is done: the process is terminated and a core image is produced. If <u>arg</u> is a location within the program, control is passed to <u>arg</u> when the trap occurs.

This call is used to implement the floating point simulator, which catches and interprets 11/45 floating point instructions.

FILES

SEE ALSO fptrap(III)

DIAGNOSTICS

. .

BUGS

)

OWNER ken, dmr

ł

NAME	intr	هيد جين	set	interrupt	handling
------	------	---------	-----	-----------	----------

SYNOPSIS sys intr; arg / intr = 27.

DESCRIPTION When <u>arg</u> is 0, interrupts (ASCII DELETE) are ignored. When <u>arg</u> is 1, interrupts cause their normal result, that is, force an <u>exit</u>. When <u>arg</u> is a location within the program, control is transferred to that location when an interrupt occurs.

> After an interrupt is caught, it is possible to resume execution by means of an <u>rti</u> instruction; however, great care must be exercised, since all I/O is terminated abruptly upon an interrupt. In particular, reads of the typewriter tend to return with O characters read, thus simulating an end of file.

FILES

SEE ALSO quit(II)

----

DIAGNOSTICS

BUGS It should be easier to resume after an interrupt, but I don't know how to make it work.

OWNER ken, dmr

NAME kill -- destroy process

\_\_\_\_

SYNOPSIS (process number in r0) sys kill / kill = 37.; not in assembler

DESCRIPTION <u>kill</u> destroys a process, given its process number. The process leaves a core image.

This call is restricted to the super-user, and is intended only to kill an otherwise unstoppable process.

FILES

1

SEE ALSO --

DIAGNOSTICS c-bit set if user is not the super-user, or if process does not exist.

BUGS <u>kill</u> has been known to be ineffective.

OWNER ken, dmr

NAME link -- link to a file

SYNOPSIS sys link; name<sub>1</sub>; name<sub>2</sub> / link = 9.

DESCRIPTION A link to <u>name</u> is created; the link has name <u>name</u>. Either name may be an arbitrary path name.

FILES

١

3

À

)

1 |} |}

1

1

SEE ALSO link(I), unlink(II)

----

----

DIAGNOSTICS The error bit (c-bit) is set when <u>name</u>, cannot be found; when <u>name</u>, already exists; when the directory of <u>name</u>, cannot be written; when an attempt is made to link to a directory by a user other than the super-user.

- 1 -

BUGS

OWNER ken, dmr

í

έ

ł

1

NAME makdir -- make a directory

SYNOPSIS sys makdir; name; mode / makdir = 14.

DESCRIPTION <u>makdir</u> creates an empty directory whose name is the null-terminated string pointed to by <u>name</u>. The mode of the directory is <u>mode</u>. The special entries . and .. are not present.

makdir can only be invoked by the super-user.

FILES

SEE ALSO mkdir(I)

\_\_\_\_

DIAGNOSTICS Error bit (c-bit) is set if the directory already exists or if the user is not the super-user.

BUGS --

OWNER ken, dmr

NAME mdate -- set modified date on file

SYNOPSIS (time to AC-MQ) sys mdate; file / mdate = 30.

DESCRIPTION <u>File</u> is the address of a null-terminated string giving the name of a file. The modified time of the file is set to the time given in the AC-MQ registers.

This call is allowed only to the super-user or to the owner of the file.

FILES

(

ł

I.

SEE ALSO

DIAGNOSTICS Error bit is set if the user is not the superuser or if the file cannot be found.

BUGS

OWNER ken, dmr

\_\_\_

\_

NAME mount mount file system
------------------------------

SYNOPSIS sys mount; special; name / mount = 21.

DESCRIPTION <u>mount</u> announces to the system that a removable file system has been mounted on special file <u>special</u>; from now on, references to file <u>name</u> will refer to the root file on the newly mounted file system. <u>Special</u> and <u>name</u> are pointers to null-terminated strings containing the appropriate path names.

> Name must exist already. If it had useful contents, they are inaccessible while the file system is mounted.

Almost always, <u>name</u> should be a directory so that an entire file system, not just one file, may exist on the removable device.

FILES

í

(

SEE ALSO mount(I), umount(II)

\_\_\_

DIAGNOSTICS Error bit (c-bit) set if <u>special</u> is inaccessible or <u>dir</u> does not exist.

BUGS At most two removable devices can be mounted at a time. The use of this call should be restricted to the super-user.

OWNER ken, dmr

1

NAME open -- open for reading or writing

SYNOPSIS sys open; name; mode / open = 5. (descriptor in r0)

DESCRIPTION <u>open</u> opens the file <u>name</u> for reading (if <u>mode</u> is 0) or writing (if <u>mode</u> is non-zero). <u>name</u> is the address of a string of ASCII characters representing a path name, terminated by a null character.

The file descriptor should be saved for subsequent calls to read (or write) and close.

In both the read and write case the file pointer is set to the beginning of the file.

If the last link to an open file is removed, the file is not destroyed until it is closed.

FILES

SEE ALSO creat(II), read(II), write(II), close(II)

DIAGNOSTICS The error bit (c-bit) is set if the file does not exist, if one of the necessary directories does not exist or is unreadable, or if the file is not readable.

BUGS --

OWNER ken, dmr

----

NAME	quit		turn	off	quit	signal	
------	------	--	------	-----	------	--------	--

SYNOPSIS sys quit; flag / quit = 26.

DESCRIPTION When <u>flag</u> is 0, this call disables quit signals from the typewriter (ASCII FS). When <u>flag</u> is 1, quits are re-enabled, and cause execution to cease and a core image to be produced. When <u>flag</u> is an address in the program, a quit causes control to be sent to that address.

> Quits should be turned off only with due consideration.

FILES

ł

1

SEE ALSO intr(II)

DIAGNOSTICS --

BUGS ---

OWNER ken, dmr

NAME	read		read	from	file
------	------	--	------	------	------

- SYNOPSIS (file descriptor in r0) sys read; buffer; nchars / read = 3. (nread in r0)
- DESCRIPTION A file descriptor is a word returned from a successful <u>open</u> call.

Buffer is the location of <u>nchars</u> contiguous bytes into which the input will be placed. It is not guaranteed that all <u>nchars</u> bytes will be read, however; for example if the file refers to a typewriter at most one line will be returned. In any event the number of characters read is returned in r0.

If r0 returns with value 0, then end-of-file has been reached.

FILES

ş

SEE ALSO open(II)

DIAGNOSTICS As mentioned, r0 is 0 on return when the end of the file has been reached. If the read was otherwise unsuccessful the error bit (c-bit) is set. Many conditions, all rare, can generate an error: physical I/O errors, bad buffer address, preposterous <u>nchars</u>, file descriptor not that of an input file.

BUGS --

OWNER ken, dmr

í

NAME	rele		release	processor
------	------	--	---------	-----------

SYNOPSIS sys rele / rele = 0; not in assembler

DESCRIPTION This call causes the process to be swapped out immediately if another process wants to run. Its main reason for being is internal to the system, namely to implement timer-runout swaps. However, it can be used beneficially by programs which wish to loop for some reason without consuming more processor time than necessary.

FILES --

SEE ALSO --

DIAGNOSTICS

BUGS --

OWNER ken, dmr

ŧ

NAME seek -- move read/write pointer

SYNOPSIS (file descriptor in r0) sys seek; offset; ptrname / seek = 19.

DESCRIPTION The file descriptor refers to a file open for reading or writing. The read (or write) pointer for the file is set as follows:

if ptrname is 0, the pointer is set to offset.

if <u>ptrname</u> is 1, the pointer is set to its current location plus <u>offset</u>.

if <u>ptrname</u> is 2, the pointer is set to the size of the file plus <u>offset</u>.

FILES -

SEE ALSO tell(II)

DIAGNOSTICS The error bit (c-bit) is set for an undefined file descriptor.

BUGS A file can conceptually be as large as 2\*\*20 bytes. Clearly only 2\*\*16 bytes can be addressed by <u>seek</u>. The problem is most acute on the tape files and RK and RF. Something is going to be done about this.

OWNER ken, dmr

Ę

1

NAME setuid -- set process ID

SYNOPSIS (process ID in r0) sys setuid / setuid = 23.

- DESCRIPTION The user ID of the current process is set to the argument in r0. Both the effective and the real user ID are set. This call is only permitted to the super-user or if r0 is the real user ID.
- FILES --

SEE ALSO getuid(II)

DIAGNOSTICS Error bit (c-bit) is set if the current user ID is not that of the super-user.

BUGS --

OWNER ken, dmr

NAME sleep -- stop execution for interval

SYNOPSIS (60ths of a second in r0) sys sleep / sleep = 35.; not in assembler

DESCRIPTION The current process is suspended from execution for the number of 60ths of a second specified by the contents of register 0.

FILES

í

SEE ALSO

DIAGNOSTICS -

BUGS Due to the implementation, the sleep interval is only accurate to 256 60ths of a second (4.26 sec). Even then, the process is placed on a low priority queue and must be scheduled.

OWNER ken, dmr

(

Ę

ĺ

NAME	stat get file status			
SYNOPSIS	sys stat; name; buf / stat = 18.			
DESCRIPTION	<u>name</u> points to a null-terminated string naming a file; <u>buf</u> is the address of a 34(10) byte buffer into which information is placed concerning the file. It is unnecessary to have any permissions at all with respect to the file, but all direc- tories leading to the file must be readable.			
	After stat, buf has the following format:			
	<pre>buf, +1 i-number +2,+3 flags (see below) +4 number of links +5 user ID of owner +6,+7 size in bytes +8,+9 first indirect block or contents block *22,+23 eighth indirect block or contents block +24,+25,+26,+27 creation time +28,+29,+30,+31 modification time +32,+33 unused The flags are as follows: 100000 used (always on) 040000 directory</pre>			
	020000 file has been modified (always on) 010000 large file 000040 set user ID 000020 executable 000010 read, owner 000004 write, owner 000002 read, non-owner 000001 write, non-owner			
FILES				
SEE ALSO	<pre>stat(I), fstat(II)</pre>			
DIAGNOSTICS	Error bit (c-bit) is set if the file cannot be found.			
BUGS	The format is going to change someday.			
OWN ER	ken, dmr			

.

.

•

ί,

- t

. (

3/15/72	
NAME	stime set time
SYNOPSIS	(time in AC-MQ) sys stime / stime = 25.
DESCRIPTION	stime sets the system's idea of the time and date. Only the super-user may use this call.
FILES	
FILES SEE ALSO	 date(I), time(II)
	<pre> date(I), time(II) Error bit (c-bit) set if user is not the super- user.</pre>
SEE ALSO	Error bit (c-bit) set if user is not the super-

l

NAME stty -- set mode of typewriter

SYNOPSIS (file descriptor in r0) sys stty; arg / stty = 31.

arg: dcrsr; dcpsr; mode

DESCRIPTION <u>stty</u> sets mode bits for a typewriter whose file descriptor is passed in r0. First, the system delays until the typewriter is quiescent. Then, the argument <u>dcrsr</u> is placed into the typewriter's receiver control and status register, and <u>dcpsr</u> is placed in the transmitter control and status register. The DC-11 manual must be consulted for the format of these words. For the purpose of this call, the most important rôle of these arguments is to adjust to the speed of the typewriter.

The <u>mode</u> arguments contains several bits which determine the system's treatment of the typewriter:

200	even parity allowed on input (e.g. for m37s)
100	add parity allowed on input
040	raw mode: wake up on all characters
020	map CR into LF; echo LF or CR as LF-CR
010	echo (full duplex)
004	map upper case to lower on input (e. g. M33)
002	echo and print tabs as spaces (e. g. CRTs)

001 inhibit all function delays (e. g. CRTS)

Characters with the wrong parity, as determined by bits 200 and 100, are ignored.

In raw mode, every character is passed back immediately to the program. No erase or kill processing is done; the end-of-file character (EOT), the interrupt character (DELETE) and the quit character (FS) are not treated specially.

Mode 020 causes input carriage returns to be turned into new-lines; input of either CR or LF causes LF-CR both to be echoed (used for GE TermiNet 300's and other terminals without the newline function).

Additional bits in the high order byte of the mode argument are used to indicate that the terminal is an IBM 2741 and to specify 2741 modes. These mode bits are:

400 terminal is an IBM 2741

- 1000 the 2741 has the transmit interrupt feature (currently ignored)
- 2000 use correspondence code conversion on output

ł

4000	use correspondence c	ode conversion	on input
	(currently ignored)	,	

Normal input and output code conversion for 2741s is EBCDIC (e. g. 963 ball and corresponding keyboard). The presence of the transmit interrupt feature permits the system to do read-ahead while no output is in progress. In 2741 mode, the low order bits 331 are ignored.

FILES --

SEE ALSO stty(I), gtty(II)

DIAGNOSTICS The error bit (c-bit) is set if the file descriptor does not refer to a typewriter.

BUGS This call should be used with care. It is all too easy to turn off your typewriter.

OWNER ken, dmr

NAME sync -- update super-block

\_\_\_\_

----

SYNOPSIS sys sync / sync = 36.; not in assembler

DESCRIPTION <u>sync</u> causes the super block for all file systems to be written out. It is only necessary on systems in which this writing may be delayed for a long time, i.e., those which incorporate hardware protection facilities.

It should be used by programs which examine a file system, for example check, df, tm, etc.

FILES

Î

{

SEE ALSO --

DIAGNOSTICS --

BUGS

OWNER ken

1

į

ı.

NAME	tell get file pointer
SYNOPSIS	(file descriptor in r0) sys tell; offset; ptrname / tell = 20. (value returned in r0)
DESCRIPTION	The file descriptor refers to an open file. The value returned in r0 is one of:
	if <u>ptrname</u> is 0, the value returned is <u>offset;</u>
	if <u>ptrname</u> is 1, the value is the current pointer plus <u>offset;</u>
	if <u>ptrname</u> is 2, the value returned is the number of bytes in the file plus <u>offset</u> .
FILES	
SEE ALSO	seek(II)
DIAGNOSTICS	The error bit (c-bit) is set if the file descrip- tor is unknown.
BUGS	Tell doesn't work. Complain if you need it.

OWNER ken, dmr

- 1 -

J

,

.

ĺ

ł

1

,

.

.

(

NAME	time get time of year
SYNOPSIS	<pre>sys time / time = 13. (time AC-MQ)</pre>
DESCRIPTION	time returns the time since 00:00:00, Jan. 1, 1971, measured in sixtieths of a second. The high order word is in the AC register and the low order is in the MQ.
FILES	
SEE ALSO	<pre>date(I), stime(II)</pre>
DIAGNOSTICS	
BUGS	The chronological-minded user will note that 2**32 sixtieths of a second is only about 2.5 years.
OWN ER	ken, dmr

NAME umount	خريد ويبيه	dismount	file	system	
-------------	------------	----------	------	--------	--

sys umount; special / umount = 22. SYNOPSIS

umount announces to the system that special file special is no longer to contain a removable file DESCRIPTION system. The file associated with the special file reverts to its ordinary interpretation (see mount). The user must take care that all activity on the

file system has ceased.

FILES

l

umount(I), mount(II) SEE ALSO

----

Error bit (c-bit) set if no file system was DIAGNOSTICS mounted on the special file.

Use of this call should be restricted to the BUGS super-user.

ken, dmr OWN ER

NAME unlink -- remove directory entry

SYNOPSIS sys unlink; name / unlink = 10.

- DESCRIPTION <u>Name</u> points to a null-terminated string. <u>Unlink</u> removes the entry for the file pointed to by <u>name</u> from its directory. If this entry was the last link to the file, the contents of the file are freed and the file is destroyed. If, however, the file was open in any process, the actual destruction is delayed until it is closed, even though the directory entry has disappeared.
- FILES

SEE ALSO rm(I), rmdir(I), link(II)

- DIAGNOSTICS The error bit (c-bit) is set to indicate that the file does not exist or that its directory cannot be written. Write permission is not required on the file itself. It is also illegal to unlink a directory (except for the super-user).
- BUGS Probably write permission should be required to remove the last link to a file, but this gets in other problems (namely, one can donate an undeletable file to someone else).

If the system crashes while a file is waiting to be deleted because it is open, the space is lost.

OWNER ken, dmr

í

í

NAME wait -- wait for process to die

SYNOPSIS sys wait / wait = 7. (process ID in r0) (termination status/user status in MQ)

DESCRIPTION <u>wait</u> causes its caller to delay until one of its child processes terminates. If any child has already died, return is immediate; if there are no children, return is immediate with the error bit set. In the case of several children several waits are needed to learn of all the deaths.

> If the error bit is not set on return, the MQ high byte contains the low byte of the child process r0 when it terminated. The MQ low byte contains the termination status of the process from the following list:

0	exit
1	bus error
2	trace trap
3	illegal instruction
4	IOT trap
5	power fail trap
6	EMT trap
7	bad system call
8	quit
9	interrupt
10	kill (see kill(II))
+16	core image produced

FILES

SEE ALSO exit(II), fork(II)

DIAGNOSTICS error bit (c-bit) on if no children not previously waited for.

BUGS

)

A child which dies but is never waited for is not really gone in that it still consumes disk swap and system table space. This can make it impossible to create new processes. The bug can be noticed when several "&" separators are given to the shell not followed by a command without an ampersand. Ordinarily things clean themselves up when an ordinary command is typed, but it is possible to get into a situation in which no commands are accepted, so no <u>waits</u> are done; the system is then hung.

The fix, probably, is to have a new kind of <u>fork</u> which creates a process for which no <u>wait</u> is necessary (or possible); also to limit the number of active or inactive descendants allowed to a process.

(

l

NAME	write		write	on	file	
------	-------	--	-------	----	------	--

SYNOPSIS (file descriptor in r0) sys write; buffer; nchars / write = 4. (number written in r0)

DESCRIPTION A file descriptor is a word returned from a successful <u>open</u> or <u>creat</u> call.

<u>buffer</u> is the address of <u>nchars</u> contiguous bytes which are written on the output file. The number of characters actually written is returned in r0. It should be regarded as an error if this is not the same as requested.

For disk and tape files, writes which are multiples of 512 characters long and begin on a 512-byte boundary are more efficient than any others.

FILES

SEE ALSO creat(II), open(II)

DIAGNOSTICS The error bit (c-bit) is set on an error: bad descriptor, buffer address, or count. physical I/O errors;

BUGS

OWNER ken, dmr

NAME atan -- arc tangent function

SYNOPSIS jsr r5,atan[2]

DESCRIPTION The atan entry returns the arc tangent of fr0 in fr0. The range is zero to pi/2. The atan2 entry returns the arc tangent of fr0/fr1 in fr0. The range is -pi to pi. The floating point simulation should be active in either floating or double mode, but in single precision integer mode.

FILES kept in /usr/lib/liba.a

SEE ALSO fptrap(III)

DIAGNOSTICS

BUGS

ł.

ł

í

ł

OWNER rhm, dmr, ken

- 1 - `

NAME atof -- ascii to floating

SYNOPSIS jsr r5, atof; subr

DESCRIPTION <u>atof</u> will convert an ascii stream to a floating number returned in fr0. The subroutine <u>subr</u> is called on r5 for each character of the ascii stream. <u>subr</u> should return the character in r0. The first character not used in the conversion is left in r0. The floating point simulation should be active in either floating or double mode, but in single precision integer mode.

FILES kept in /usr/lib/liba.a

SEE ALSO fptrap(III)

DIAGNOSTICS -

<

!

BUGS The subroutine <u>subr</u> should not disturb any registers.

OWNER ken

ł٠

ĺ

Ĺ

i

NAME atoi -- ascii to integer

SYNOPSIS jsr r5, atoi; subr

- DESCRIPTION <u>atoi</u> will convert an ascii stream to a binary number returned in mq. The subroutine <u>subr</u> is called on r5 for each character of the ascii stream. <u>subr</u> should return the character in r0. The first character not used in the conversion is left in r0.
- FILES kept in /usr/lib/liba.a

-----

SEE ALSO

DIAGNOSTICS ---

BUGS The subroutine <u>subr</u> should not disturb any registers.

OWNER ken

.

ĺ

- (

1

(

	and sometants
NAME	const floating point constants
SYNOPSIS	
DESCRIPTION	The following floating point constants are correctly represented in double precision.
	one 1.0 pi2 0.5*3.1415
FILES	kept in /usr/lib/liba.a
SEE ALSO	fptrap(III)
DIAGNOSTICS	
BUGS	
OWNER	rhm, dmr, ken

•

## CTIME (III)

3/15/72

É

(

Į

•

ł.

NAME	ctime convert date and time to ASCII
SYNOPSIS	(move time to AC-MQ) mov \$buffer,r0 jsr pc,ctime
DESCRIPTION	The buffer is 15 characters long. The time has the format
	Oct 9 17:32:24
	The input time is in the AC and MQ registers in the form returned by <u>sys time</u> .
FILES	kept in /usr/lib/liba.a
SEE ALSO	<pre>ptime(III), time(II)</pre>
DIAGNOSTICS	
BUGS	
OWNER	dmr

- 1 -

1

•

3/15/72

ł

Ŷ

i

1

.-

NAME	exp exponential function
SYNOPSIS	jsr r5,exp
DESCR IPTION	The exponential of frO is returned in frO. The floating point simulation should be active in either floating or double mode, but in single precision integer mode.
FILES	kept in /usr/lib/liba.a
SEE ALSO	fptrap(III)
DIAGNOSTICS	The c-bit is set if the result is not represent- able.
BUGS	<b></b>
OWNER	rhm, dmr, ken

þ

1

1

١

NAME fptrap -- PDP-11/45 floating point simulator

SYNOPSIS .globl fptrap sys ilgins; fptrap

DESCRIPTION <u>fptrap</u> is a package which picks up instructions which are illegal for the PDP-11/20, and if they correspond to 11/45 floating point instructions, simulates their operation. The following instructions are supported:

```
cfcc
setf
seti
setd
setl
         fdst -
clrf
        fsrc
tstf
         fdst
absf
         fdst
neqf
mulf fsrc,fr
modf fsrc,fr
addf fsrc,fr
        fsrc,fr (=ldf)
movf
        fr,fdst (=stf)
movf
subf
        fsrc,fr
        fsrc,fr
cmpf
divf fsrc,fr
movfi fr,dst (=stcfi)
movif src,fr (=ldcif)
movfo fr,fdst (=stcxy)
movof fsrc, fr (=ldcyx)
```

Here <u>src</u> and <u>dst</u> stand for source and destination, <u>fsrc</u> and <u>fdst</u> for floating source and destination, and <u>fr</u> for floating register. Notice that the names of several of the opcodes have changed. The only strange instruction is <u>movf</u>, which turns into <u>stf</u> if its source operand is a floating register, and into <u>ldf</u> if not.

The simulator sets the floating condition codes on both <u>ldf</u> and <u>stf</u>. The 11/45 hardware does not set the fcc on stf.

Short and long format for both floating point numbers and integers is supported. Truncation mode is always in effect. Traps for overflow and other arithmetic errors are not supported. Illegal instructions or addresses cause a simulated trap so that a core image is produced.

The condition code bits are maintained correctly.

For floating-point source operands, immediate mode ((pc)+) is not supported, since the

PDP-11/45 handbook is not clear on what to do about it.

After an arithmetic error the result is generally meaningless.

The arithmetic is always done in doubleprecision, so exact but unrounded results are to be expected in single-precision mode. Double precision results are probably less correct than the hardware will be.

The lower parts of the floating registers become meaningless during single-precision operations.

FILES kept in /usr/lib/liba.a

SEE ALSO PDP-11/45 handbook, ilgins(II)

DIAGNOSTICS trap, c-bit, v-bit

BUGS see above

OWNER ken, dmr

- 2 -

3/15/72

## NAME ftoa -- floating to ascii conversion

SYNOPSIS jsr r5,ftoa; subr

- DESCRIPTION <u>ftoa</u> will convert the floating point number in fr0 into ascii in the form [-]d.ddddddd<u>e</u>[-]dd\*. The floating point simulator should be active in either floating or double mode, but in single integer mode. For each character generated by ftoa, the subroutine <u>subr</u> is called on register r5 with the character in r0.
- FILES kept in /usr/lib/liba.a

SEE ALSO fptrap(III)

DIAGNOSTICS

١

•

BUGS The subroutine <u>subr</u> should not disturb any registers.

OWNER ken

	CONNECT, GERTS (III)			
3/15/72				
NAME	connect, gerts Gerts communication over 201			
SYNOPSIS	jsr r5,connect (error return)/			
	jsr r5,gerts; fc; oc; ibuf; obuf (error return)			
DESCRIPTION	The GECOS GERTS interface is so bad that a description here is inappropriate. Anyone need- ing to use this interface should contact the own- er.			
FILES	/dev/dn0, /dev/dp0 kept in /usr/lib/liba.a			
SEE ALSO	dn(IV), dp(IV), HIS documentation			
DIAGNOSTICS				
BUGS				
OWNER	ken			

•

ł

i

)

1

1

1 ł

Ì

7

3/15/72

. (

getw, getc, fopen -- buffered input NAME \$filename,r0 mov SYNOPSIS r5, fopen; iobuf jsr r5,getc; iobuf jsr (character in r0) r5,getw; iobuf jsr (word in r0) These routines are used to provide a buffered DESCRIPTION input facility. iobuf is the address of a 518(10) byte buffer area whose contents are maintained by these routines. Its format is: / file descriptor •=•+2 ioptr: / characters left in buffer •=•+2 / ptr to next character •=•+2 / the buffer .=.+512. fopen may be called initially to open the file. On return, the error bit (c-bit) is set if the open failed. If fopen is never called, get will read from the standard input file. getc returns the next byte from the file in r0. The error bit is set on end of file or a read error. getw returns the next word in r0. getc and getw may be used alternately; there are no odd/even problems. iobuf must be provided by the user; it must be on a word boundary. kept in /usr/lib/liba.a FILES open(II), read(II), putc(III) SEE ALSO c-bit set on EOF or error DIAGNOSTICS BUGS dmr OWNER

6/12/72

ł

(

NAME hypot -- calculate hypotenuse (A in fr0)

- SYNOPSIS (A in fr0) (B in fr0) jsr r5, hypot
- DESCRIPTION The square root of fr0\*fr0 + fr1\*fr1 is returned in fr0. The calculation is done in such a way that overflow will not occur unless the answer is not representable in floating point.

The floating point simulator should be active in either single or double mode.

FILES kept in /usr/lib/liba.a

SEE ALSO fptrap(III)

DIAGNOSTICS The c-bit is set if the result cannot be represented.

BUGS

OWNER ken, dmr

3/15/72

i

(

NAME	itoa integer to ascii conversion		
SYNOPSIS	jsr r5,itoa; subr		
DESCRIPTION	<u>itoa</u> will convert the number in r0 into ascii decimal possibly preceded by a - sign. For each character generated by itoa, the subroutine <u>subr</u> is called on register r5 with the character in r0.		
FILES	kept in /usr/lib/liba.a		
SEE ALSO			
DIAGNOSTICS			
BUGS	The subroutine <u>subr</u> should not disturb any regis- ters.		
OWNER	ken		

LOG (III)

...

3/15/72

NAME log -- logarithm base e

SYNOPSIS jsr r5,log

DESCRIPTION The logarithm base e of fr0 is returned in fr0. The floating point simulation should be active in either floating or double mode, but in single precision integer mode.

FILES kept in /usr/lib/liba.a

SEE ALSO fptrap

DIAGNOSTICS The error bit (c-bit) is set if the input argument is less than or equal to zero.

BUGS

Į

OWNER ken

.

,

ł

1

1

NAME	mesg write message on typewriter		
SYNOPSIS	jsr r5,mesg; <now is="" the="" time\0="">; .even</now>		
DESCRIPTION	mesq writes the string immediately following its call onto the standard output file. The string is terminated by a O byte.		
FILES	kept in /usr/lib/liba.a		
SEE ALSO			
DIAGNOSTICS			
BUGS			
OWN ER	ken, dmr		

NAME nlist -- get entries from name list

SYNOPSIS jsr r5, nlist; file; list

DESCRIPTION <u>nlist</u> will examine the name list in an assembler output file and selectively extract a list of values. The file name is a standard UNIX path name. The name list consists of a list of 8character names (null padded) each followed by two words. The list is terminated with a zero. Each name is looked up in the name list of the file. If the name is found, the type and value of the name are placed in the two words following the name. If the name is not found, the type

> This subroutine is useful for examining the system name list kept in the file /sys/sys/unix. In this way programs can obtain system 'magic' numbers that are up to date.

FILES kept in /usr/lib/liba.a

SEE ALSO a.out(V)

DIAGNOSTICS All type entries are set to -1 if the file cannot be found or if it is not a valid namelist.

BUGS

OWNER ken

## 3/15/72

•

à

1

NAME	ptime print date and time	
SYNOPSIS	(move time to ac-mq) mov file,r0 jsr pc,ptime	
DESCRIPTION	ptime prints the date and time in the form	
	Oct 9 17:20:33	
	on the file whose file descriptor is in r0. The string is 15 characters long. The time to be printed is placed in the AC and MQ registers in the form returned by <u>sys time</u> .	
FILES	kept in /usr/lib/liba.a	
SEE ALSO	time(II), ctime(III) (used to do the conversion)	
DIAGNOSTICS		
BUGS	see ctime	
OWN ER	dmr, ken	

6/12/72

(

ł

ł

NAME	putc, putw, fcreat, flush buffered output		
SYNOPSIS	mov \$filename,r0 jsr r5,fcreat; iobuf		
	(get byte in r0) jsr r5,putc; iobuf		
	(get word in r0) jsr r5,putw; iobuf		
	jsr r5,flush; iobuf		
DESCRIPTION	<u>fcreat</u> creates the given file (mode 17) and sets up the buffer <u>iobuf</u> (size 518(10) bytes); <u>putc</u> and <u>putw</u> write a byte or word respectively onto the file; <u>flush</u> forces the contents of the buffer to be written, but does not close the file. The format of the buffer is:		
	<pre>iobuf: .=.+2 / file descriptor .=.+2 / characters unused in buffer .=.+2 / ptr to next free character .=.+512. / buffer</pre>		
	<u>fcreat</u> sets the error bit (c-bit) if the file creation failed; none of the other routines re- turn error information.		
	Before terminating, a program should call <u>flush</u> to force out the last of the output.		
	The user must supply <u>iobuf</u> , which should begin on a word boundary.		
FILES	kept in /usr/lib/liba.a		
SEE ALSO	<pre>creat(II), write(II), getc(III)</pre>		
DIAGNOSTICS	error bit possible on <u>fcreat</u> call		
BUGS			
OWNER	dmr		

NAME

qsort -- quicker sort

SYNOPSIS (base of data in r1) (end of data in r2) (element width in r3) jsr pc.qsort

\_\_\_\_

ken

DESCRIPTION <u>qsort</u> is an implementation of the quicker sort algorithm. It is designed to sort equal length byte strings. Registers r1 and r2 delimit the region of core containing the array of byte strings to be sorted: r1 points to the start of the first string, r2 to the first location above the last string. Register r3 contains the length of each string. r2-r1 should be a multiple of r3. On return, r0, r1, r2, r3, r4, AC and MQ are destroyed.

FILES

SEE ALSO ---

DIAGNOSTICS

BUGS The user should be able to supply his own comparison routine.

OWNER

t

ŧ

١

)

1

6/15/72

salloc -- string manipulation routines NAME (get size in r0) SYNOPSIS pc,allocate jsr (get source pointer in r0, destination pointer in r1) pc,copy jsr jsr pc,wc (all following instructions assume r1 contains pointer) pc, release jsr (get character in r0) pc, putchar jsr pc,lookchar jsr (character in r0) pc,getchar jsr (character in r0) (get character in r0) jsr pc, alterchar (get position in r0) pc,seekchar jsr pc, backspace jsr (character in r0) (get word in r0) pc, putword jsr pc,lookword isr (word in r0) pc,getword jsr (word in r0) (get word in r0) pc,alterword jsr pc, backword jsr (word in r0) pc, length jsr (length in r0) pc, position jsr (position in r0) pc, rewind jsr

jsr pc, create

jsr pc,fsfile

jsr pc,zero

DESCRIPTION

This package is a complete set of routines for dealing with almost arbitrary length strings of words and bytes. The strings are stored on a disk file, so the sum of their lengths can be considerably larger than the available core.

For each string there is a header of four words, namely a write pointer, a read pointer and pointers to the beginning and end of the block containing the string. Initially the read and write pointers point to the beginning of the string. All routines that refer to a string require the header address in r1. Unless the string is destroyed by the call, upon return r1 will point to the same string, although the string may have grown to the extent that it had to be be moved.

<u>allocate</u> obtains a string of the requested size and returns a pointer to its header in r1.

<u>release</u> releases a string back to free storage.

<u>putchar</u> and <u>putword</u> write a byte or word respectively into the string and advance the write pointer.

<u>lookchar</u> and <u>lookword</u> read a byte or word respectively from the string but do not advance the read pointer.

<u>getchar</u> and <u>getword</u> read a byte or word respectively from the string and advance the read pointer.

<u>alterchar</u> and <u>alterword</u> write a byte or word respectively into the string where the read pointer is pointing and advance the read pointer.

backspace and backword read the last byte or word written and decrement the write pointer.

All write operations will automatically get a larger block if the current block is exceeded. All read operations return with the error bit set if attempting to read beyond the write pointer.

<u>seekchar</u> moves the read pointer to the offset specified in r0.

- 2 -

.

6/15/72

i

(

(

.

/ ( 0 / ) =	
	<u>length</u> returns the current length of the string (beginning pointer to write pointer) in r0.
	position returns the current offset of the read pointer in r0.
	rewind moves the read pointer to the current position of the write pointer.
	<u>create</u> returns the read and write pointers to the beginning of the string.
	<u>fsfile</u> moves the write pointer to the current position of the read pointer.
	zero zeros the whole string and sets the write pointer to the beginning of the string.
	copy copies the string whose header pointer is in r0 to the string whose header pointer is in r1. Care should be taken in using the copy instruc- tion since r1 will be changed if the contents of the source string is bigger than the destination string.
	wc forces the contents of the internal buffers and the header blocks to be written on disc.
FILES	The allocator proper is in /usr/llc/alloc/alloca.
	The archive /usr/llc/alloc/allocb contains the individual routines discussed above.
	alloc.d is the temporary file used to contain the strings.
SEE ALSO	
DIAGNOSTICS	"error in copy" if a disk write error occurs dur- ing the execution of the copy instruction. "error in allocator" if any routine is called with a bad header pointer. "Cannot open output file" if file alloc.d cannot be created or opened. "Out of space" if there's no available block of the requested size or no headers avail- able for a new block.
BUGS	
OWNER	llc, rhm

3/15/72

NAME sin, cos -- sine cosine

SYNOPSIS jsr r5, sin (cos)

DESCRIPTION The sine (cosine) of fr0 (radians) is returned in fr0. The floating point simulation should be active in either floating or double mode, but in single precision integer mode. All floating registers are used.

FILES kept in /usr/lib/liba.a

SEE ALSO fptrap(III)

\_

DIAGNOSTICS

t

١

) 1

j

BUGS Size of the argument should be checked to make sure the result is meaningful.

OWNER ken, dmr

٠

3/15/72

ł.

ĺ

(

NAME	sqrt square root function		
SYNOPSIS	jsr r5, sqrt		
DESCRIPTION	The square root of fr0 is returned in fr0. The floating point simulation should be active in either floating or double mode, but in single precision integer mode.		
FILES	kept in /usr/lib/liba.a		
SEE ALSO	fptrap(III)		
DIAGNOSTICS	The c-bit is set on negative arguments.		
BUGS			
OWN ER	rhm, dmr, ken		

3/15/72

NAME

(

ŧ

switch -- switch on value

SYNOPSIS (switch value in r0) jsr r5,switch; swtab (not-found return)

swtab: val1; lab1;

valn; labn ..; O

DESCRIPTION <u>switch</u> compares the value of r0 against each of the val,; if a match is found, control is transferred to the corresponding lab, (after popping the stack once). If no match has been found by the time a null lab, occurs, <u>switch</u> returns.

FILES kept in /usr/lib/liba.a

SEE ALSO

DIAGNOSTICS

BUGS

OWNER ken, dmr

- 1 -

ť.

!

ł

\*

١

ł

ł

NAME	dn0 dn-11 ACU interface
SYNOPSIS	
DESCRIPTION	<u>dn0</u> is a write-only file. Bytes written on <u>dn0</u> must be ASCII digits. Each digit corresponds to a digit of a telephone number to be called. The entire telephone number must be presented in a single <u>write</u> system call. The call must complete with the last digit.
FILES	found in /dev
SEE ALSO	dpO(IV), write(II)
DIAGNOSTICS	
BUGS	
OWNER	ken, dmr

Ę

ĺ

ŧ

•

,

í

. (

NAME	dp0 dp-11 201 data-phone interface
SYNOPSIS	
DESCR IPTION	<u>dp0</u> is a 201 data-phone interface file. <u>read</u> and <u>write</u> calls to <u>dp0</u> are limited to a maximum of 400 bytes. Each write call is sent as a single record. Seven bits from each byte are written along with an eighth odd parity bit. The sync must be user supplied. Each read call returns characters received from a single record. Seven bits are returned unaltered; the eighth bit is set if the byte was not received in odd parity. A 20 second time out is set and a zero byte record is returned if nothing is received in that time.
FILES	found in /dev
SEE ALSO	dnO(IV), gerts(III)
DIAGNOSTICS	
BUGS	The <u>dp</u> file is GECOS oriented. It should be more flexible.

OWNER ken, dmr

- 1 -

.

l

(

í

(

NAME	/dev/lpr line printer		
SYNOPSIS			
DESCRIPTION	The line printer special file is the UNIX inter- face to a DEC LP-11 line printer. This file may only be opened (or creat'ed) for writing. Any- thing written on this file is printed on the line printer. The following special cases for the printer are handled:		
	On opening and on closing, the paper is slewed to the top of the next page.		
	For the 64 character printer (LP11-FA), all lower case letters are converted to upper case.		
	Tabs are converted to align on every eighth column.		
	New lines and form feeds are ignored when the printer is at the top of a page. This is done so that <u>pr</u> and <u>roff</u> output may be directed to the printer and sync on page boundaries even with automatic page slew.		
	Carriage return and back space can cause mul- tiple printing on a single line to allow for overstruck graphics.		
FILES	found in /dev		
SEE ALSO			
DIAGNOSTICS			
BUGS			
OWN ER	ken, dmr		

,

NAME mem -- core memory

SYNOPSIS

DESCRIPTION <u>mem</u> maps the core memory of the computer into a file. It may be used, for example, to examine, and even to patch the system using the debugger.

> Mem is a byte-oriented file; its bytes are numbered 0 to 65,535.

FILES found in /dev

SEE ALSO ·

DIAGNOSTICS

ł

BUGS If a location not corresponding to implemented memory is read or written, the system will incur a bus-error trap and, in panic, will reboot itself.

OWNER ken, dmr

6/12/72

mt0 -- magtape

SYNOPSIS

NAME

DESCRIPTION <u>mt0</u> is the DEC TU10/TM11 magtape. When opened for reading or writing, the magtape is rewound. A tape consists of a series of 256 word records terminated by an end-of-file. Reading less than 256 words (512 bytes) causes the rest of a record to be ignored. Writing less than a record causes null padding to 512 bytes. When the magtape is closed after writing, an end-of-file is written.

Seek has no effect on the magtape. The magtape can only be opened once at any instant.

FILES found in /dev

SEE ALSO mt(I)

DIAGNOSTICS

BUGS Seek should work on the magtape. Also, a provision of having the tape open for reading and writing should exist. A multi-file and multireel facility should be incorporated.

OWN ER

1

ken, dmr

NAME	ppt	وروب محت	punched	paper	tape
------	-----	----------	---------	-------	------

SYNOPSIS

DESCRIPTION <u>ppt</u> refers to the paper tape reader or punch, depending on whether it is read or written.

> When <u>ppt</u> is opened for writing, a 100-character leader is punched. Thereafter each byte written is punched on the tape. No editing of the characters is performed. When the file is closed, a 100-character trailer is punched.

When <u>ppt</u> is opened for reading, the process waits until tape is placed in the reader and the reader is on-line. Then requests to read cause the characters read to be passed back to the program, again without any editing. This means that several null characters will usually appear at the beginning of the file; they correspond to the tape leader. Likewise several nulls are likely to appear at the end. End-of-file is generated when the tape runs out.

Seek calls for this file are meaningless and are effectively ignored (however, the read/write pointers are maintained and an arbitrary sequence of reads or writes intermixed with seeks will give apparently correct results when checked with tell).

FILES found in /dev

SEE	ALSO	
	11100	

DIAGNOSTICS

BUGS

1

OWNER ken, dmr

	rfO		RF11-RS11	fixed-head	disk	file
NAME						

SYNOPSIS

1

This file refers to the entire RF disk. It may be either read or written, although writing is DESCRIPTION inherently very dangerous, since a file system resides there.

The disk contains 1024 256-word blocks, numbered O to 1023. Like the other block-structured dev-ices (tape, RK disk) this file is addressed in blocks, not bytes. This has two consequences: seek calls refer to block numbers, not byte numbers; and sequential reading or writing always advance the read or write pointer by at least one block. Thus successive reads of 10 characters from this file actually read the first 10 characters from successive blocks.

found in /dev FILES

tap0(IV), rk0(IV) SEE ALSO

DIAGNOSTICS

The fact that this device is addressed in terms of blocks, not bytes, is extremely unfortunate. BUGS It is due entirely to the fact that read and write pointers (and consequently the arguments to seek and tell) are single-precision numbers. This really has to be changed but unfortunately the repercussions are serious.

ken, dmr OWN ER

f

ŧ,

NAME	rk0 — RKO3 (or RKO5) disk
SYNOPSIS	
DESCRIPTION	<u>rkO</u> refers to the entire RKO3 disk as a single sequentially-addressed file. Its 256-word blocks are numbered 0 to 4871. Like the RF disk and the tape files, its addressing is block-oriented. Consult the rfO(IV) section.
FILES	found in /dev
SEE ALSO	rfO(IV), tapO(IV)
DIAGNOSTICS	
BUGS	See rf0(IV)
OWN ER	ken, dmr

.

、

.

ţ

. !

NAME	rp0 RP11/RP02 disk
SYNOPSIS	
DESCRIPTION	<u>rp0</u> refers to the entire RP02 disk as a single sequentially-addressed file. Its 256-word blocks are numbered 0 to 40599. Like the RF disk and the tape files, its addressing is block-oriented. Consult the rf0(IV) section.
FILES	found in /dev
SEE ALSO	rfO(IV), tapO(IV)
DIAGNOSTICS	
BUGS	See rf0(IV) Due to a hardware bug, block 40599 on the RP can- not be accessed.
OWNER	ken, dmr

,

į

1

	NAME	tap0 .		tap7
--	------	--------	--	------

-

SYNOPSIS

DESCRIPTION These files refer to DECtape drives 0 to 7. Since the logical drive number can be manually set, all eight files exist even though at present there are fewer physical drives.

> The 256-word blocks on a standard DECtape are numbered 0 to 577. However, the system makes no assumption about this number; a block can be read or written if it exists on the tape and not otherwise. An error is returned if a transaction is attempted for a block which does not exist.

Like the RK and RF special files, addressing on the tape files is block-oriented. See the RFO section.

- FILES found in /dev
- SEE ALSO /dev/rf0, /dev/rk0

\_\_\_

DIAGNOSTICS

BUGS see /dev/rf0

OWNER ken, dmr

i

ĺ

)

1

•

ł

ŧ

NAME	tty console typewriter
SYNOPSIS	
DESCRIPTION	<u>tty</u> (as distinct from <u>tty0</u> ,, <u>ttyn</u> ) refers to the console typewriter hard-wired to the PDP-11.
	Generally, the disciplines involved in dealing with <u>tty</u> are similar to those for <u>tty0</u> and the appropriate section should be consulted. The following differences are salient:
	The system calls <u>stty</u> and <u>gtty</u> do not apply to this device. It cannot be placed in raw mode; on input, upper case letters are always mapped into lower case letters; a carriage return is echoed when a line-feed is typed.
	The quit character is not FS (as with <u>tty0</u> ) but is generated by the key labelled "alt mode."
	By appropriate console switch settings, it is possible to cause UNIX to come up as a single- user system with I/O on this device.
FILES	found in /dev
SEE ALSO	ttyO(IV), init(VII)
DIAGNOSTICS	
BUGS	• ·
OWNER	ken, dmr

•

NAME tty0 ... tty7 -- communications interfaces

. .

SYNOPSIS

DESCRIPTION

These files refer to DC11 asynchronous communications interfaces. At the moment there are eight of them, but the number is subject to change.

When one of these files is opened, it causes the process to wait until a connection is established. (In practice, however, user's programs seldom open these files; they are opened by <u>init</u> and become a user's standard input and output file.) The very first typewriter file open in a process becomes the <u>control typewriter</u> for that process. The control typewriter plays a special role in handling quit or interrupt signals, as discussed below. The control typewriter is inherited by a child process during a <u>fork</u>.

A terminal associated with one of these files ordinarily operates in full-duplex mode. Characters may be typed at any time, even while output is occurring, and are only lost when the system's character input buffers become completely choked, which is rare, or when the user has accumulated the maximum allowed number of input characters which have not yet been read by some program. Currently this limit is 150 characters. When this is happening the character "#" is echoed for every lost input character.

When first opened, the standard interface mode assumed includes: ASCII characters; 150 baud; even parity accepted; 10 bits/character (one stop bit); and newline action character. The system delays transmission after sending certain function characters; delays for horizontal tab, newline, and form feed are calculated for the Teletype Model 37; the delay for carriage return is calculated for the GE TermiNet 300. Most of these operating states can be changed by using the system call stty(II). In particular the following hardware states are program settable independently for input and output (see DC11 manual): 110, 134.5, 150, 300, 600, or 1200 baud; one or two stop bits on output; and 5, 6, 7, or 8 bits/character. In addition, the following software modes can be invoked: acceptance of even parity, odd parity, or both; a raw mode in which all characters may be read one at a time; a carriage return (CR) mode in which CR is mapped into newline on input and either CR or line feed (LF) cause echoing of the sequence LF-CR; mapping of upper case letters into lower case; suppression of echoing; suppression of delays after function

characters; the echoing of input tabs as spaces; and setting the system to handle IBM 2741s. See getty(VII) for the way that terminal speed and type are detected.

Normally, typewriter input is processed in units of lines. This means that a program attempting to read will be suspended until an entire line has been typed. Also, no matter how many characters are requested in the read call, at most one line will be returned. It is not however necessary to read a whole line at once; any number of characters may be requested in a read, even one, without losing information.

During input, erase and kill processing is normally done. The character "#" erases the last character typed, except that it will not erase beyond the beginning of a line or an EOF. The character "@" kills the entire line up to the point where it was typed, but not beyond an EOF. Both these characters operate on a keystroke basis independently of any backspacing or tabbing that may have been done. Either "@" or "#" may be entered literally by preceding it by "\"; the erase or kill character remains, but the "\"

It is possible to use raw mode in which the program reading is wakened on each character. The program waits only until at least one character has been typed. In raw mode, no erase or kill processing is done; and the EOT, quit and interrupt characters are not treated specially.

The ASCII EOT character may be used to generate an end of file from a typewriter. When an EOT is received, all the characters waiting to be read are immediately passed to the program, without waiting for a new-line. Thus if there are no characters waiting, which is to say the EOT occurred at the beginning of a line, zero characters will be passed back, and this is the standard end-of-file signal.

When the carrier signal from the dataset drops (usually because the user has hung up his terminal) any read returns with an end-of-file indication. Thus programs which read a typewriter and test for end-of-file on their input can terminate appropriately when hung up on.

Two characters have a special meaning when typed. The ASCII DEL character (sometimes called "rubout") is the <u>interrupt</u> signal. When this character is received from a given typewriter, a search

(

is made for all processes which have this typewriter as their control typewriter, and which have not informed the system that they wish to ignore interrupts. If there is more than one such process, one of these is selected, for practical purposes at random. If interrupts aren't being ignored, the process is either forced to exit or a trap is simulated to an agreed-upon location in the process. See intr(II).

The ASCII character FS is the <u>quit</u> signal. Its treatment is identical to the interrupt signal except that unless the receiving process has made other arrangements it will not only be terminated but a core image file will be generated. See quit(II).

Output is prosaic compared to input. When one or more characters are written, they are actually transmitted to the terminal as soon as previously-written characters have finished typ-Input characters are echoed by putting them ing. When a proin the output queue as they arrive. gram produces characters more rapidly than they can be typed, it will be suspended when its output queue exceeds some limit. When the queue has drained down to some threshold the program is resumed. Even parity is always generated on output. The EOT character is not transmitted to prevent terminals which respond to it from being hung up.

The system will handle IBM 2741 terminals. See getty(VII) for the way that 2741s are detected. In 2741 mode, the hardware state is: 134.5 baud; one output stop bit; and 7 bits/character. Because the 2741 is inherently half-duplex, input is not echoed. Proper function delays are proyided. For 2741s without a feature known as transmit interrupt" it is not possible to collect input ahead of the time that a program reads the typewriter, because once the keyboard has been enabled there is no way to send further output to the 2741. It is currently assumed that the feature is absent; thus the keyboard is unlocked only when some program reads. The interrupt signal (normally ASCII DEL) is simulated when the 2741 "attention" key is pushed to generate either a 2741 style EOT or a break. It is not possible to generate anything corresponding to the end-of-file EOT or the quit signal. Currently IBM EBCDIC is default for input and output; correspondence code output is settable (see stty(I)). The full ASCII character set is not available: "[", "]", "{", ", are mis , are missing on input and are printed as blank on output;

6/12/72

- - -

(

(

"¢" is used for "\"; "¬" for "^"; "'" for both "'" and "'" on output; and "!" maps into "'" on input. Similar mappings occur with correspondence code output.

FILES found in /dev

SEE ALSO tty(I), getty(VII)

----

DIAGNOSTICS

BUGS The primarily Model 37 oriented delays may not be appropriate for all other ASCII terminals.

OWNER ken, dmr, jfo

NAME a.out -- assembler and link editor output

SYNOPSIS

4

DESCRIPTION <u>a.out</u> is the output file of the assembler <u>as</u> and the link editor <u>ld</u>. In both cases, <u>a.out</u> is executable provided there were no errors and no unresolved external references.

> This file has four sections: a header, the program and data text, a symbol table, and relocation bits (in that order). The last two may be empty if the program was loaded with the "-s" option of <u>ld</u> or if the symbols and relocation have been removed by <u>strip</u>.

The header always contains 8 words:

1 a "br .+20" instruction (407(8))
2 The size of the program text segment
3 The size of the initialized data segment
4 The size of the uninitialized (bss) segment
5 The size of the symbol table
6 The entry location (always 0 at present)
7 The stack size required (0 at present)
8 A flag indicating relocation bits have been
suppressed

The sizes of each segment are in bytes but are even. The size of the header is not included in any of the other sizes.

When a file produced by the assembler or loader is loaded into core for execution, three logical segments are set up: the text segment, the data segment, and the uninitialized segment, in that order. The text segment begins at the lowest location in the core image; the header is not loaded. The data segment begins immediately after the text segment, and the bss segment immediately after the data segment. The bss segment is initialized by 0's. In the future the text segment will be write-protected and shared.

The start of the text segment in the file is 20(8); the start of the data segment is  $20+S_t$  (the size of the text) the start of the relocation information is  $20+S_t+S_d$ ; the start of the symbol table is  $20+2(S_t+S_d)$  if the relocation information is present,  $20+S_t+S_d$  if not.

The symbol table consists of 6-word entries. The first four contain the ASCII name of the symbol, null-padded. The next word is a flag indicating the type of symbol. The following values are possible:

í

00 undefined symbol

- 01 absolute symbol
- 02 text segment symbol
- 03 data segment symbol
- 04 bss segment symbol
- 40 undefined external (.globl) symbol
- 41 absolute external symbol
- 42 text segment external symbol
- 43 data segment external symbol
- 44 bss segment external symbol

Values other than those given above may occur if the user has defined some of his own instructions.

The last word of a symbol table entry contains the value of the symbol.

If the symbol's type is undefined external, and the value field is non-zero, the symbol is interpreted by the loader <u>ld</u> as the name of a common region whose size is indicated by the value of the symbol.

If <u>a.out</u> contains no unresolved global references, the text portions are exactly as they will appear in core when the file is executed. If the value of a word in the text portion involves a reference to an undefined global, the word is replaced by the offset to be added to the symbol's value when it becomes defined.

If relocation information is present, it amounts to one word per word of program text or initialized data. There is no relocation information if the "suppress relocation" flag in the header is on.

Bits 3-1 of a relocation word indicate the segment referred to by the text or data word associated with the relocation word:

- 00 indicates the reference is absolute
- 02 indicates the reference is to the text segment
- 04 indicates the reference is to the data segment
- 06 indicates the reference is to the bss segment
- 10 indicates the reference is to an undefined external symbol.

Bit 0 of the relocation word indicates if <u>on</u> that the reference is relative to the pc (e.g. "clr x"); if <u>off</u>, the reference is to the actual symbol (e.g., clr  $\pm$ ).

ţ

i

ł

•

•

)

ł

	The remainder of the relocation word (bits 15-4) contains a symbol number in the case of external references, and is unused otherwise. The first symbol is numbered 0, the second 1, etc.
FILES	
SEE ALSO	<u>as ld, strip, nm, un(I)</u>
DIAGNOSTICS	
BUGS	
OWNER	dmr

l

ţ

. (

1

١

NAME	archive (library) file format
SYNOPSIS	
DESCRIPTION	The archive command <u>ar</u> is used to combine several files into one. Its use has three benefits: when files are combined, the file space consumed by the breakage at the end of each file (256 bytes on the average) is saved; directories are smaller and less confusing; archive files of object pro- grams may be searched as libraries by the loader <u>ld</u> .
	A file produced by <u>ar</u> has a "magic number" at the start, followed by the constituent files, each preceded by a file header. The magic number is -147(10), or 177555(8) (it was chosen to be un- likely to occur anywhere else). The header of each file is 16 bytes long:
	0-7 file name, null padded on the right
	8-11 Modification time of the file
	12 User ID of file owner
	13 file mode
	14-15 file size
	If the file is an odd number of bytes long, it is padded with a null byte, but the size in the header is correct.
	Notice there is no provision for empty areas in an archive file.
FILES	
SEE ALSO	<u>ar, 1d</u>
DIAGNOSTICS	
BUGS	
OWNER	ken, dmr

.

format of core image NAME

SYNOPSIS

DESCRIPTION

(

í

Three conditions cause UNIX to write out the core image of an executing program: the program generates an unexpected trap (by a bus error or illegal instruction); the user sends a "quit" signal (which has not been turned off by the program); a trap is simulated by the floating point simulator. The core image is called "core" and is written in the current working directory (provided it can be; normal access controls apply).

The size and structure of the core image file depend to some extent on which system is involved. In general there is a 512-byte area at the end which contains the system's per-process data for that process. The remainder represents the actual contents of the user's core area when the core image was written. In the current system, this area is variable in size in that only the locations from user 0 to the program break, plus the stack, is dumped.

When any trap which is not an I/O interrupt occurs, all the useful registers are stored on the stack. After all the registers have been stored, the contents of sp are placed in the first cell of the user area; this cell is called <u>u.sp</u>. Therefore, within the core image proper, there is an area which contains the following registers in the following order (increasing addresses):

 $(u.sp) \rightarrow sc$ 

ma

ac r5 r4 r3 r2 r1 r0 pc (at time of fault) processor status (at time of fault)

The last two are stored by the hardware. It follows that the contents of sp at the time of the fault were (u.sp) plus  $22(\overline{10})$ .

The actual location of this data depends on which system is being used. In the current system, which has relocation and protection hardware, the stack discussed above is the system stack, and is kept in the per-user area; in older systems,

- 1 -

,

.

۱

t

(

there is only one stack, and it is located in the user's core area.

In general the debugger db(I) should be used to deal with core images.

FILES --

SEE ALSO ---

DIAGNOSTICS --

BUGS --

OWNER ken, dmr

• ,

.

- 2 -

NAME

ŝ,

i

format of directories

SYNOPSIS

DESCRIPTION A directory behaves exactly like an ordinary file, save that no user may write into a directory. The fact that a file is a directory is indicated by a bit in the flag word of its i-node entry.

> Directory entries are 10 bytes long. The first word is the i-node of the file represented by the entry, if non-zero; if zero, the entry is empty.

Bytes 2-9 represent the (8-character) file name, null padded on the right. These bytes are not necessarily cleared for empty slots.

By convention, the first two entries in each directory are for "." and ... The first is an entry for the directory itself. The second is for the parent directory. The meaning of "... is modified for the root directory of the master file system and for the root directories of removable file systems. In the first case, there is no parent, and in the second, the system does not permit off-device references without a <u>mount</u> system call. Therefore in both cases "... has the same meaning as "...

FILES --

SEE ALSO file system format

DIAGNOSTICS

BUGS -

OWNER ken, dmr

- 1 -

format of file system

NAME

ł

í.

SYNOPSIS

DESCRIPTION Every file system storage volume (e.g. RF disk, RK disk, DECtape reel) has a common format for certain vital information.

> Every such volume is divided into a certain number of 256 word (512 byte) blocks. Blocks 0 and 1 are collectively known as the super-block for the device; they define its extent and contain an i-node map and a free-storage map. The first word contains the number of bytes in the free-storage map; it is always even. It is followed by the map. There is one bit for each block on the device; the bit is "1" if the block Thus if the number of free-map bytes is is free.  $\underline{n}$ , the blocks on the device are numbered 0 Through 8n-1. The free-map count is followed by the free map itself. The bit for block k of the device is in byte  $\underline{k}/8$  of the map; it is offset  $k \pmod{8}$  bits from the right. Notice that bits exist for the superblock and the i-list, even though they are never allocated or freed.

After the free map is a word containing the byte count for the i-node map. It too is always even. I-numbers below 41(10) are reserved for special files, and are never allocated; the first bit in the i-node free map refers to i-number 41. Therefore the byte number in the i-node map for i-node <u>i</u> is  $(\underline{i}-41)/8$ . It is offset  $(\underline{i}-41)$  (mod 8) bits from the right; unlike the free map, a "0" bit indicates an available i-node.

I-numbers begin at 1, and the storage for i-nodes begins at block 2. Also, i-nodes are 32 bytes long, so 16 of them fit into a block. Therefore, i-node  $\underline{i}$  is located in block ( $\underline{i}+31$ )/16 of the file system, and begins  $32^{\circ}((\underline{i}+31)(\mod 16))$  bytes from its start.

There is always one file system which is always mounted; in standard UNIX it resides on the RF disk. This device is also used for swapping. The swap areas are at the high addresses on the device. It would be convenient if these addresses did not appear in the free list, but in fact this is not so. Therefore a certain number of blocks at the top of the device appear in the free map, are not marked free, yet do not appear within any file. These are the blocks that show up missing in a <u>check</u> of the RF disk.

Again on the primary file system device, there

(

Ę

are several pieces of information following that previously discussed. They contain basically the information typed by the <u>tm</u> command; namely, the times spent since a cold boot in various categories, and a count of I/O errors. In particular, there are two words with the calendar time (measured since 00:00 Jan 1, 1971); two words with the time spent executing in the system; two words with the time spent waiting for I/O on the RF and RK disks; two words with the time spent executing in a user's core; one byte with the count of errors on the RF disk; and one byte with the count of errors on the RK disk. All the times are measured in sixtieths of a second.

I-node 41(10) is reserved for the root directory of the file system. No i-numbers other than this one and those from 1 to 40 (which represent special files) have a built-in meaning. Each i-node represents one file. The format of an i-node is as follows, where the left column represents the offset from the beginning of the i-node:

0-1	flags (see below)
2	number of links
3	user ID of owner
4-5	size in bytes
6-7	first indirect block or contents block
20-21 22-25 26-29 30-31	eighth indirect block or contents block creation time modification time unused

The flags are as follows:

100000	i-node is allocated
040000	directory
020000	file has been modified (always on)
010000	large file
000040	set user ID on execution
000020	executable
000010	read, owner
000004	write, owner
000002	read, non-owner
000001	write, non-owner

The allocated bit (flag 100000) is believed even if the i-node map says the i-node is free; thus corruption of the map may cause i-nodes to become unallocatable, but will not cause active nodes to be reused.

Byte number <u>n</u> of a file is accessed as follows: <u>n</u> is divided by 512 to find its logical block number (say <u>b</u>) in the file. If the file is small

í

(flag 010000 is 0), then <u>b</u> must be less than 8, and the physical block number corresponding to <u>b</u> is the <u>b</u>th entry in the address portion of the i-node.

If the file is large, <u>b</u> is divided by 256 to yield a number which must be less than 8 (or the file is too large for UNIX to handle). The corresponding slot in the i-node address portion gives the physical block number of an indirect block. The residue mod 256 of <u>b</u> is multiplied by two (to give a byte offset in the indirect block) and the word found there is the physical address of the block corresponding to <u>b</u>.

If block <u>b</u> in a file exists, it is not necessary that all blocks less than <u>b</u> exist. A zero block number either in the address words of the i-node or in an indirect block indicates that the corresponding block has never been allocated. Such a missing block reads as if it contained all zero words.

FILES -

SEE ALSO format of directories

DIAGNOSTICS

BUGS Two blocks are not enough to handle the i- and free-storage maps for an RP02 disk pack, which contains around 10 million words.

OWNER ---

•

, ,

1

NAME	ident IDENT card file			
SYNOPSIS				
DESCRIPTION	ident is a file used to generate GECOS \$IDENT cards by the off-line print program opr(I). There is one entry per line in the following style:			
	05:m1234,m789,name			
	which causes the following \$IDENT card to be generated:			
	\$ IDENT m1234,m789,name			
FILES	kept in /etc/ident.			
SEE ALSO	opr(I)			
DIAGNOSTICS				
BUGS				
OWNER	ken, dmr			

- 1 -

3/15/72

ί

L

passwd -- password file NAME SYNOPSIS ---passwd contains for each user the following DESCRIPTION information: name (login name) password numerical user ID default working directory program to use as Shell This is an ASCII file. Each field within each user's entry is separated from the next by a colon. Each user is separated from the next by a new-line. If the password field is null, no password is demanded; if the Shell field is null, the Shell itself is used. This file, naturally, is inaccessible to anyone but the super-user. This file resides in directory /etc. FILES \_\_\_\_ /etc/init SEE ALSO DIAGNOSTICS BUGS super-user OWNER

NAME

tap -- DEC/mag tape formats

SYNOPSIS

DESCRIPTION The DECtape command <u>tap</u> and the magtape command <u>mt</u> dump and extract files to and from their respective tape media. The format of these tapes are the same.

> Block zero of the tape is not used. It is available as a boot program to be used in a stand alone enviornment. This has proved valuable for DEC diagnostic programs.

> Blocks 1 thru 24 contain a directory of the tape. There are 192 entries in the directory; 8 entries per block; 64 bytes per entry. Each entry has the following format:

path name	32 bytes
mode	1 byte
uid	1 byte
size	2 bytes
time modified	4 bytes
tape address	2 bytes
unused	20 bytes
check sum	2 bytes

The path name entry is the path name of the file when put on the tape. If the pathname starts with a zero word, the entry is empty. It is at most 32 bytes long and ends in a null byte. Mode, uid, size and time modified are the same as described under inodes (see file system (V)) The tape address is the tape block number of the start of the contents of the file. Every file starts on a block boundary. The file occupies (size+511)/512 blocks of continuous tape. The checksum entry has a value such that the sum of the 32 words of the directory is zero.

Blocks 25 on are available for file storage.

A fake entry (see mt(I), tap(I)) has a size of zero.

FILES

SEE ALSO filesystem(V), mt(I), tap(I)

DIAGNOSTICS

BUGS

OWNER ken, dmr

NAME /etc/uids -- map user names to user IDs

SYNOPSIS -

DESCRIPTION This file allows programs to map user names into user numbers and vice versa. Anyone can read it. It resides in directory /etc, and should be updated along with the password file when a user is added or deleted.

The format is an ASCII name, followed by a colon, followed by a decimal ASCII user ID number.

FILES --

SEE ALSO ---

1

ί

DIAGNOSTICS -

BUGS ---

OWNER dmr, ken

- 1 -

NAME /tmp/utmp -- user information

SYNOPSIS

DESCRIPTION This file allows one to discover information about who is currently using UNIX. The file is binary; each entry is 16(10) bytes long. The first eight bytes contain a user's login name or are null if the table slot is unused. The low order byte of the next word contains the last character of a typewriter name (currently, '0' to '5' for /dev/tty0 to /dev/tty5). The next two words contain the user's login time. The last word is unused.

This file resides in directory /tmp.

FILES

SEE ALSO /etc/init, which maintains the file.

DIAGNOSTICS

BUGS ---

OWNER ken, dmr

- 1 -

(

(

· (

NAME	/tmp/wtmp user login history
SYNOPSIS	
DESCRIPTION	This file records all logins and logouts. Its format is exactly like utmp(V) except that a null user name indicates a logout on the associated typewriter, and the typewriter name 'x' indicates that UNIX was rebooted at that point.
	Wtmp is maintained by login(I) and init(VII). Neither of these programs creates the file, so if it is removed record-keeping is turned off.
FILES	
SEE ALSO	<pre>init(VII), login(I), tacct(I), acct(I)</pre>
DIAGNOSTICS	
BUGS	
OWNER	ken, dmr

د

-

۱

í

i

4

NAME basic -- DEC supplied BASIC

SYNOPSIS basic [file]

DESCRIPTION Basic is the standard BASIC V000 distributed as a stand alone program. The optional file argument is read before the console. See DEC-11-AJPB-D manual.

Since <u>bas</u> is smaller and faster, <u>basic</u> is not maintained on line.

FILES --

SEE ALSO bas

- DIAGNOSTICS See manual
- BUGS GOK
- OWNER dmr

6/12/72

I.

. ţ BC (VI)

•

NAME	bc B interpreter				
SYNOPSIS	<u>bc</u> [ <u>-c</u> ] sfile <sub>1</sub> .b ofile <sub>1</sub>				
DESCRIPTION	<u>bc</u> is the UNIX B interpreter. It accepts three types of arguments:				
	Arguments whose names end with ".b" are assumed to be B source programs; they are compiled, and the object program is left on the file sfileo (i.e. the file whose name is that of the source with ".o" substituted for ".b").				
	Other arguments (except for "-c") are assumed to be either loader flag arguments, or B-compatible object programs, typically produced by an earlier <u>bc</u> run, or perhaps libraries of B-compatible routines. These programs, together with the results of any compilations specified, are loaded (in the order given) to produce an executable program with name <u>a.out</u> .				
	The "-c" argument suppresses the loading phase, as does any syntax error in any of the routines being compiled.				
	The language itself is described in [1].				
	The future if B is uncertain. The language has been totally eclipsed by the newer, more power- ful, more compact, and faster language C.				
FILES	file.b input file a.out loaded output b.tmp1 temporary (deleted) temporary (deleted) /usr/lang/bdir/b[ca] translator /usr/lib/libb.a builtin functions, etc. /usr/lang/bdir/bilib.a interpreter library				
SEE ALSO	<pre>[1] K. Thompson; MM-72-1271-1; Users' Reference to B. c(I)</pre>				
DIAGNOSTICS	see [1].				
BUGS	Certain external initializations are illegal. (In particular: strings and addresses of exter- nals.)				
OWN ER	ken, dmr				

NAME

١

bj -- the game of black jack

SYNOPSIS /usr/games/bj

DESCRIPTION Black jack is a serious attempt at simulating the dealer in the game of black jack (or twenty-one) as might be found in Reno.

The following rules apply:

The bet is \$2 every hand.

A player 'natural' (black jack) pays \$3. A dealer natural loses \$2. Both dealer and player naturals is a 'push' (no money exchange).

If the dealer has an ace up, the player is allowed to make an 'insurance' bet against the chance of a dealer natural. If this bet is not taken, play resumes as normal. If the bet is taken, it is a side bet where the player wins \$2 if the dealer has a natural and loses \$1 if the dealer does not.

If the player is dealt two cards of the same value, he is allowed to 'double'. He is allowed to play two hands, each with one of these cards. (The bet is doubled also; \$2 on each hand.)

If a dealt hand has a total of ten or eleven, the player may 'double down'. He may double the bet (\$2 to \$4) and receive exactly one more card on that hand.

Under normal play, the player may 'hit' (draw a card) as long as his total is not over twenty-one. If the player 'busts' (goes over twenty-one), the dealer wins the bet.

When the player 'stands' (decides not to hit), the dealer hits until he attains a total of seventeen or more. If the dealer busts, the player wins the bet.

If both player and dealer stand, the one with the largest total wins. A tie is a push.

The machine deals and keeps score. The following questions will be asked at appropriate times. Each question is answered by y followed by a new line for 'yes', or just new line for 'no'.

? means 'do you want a hit?' Insureance?

Double down?

Every time the deck is shuffled, the dealer so states and the 'action' (total bet) and 'standing' (total won or loss) is printed. To exit, hit the interrupt key (DEL) and the action and standing will be printed.

- FILES ---
- SEE ALSO

DIAGNOSTICS --

BUGS --

OWNER ken

,

į

i

NAME cal -- print calendar

SYNOPSIS /usr/ken/cal year

DESCRIPTION Cal will print a calendar for the given year. The year can be between 0 (really 1 BC) and 9999. For years when several calendars were in vogue in different countries, the calendar of England (and therefore her colonies) is printed.

```
P.S. try cal of 1752.
```

FILES	
SEE ALSO	
DIAGNOSTICS	الثبن مست

BUGS

OWNER ken

NAME chash -- precompile a hash table for cref

SYNOPSIS chash file1 file2

DESCRIPTION CHASH takes symbols (character sequences; one per line) from <u>file1</u> and compiles a hash table for the use of <u>cref</u>. The table is written on <u>file2</u>.

A subroutine suitable for searching such a hash table is available from the author.

FILES ----

SEE ALSO cref

DIAGNOSTICS ----

BUGS There can only be 199 symbols; they may total only 600 characters of text.

OWNER lem

ł

- 1 -

(

ł,

NAME	cref	 make	cross	reference	listing

SYNOPSIS <u>cref</u> [ -soi ] name1 ...

DESCRIPTION CREF makes a cross reference listing of files in assembler format (see AS(I)). The files named as arguments in the command line are searched for symbols (defined as a succession of alphabetics, numerics, '.', or '\_', beginning with an alphabetic, '.', or '\_').

The output report is in four columns:

(1) (2) (3) (4) symbol file see text as it appears in file below

The third column contains the line number in the file by default; the <u>-s</u> option will cause the most recent name symbol to appear there instead.

CREF uses either an <u>iqnore</u> file or an <u>only</u> file. If the <u>-i</u> option is given, it will take the next file name to be an <u>iqnore</u> file; if the <u>-o</u> option is given, the next file name will be taken as an <u>only</u> file. Either <u>iqnore</u> or <u>only</u> files must be made by <u>chash</u> (q.v.). If an <u>iqnore</u> file is given, all the symbols in the file will be ignored in columns (1) and (3) of the output. If an <u>only</u> file is given, only symbols appearing in the file will appear in column (1), but column (3) will still contain the most recent name encountered. Only one of the options <u>-i</u> or <u>-o</u> may be used. The default setting is <u>-i</u>; all symbols predefined in the assembler are ignored, except system call names, which are collected.

FILES Files t.0, t.1, t.2, t.3 are created (i.e. DESTROYED) in the working directory of anyone using <u>cref</u>. This nuisance will be repaired soon. The output is left in file <u>s.out</u> in the working directory.

/usr/lem/s.tab is the default ignore file.

SEE ALSO chash(VI); as(I)

DIAGNOSTICS "line too long" -- input line >131 characters "symbol too long" -- symbol >20 characters "too many symbols" -- >10 symbols in line "cannot open t.?" -- bug; see author ÷.

i

- "cannot fork; examine t.out" -- can't start <u>sort</u> process; intermediate results are on files <u>t.0, t.1,t.2,t.3</u>. These may be sorted independently and the results concatenated by the user.
- "cannot sort" -- odd response from <u>sort;</u> examine intermediate results, as above.
- "impossible situation" -- system bug
- "cannot open" file -- one of the input names cannot be opened for reading.

BUGS The destruction of unsuspecting users' files should soon be fixed. A limitation that may eventually go away is the restriction to assembler language format. There should be options for FORTRAN, English, etc., lexical analysis.

> File names longer than eight characters cause misalignment in the output if tabs are set at every eigth column.

OWNER

lem

- 2 -

١

1

(

.

NAME	das disassembler
SYNOPSIS	
DESCRIPTION	A PDP-11 disassembler exists. Contact the owner for more information.
FILES	
SEE ALSO	
DIAGNOSTICS	
BUGS	
OWNER	ken

4

ι.

i

	NAME	dli load DEC binary paper tapes				
	SYNOPSIS	dli output [input]				
(	DESCRIPTION	<u>dli</u> will load a DEC binary paper tape into the output file. The binary format paper tape is read from the input file (/dev/ppt is default.)				
	FILES	/dev/ppt				
	SEE ALSO					
	DIAGNOSTICS	"checksum"				
	BUGS					
	OWN ER	dmr				

s

•

NAME dpt --- read DEC ASCII paper tape

SYNOPSIS dpt output [input]

DESCRIPTION <u>dpt</u> reads the input file (/dev/ppt default) assuming the format is a DEC generated ASCII paper tape of an assembly language program. The output is a UNIX ASCII assembly program.

FILES /dev/ppt

SEE ALSO --

DIAGNOSTICS

BUGS Almost always a hand pass is required to get a correct output.

OWNER ken, dmr

.

ł

1

Ĺ

NAME	moo a game
SYNOPSIS	/usr/games/moo
DESCRIPTION	moo is a guessing game imported from England.
FILES	
SEE ALSO	
DIAGNOSTICS	
BUGS	
OWNER	ken

.

•

`

١.

NAME ptx — permuted index

SYNOPSISptx1input temp1sorttemp1temp2ptx2temp2output

DESCRIPTION <u>ptx</u> generates a permuted index from file <u>input</u> on file <u>output</u>. It is in two pieces: the first does the permutation, generating one line for each keyword in an input line. The keyword is rotated to the front. The permuted file must then be sorted. <u>ptx2</u> then rotates each line around the middle of the page.

> input should be edited to remove useless lines. The following words are suppressed: a, and as, is, for, of, on, or, the, to, up.

The index for this manual was generated using ptx.

FILES --

SEE ALSO sort

----

DIAGNOSTICS

BUGS

OWNER dmr

.

ŧ

٠

.

NAME	tmg compiler compiler
SYNOPSIS	tmg name
DESCRIPTION	tmg produces a translator for the language whose syntactic and translation rules are described in file name <u>.t</u> . The new translator appears in a.out and may be used thus:
	<u>a.out</u> input [ output ]
	Except in rare cases input must be a randomly addressable file. If no output file is speci- fied, the standard output file is assumed.
	The tmg language is described in (Reference).
FILES	<pre>/etc/tmg the compiler-compiler /etc/tmga,/etc/tmgb,/etc/tmgc libraries /etc/tmg0.s global definitions</pre>
SEE ALSO	
DIAGNOSTICS	<pre>??? illegal input, offending line follows fatal error codes, appear in tmg and a.out: ad address out of bounds so stack overflow ga address out of bounds while generating ko too much parse without output to symbol table overflow gn getnam on symbol not in table co character string overflow</pre>
BUGS	·
OWN ER	doug

## 3/15/72

ţ

NAME ttt -- tic-tac-toe

SYNOPSIS /usr/games/ttt

DESCRIPTION <u>ttt</u> is the X's and O's game popular in 1st grade. This is a learning program that never makes the same mistake twice.

FILES ttt.k -- old mistakes

SEE ALSO

DIAGNOSTICS ---

BUGS --

OWNER ken

٠

NAME

ascii -- map of ASCII character set

SYNOPSIS <u>cat /usr/pub/ascii</u>

DESCRIPTION <u>ascii</u> is a map of the ASCII character set, to be printed as needed. It contains:

000 nul 001 soh 002 stx 003 etx 004 eot 005 eng 006 ack 007 b	e⊥¦ i !
1000  mull  001  sob  1002  stx 1003  etx 1004  eoc 1003  out  1004  eoc 1003  out 1004  eoc 1003  out 1004  eoc 1004  eoc 1003  eoc 1004  eoc	<b>1</b> !
1040 La 1044 bt 1012 bl 1013 VC 1014 hp 1013 CL 1010 20 1	<b>i</b> -
1010 b3 1021 dc1 1022 dc2 1023 dc3 024 dc4 025 nak 026 syn 027 e	tb
1020 dielozi dei ozo - 1024 fa 1025 gs 1036 rs 103/ u	5
1030 can $1031$ ell $1042$ sub $1042$ # $1044$ e $1045$ % $1046$ & $1047$	
1040  sp $1041$ $1052$ $1054$ $1054$ $1055 - 1056$ $1057$	
050 ( 051 ) 052 2 063 3 064 4 065 5 066 6 067	7
$060 \ 0 \ 061 \ 1 \ 062 \ 2 \ 073 \ 074 \ (075 = 076 ) 077$	?
070 8 071 9 072 1073 , 104 D 105 E 106 F 107	G
100 @ 101 A 102 B 103 C 104 D 115 M 116 N 117	0
110 H 111 I 112 J 113 K 112 H 125 H 126 V 127	W
120 P 121 Q 122 R 123 S 124 1 135 1 136 1 137	Ì
$ 130 \times  131 \times  132 \times  133 \cup  134 \cup  135 \cup  146 +  147$	gĺ
140 141 a 142 b 143 C 144 a 145 m 156 n 157	δİ
150 h $151$ i $152$ j $153$ K $154$ i $155$ m $166$ w $167$	w
160 p 161 g 162 r 163 s 164 c 165 1 177 d	el
$ 170 \times  171 \times  172 \times  172 \times  173 $ { $ 174 +  175 $ } $ 176 + 177 = 177 $	

FILES found	in	/usr/pub
-------------	----	----------

----

\_\_\_

SEE ALSO

D IAGNOST ICS

- BUGS ---
- OWNER jfo

- 1 -

NAME bos, maki, rom, vcboot, msys, et al

SYNOPSIS

Ĺ

l

DESCRIPTION On the RF disk, the highest 16K words are reserved for stand-alone programs. These 16K words are allocated as follows:

bos		(1K)
Warm	UNIX	(7K)
Cold	UNIX	(8K)

The UNIX read only memory (ROM) is home cut with 2 programs of 16 words each. The first (address 173000) reads <u>bos</u> from the RF disk into core location 154000 and transfers to 154000. The other ROM program (address 173040) reads a DECtape sitting in the end-zone on drive 0 into core location 0 and transfers to 0. This latter operation is compatible with part of DEC's standard ROM. The disassembled code for the UNIX ROM follows:

173000:	mov mov mov mov mov tstb bge jmp	<pre>\$177472,r0 \$3,-(r0) \$140000,-(r0) \$154000,-(r0) \$-2000,-(r0) \$5,-(r0) (r0)2 *\$154000</pre>	12700;177472 12740;3 12740;140000 12740;154000 12740;176000 12740;5 105710 2376 137;154000
173040:	mov clr mov mov tstb bge tst bne movb tstb bge clr	\$177350,r0 -(r0) r0,-(r0) \$3,-(r0) (r0) 2 *\$177350 \$5,(r0) (r0) 2 pc	12700;177350 5040 10040 12740;3 105710 2376 5737;177350 1377 112710;5 105710 2376 5007

The program <u>bos</u> (Bootstrap Operating System) examines the console switchs and executes one of several internal programs depending on the setting. The following settings are currently recognized:

- ??? Will read Warm UNIX from the RF into core location 0 and transfer to 600.
- 1 Will read Cold UNIX from the RF into core

location 0 and transfer to 600.

- 10 Will dump all of memory from core location 0 onto DECtape drive 7 and then halt.
- 20 Will read 256 words from RKO into core O and transfer to zero. This is the procedure to boot DOS from an RK.
- 40 This is the same as 10 above, but instead of halting, UNIX warm is loaded.
- 0 Will load a standard UNIX binary paper tape into core location 0 and transfer to 0.
- 77500 Will load the standard DEC absolute and binary loaders and transfer to 77500.

Thus we come to the UNIX warm boot procedure: put 173000 into the switches, push <u>load address</u> and then push <u>start</u>. The alternate switch setting of 173030 that will load warm UNIX is used as a signal to bring up a single user system for special purposes. See init(VII). For systems without a rom, UNIX (both warm and cold) have a copy of the disk boot program at location 602. This is probably a better warm boot procedure because the program at 602 also attempts to complete outstanding I/O.

Cold boots can be accomplished with the Cold UNIX program, but they're not. Thus the Cold UNIX slot on the RF may have any program desired. This slot is, however, used during a cold boot. Mount the UNIX INIT DECtape on drive 0 positioned in the end-zone. Put 173040 into the switches. Push load address. Put 1 into the switches. Push start. This reads a program called vcboot from the tape into core location 0 and transfers to it. vcboot then reads 16K words from the DECtape (blocks 1-32) and copies the data to the highest 16K words of the RF. Thus this initializes the read-only part of the RF. vcboot then reads in bos and executes it. bos then reads in Cold UNIX and executes that. Cold UNIX halts for a last chance before it completely initializes the RF file system. Push continue, and Cold UNIX will initialize the RF. It then sets into execution a user program that reads the DECtape for initialization files starting from block 33. When this is done, the program executes /etc/init which should have been on the tape.

The INIT tape is made by the program <u>maki</u> running

- 2 -

!

l

under UNIX. <u>maki</u> writes <u>vcboot</u> on block 0 of  $/\underline{dev}/\underline{tap7}$ . It then copies the RF 16K words (using  $/\underline{dev}/\underline{rf0}$ ) onto blocks 1 thru 32. It has internally a list of files to be copied from block 33 on. This list follows:

/etc/init
/bin/chmod
/bin/date
/bin/login
/bin/ls
/bin/mkdir
/etc/mount
/bin/sh
/bin/tap

Thus this is the set of programs available after a cold boot. <u>init</u> and <u>sh</u> are mandatory. For multi-user UNIX, <u>getty</u> and <u>login</u> are also necessary. <u>mkdir</u> is necessary due to a bug in <u>tap</u>. <u>tap</u> and <u>mount</u> are useful to bring in new files. As soon as possible, <u>date</u> should be done. That leaves <u>ls</u> and <u>chmod</u> as frosting.

The last link in this incestuous daisy chain is the program msys.

<u>msys</u> char file

will copy the file <u>file</u> onto the RF read only slot specified by the characacter <u>char</u>. Char is taken from the following set:

<u>b</u> bos <u>u</u> Warm UNIX <u>1</u> Cold UNIX

Due to their rarity of use, <u>maki</u> and <u>msys</u> are maintained off line and must be reassembled before used.

FILES /dev/rf0, /dev/tap?

ken

SEE ALSO init(VII), tap(I), sh(I), mkdir(I)

DIAGNOST ICS

BUGS This section is very configuration dependent. Thus, it does not describe the boot procedure for any one machine.

OWNER

NAME getty -- set typewriter mode and get user's name

SYNOPSIS

DESCRIPTION <u>getty</u> is invoked by init (VII) immediately after a typewriter is opened following a dial-in. The user's login name is read and the login(I) command is called with this name as an argument. While reading this name <u>getty</u> attempts to adapt the system to the speed and type of terminal being used.

> getty initially sets the speed of the interface to 150 baud, specifies that raw mode is to be used (break on every character), that echo is to be suppressed, and either parity allowed. It types the login: message (which includes the characters which put the 37 Teletype terminal into full-duplex and unlock its keyboard). Then the user's name is read, a character at a time. If a null character is received, it is assumed to be the result of the user pushing the "break" ("interrupt") key. The speed is then changed to 300 baud and the "login:" is typed again, this time with the appropriate sequence which puts a GE TermiNet 300 into full-duplex. This sequence is acceptable to other 300 baud terminals also. If a subsequent null character is received, the speed is changed again. The general approach is to cycle through a set of speeds in response to null characters caused by breaks. The sequence at this installation is 150, 300, and 134.5 baud.

Detection of IBM 2741s is accomplished while the speed is set to 150 baud. The user sends a 2741 style "eot" character by pushing the attention key or by typing return; at 150 baud, this character looks like the ascii "(174<sub>8</sub>). Upon receipt of the "eot", the system is set to operate 2741s and a login: "message is typed.

The user's name is terminated by a new-line or carriage-return character. The latter results in the system being set to to treat carriage returns appropriately (see stty(II)).

The user's name is scanned to see if it contains any lower-case alphabetic characters; if not, the system is told to map any future upper-case characters into the corresponding lower-case characters. Thus UNIX is usable from upper-case-only terminals.

Finally, login is called with the user's name as argument.

- 1 -

6/12/72

ć

(

.

FILES	/etc/getty
SEE ALSO	<pre>init(VII), login(I), stty(II)</pre>
DIAGNOSTICS	·
BUGS	
OWNER	dmr, ken, jfo

1

NAME glob -- generate command arguments

SYNOPSIS

DESCRIPTION <u>glob</u> is used to expand arguments to the shell containing "\*", '[', or "?". It is passed the argument list containing the metacharacters; <u>glob</u> expands the list and calls the command itself.

FILES found in /etc/glob

----

SEE ALSO sh(I)

DIAGNOSTICS "No match", "No command", "No directory"

BUGS If any of '\*', '[', or '?' occurs both quoted and unquoted in the original command line, even the quoted metacharacters are expanded.

> <u>glob</u> gives the "No match" diagnostic only if no arguments at all result. This is never the case if there is any argument without a metacharacter.

OWN ER

dmr

NAME init -- process control initialization

SYNOPSIS

DESCRIPTION <u>init</u> is invoked inside UNIX as the last step in the boot procedure. Generally its role is to create a process for each typewriter on which a user may log in.

> First, <u>init</u> checks to see if the console switches contain 173030. (This number is likely to vary between systems.) If so, the console typewriter <u>tty</u> is opened for reading and writing and the shell is invoked immediately. This feature is used to bring up a test system, or one which does not contain DC-11 communications interfaces. When the system is brought up in this way, the <u>getty</u> and <u>login</u> routines mentioned below and described elsewhere are not needed.

> Otherwise, <u>init</u> does some housekeeping: the mode of each DECtape file is changed to 17 (in case the system crashed during a <u>tap</u> command); directory /usr is mounted on the RKO disk; directory /sys is mounted on the RK1 disk. Also a dataphone daemon is spawned to restart any jobs being sent.

> Then <u>init</u> forks several times to create a process for each typewriter mentioned in an internal table. Each of these processes opens the appropriate typewriter for reading and writing. These channels thus receive file descriptors 0 and 1, the standard input and output. Opening the typewriter will usually involve a delay, since the <u>open</u> is not completed until someone is dialled in (and carrier established) on the channel. Then the process executes the program /<u>etc/getty</u> (q.v.). <u>getty</u> will read the user'sname and invoke <u>login</u> (q.v.) to log in the userand execute the shell.

> Ultimately the shell will terminate because of an end-of-file either typed explicitly or generated as a result of hanging up. The main path of <u>init</u>, which has been waiting for such an event, wakes up and removes the appropriate entry from the file <u>utmp</u>, which records current users, and makes an entry in <u>wtmp</u>, which maintains a history of logins and logouts. Then the appropriate typewriter is reopened and <u>getty</u> reinvoked.

FILES kept in /etc/init; uses /dev/tap, /dev/tty, /dev/tty?, /tmp/utmp, /tmp/wtmp

SEE ALSO

login(I), login(VII), getty(VII), sh(I), dpd(I)

6/15/72

1

ŧ

DIAGNOSTICS	none	possible
BUGS	none	possible
OWNER	ken,	dmr

•

.

## 6/15/72

i

NAME	kbd keyboard map
SYNOPSIS	cat /usr/pub/kbd
DESCRIPTION	<u>kbd</u> contains a map to the keyboard for model 37 Teletype terminals with the extended character set feature. If <u>kbd</u> is printed on such a termi- nal, the following will appear:
	<[1234567890]^\ >qwertyuiop@ asdfghjkl;: zxcvbnm,./
	< <sup>∇1234567890-¬∂</sup> ſr > v ;: ,./
	<{!"#\$%&'() =_} >QWERTYUIOP ASDFGHJKL+* ZXCVBNM,.?
	< !"#\$%&'() =- >ζΔΛ∑θσφτΘΠ αεδΦΓΨπρλ+* Ωξωψβημ,.?

,

FILES	
SEE ALSO	تکن ہیں
DIAGNOSTICS	
BUGS	
OWNER	jfo

·

NAME logging in and logging out

SYNOPSIS

DESCRIPTION

UNIX must be called from an appropriate terminal. UNIX supports ASCII terminals typified by the Teletype M37, the GE Terminet 300, the Memorex 1240, and various graphical terminals on the one hand, and IBM 2741-type terminals on the other.

Not all installations support all these terminals. Often the M33/35 Teletype is supported instead of the 2741. Depending on the hardware installed, most terminals operating at 110, 134.5, 150, or 300 baud can be accommodated.

To use UNIX, it is also necessary to have a valid UNIX user ID and (if desired) password. These may be obtained, together with the telephone number, from the system administrators.

The same telephone number serves terminals operating at all the standard speeds. The discussion below applies when the standard speeds of 134.5 (2741's) 150 (TTY 37's) and 300 (Terminet 300's) are available.

When a connection is established via a 150-baud terminal (e.g. TTY 37) UNIX types out "login:"; you respond with your user name, and, if requested, with a password. (The printer is turned off while you type the password.) If the login was successful, the "@" character is typed by the Shell to indicate login is complete and commands may be issued. A message of the day may be typed if there are any announcements. Also, if there is a file called "mailbox", you are notified that someone has sent you mail. (See the <u>mail</u> command.)

From a 300-baud terminal, the procedure is slightly different. Such terminals often have a full-duplex switch, which should be turned on (or conversely, half-duplex should be turned off). When a connection with UNIX is established, a few garbage characters are typed (these are the login: message at the wrong speed). You should depress the break key; this is a speedindependent signal to UNIX that a 300-baud terminal is in use. It will type login: (at the correct speed this time) and from then on the procedure is the same as described above.

From a 2741, no message will appear. After the telephone connection is established, press the "ATTN" button. UNIX should type "login:" as

6/15/72

(

described above. If the greeting does not appear after a few seconds, hang up and try again; something has gone wrong. If a password is required, the printer cannot be turned off, so it will appear on the paper when you type it.

For more information, consult getty(VII), which discusses the login sequence in more detail, and ttyO(IV), which discusses typewriter I/O.

Logging out is simple by comparison (in fact, sometimes too simple). Simply generate an endof-file at Shell level by using the EOT character; the login: message will appear again to indicate that you may log in again.

It is also possible to log out simply by hanging up the terminal; this simulates an end-of-file on the typewriter.

FILES /etc/motd may contain a message-of-the-day.

SEE ALSO init(VII), getty(VII), tty0(IV)

DIAGNOSTICS

BUGS Hanging up on programs which never read the typewriter or which ignore end-of-files is very dangerous; in the worst cases, the programs can only be halted by restarting the system.

OWNER ken, dmr

----

6/15/72

ŕ

NAME	msh mini-shell
SYNOPSIS	
DESCRIPTION	<u>msh</u> is a heavily simplified version of the Shell. It reads one line from the standard input file, interprets it as a command, and calls the com- mand.
	The mini-shell supports few of the advanced features of the Shell; none of the following characters is special:
	> < \$ \ ; &
	However, <b>"*", "[",</b> and "?" are recognized and <u>glob</u> is called. The main use of <u>msh</u> is to pro- vide a command-executing facility for various interactive sub-systems.
FILES	found in /etc/msh
SEE ALSO	sh, glob
DIAGNOSTICS	"?"
BUGS	
OWN ER	ken, dmr

- 1 -

,

٩

(

{

NAME tabs -- tab stop set

SYNOPSIS cat /usr/pub/tabs

----

DESCRIPTION When printed on a suitable terminal, this file will set tab stops at columns 8, 16, 24, 32, .... Suitable terminals include the Teletype model 37 and the GE TermiNet 300.

These tabs stop settings are desirable because UNIX assumes them in calculating delays.

FILES
-------

SEE ALSO

DIAGNOSTICS

BUGS --

OWNER ken