



ConTeXt

commands

EN

ConTeXt

commands

en / english
January 2, 2007

`\about {1.2.}`

- 1 TEXT
- 2 REFERENCE

`\adaptlayout [...,1...] [...,2OPTIONAL...]`

- 1 NUMBER
- 2 `height = DIMENSION max`
`lines = NUMBER`

`\adding [...]`

- * `small medium big`

`\appendix [...,1...] {2.}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\arg {*.}`

- * TEXT

`\at {1.} {2.} [3.]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\atpage [...]`

- * REFERENCE

`\background`

`\blackrule [...,*...]`
OPTIONAL

- * *inherits from* `\setupblackrules`

`\blackrules [...,*...]`

- * *inherits from* `\setupblackrules`

`\blank [...,*...]`
OPTIONAL

- * `small medium big nowhite back white disable force reset line halpline FORMULA fixed flexible none`

`\bookmark [...1...] {...2...}`
OPTIONAL

- 1 IDENTIFIER
- 2 TEXT

`\but [...]`

- * REFERENCE

`\button [...,1...] {...2...} [...3...]`
OPTIONAL

- 1 *inherits from* \setupbuttons
- 2 TEXT
- 3 REFERENCE

`\bypassblocks [...,1...] [...2...]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\Cap {...}`

- * TEXT

`\cap {...}`

- * TEXT

`\CAP {...}`

- * TEXT

`\Caps {... * ...}`

- * WORD

`\chapter [...1...] {...2...}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\character {...}`

- * TEXT

`\Character {...}`

- * TEXT

`\Characters {...}`

* TEXT

`\characters {...}`

* TEXT

`\chem {...1} {...2} {...3}`

1 TEXT

2 TEXT

3 TEXT

`\clip [...,1OPTIONAL,...] {...2}`

1 *inherits from* \setupclipping

2 TEXT

`\clonefield [...1] [...,2,...] [...3] [...,4OPTIONAL,...]`

1 IDENTIFIER

2 IDENTIFIER

3 IDENTIFIER

4 IDENTIFIER

`\color [...1] {...2}`

1 TEXT

2 TEXT

`\column`

`\comment [...1OPTIONAL] [...,2OPTIONAL,...] {...3}`

1 IDENTIFIER

2 *inherits from* \setupcomment

3 TEXT

`\comparecolorgroup [...1]`

* IDENTIFIER

`\comparepalet [...1]`

* IDENTIFIER

`\completeCOMBINEDLIST [...1] [...,2,...]`

1 IDENTIFIER

2 *inherits from* \setupcombinedlist

`\completelistofFLOATS`

`\completelistofSORTS`

`\completelistofSYNONYMS`

`\completeREGISTER [...,*,...]`

OPTIONAL

** inherits from \setupregister*

`\convertnumber {.1.} {.2.}`

1 TEXT

2 TEXT

`\copyfield [.1.] [...,2,...]`

1 IDENTIFIER

2 IDENTIFIER

`\correctwhitespace {...}`

** TEXT*

`\coupledocument [.1.] [.2.] [.3.]`

1 IDENTIFIER

2 file

3 IDENTIFIER

`\coupledREGISTER [.1.] {.2.}`

OPTIONAL

1 TEXT

2 ENTRY

`\couplemarking [.1.] [.2.]`

1 IDENTIFIER

2 IDENTIFIER

`\couplepage [...,1,...] [...,2,...]`

1 IDENTIFIER

2 option = doublesided
before = COMMAND
after = COMMAND

`\couplepaper [...]`

** IDENTIFIER*

`\coupleregister [...]`

* IDENTIFIER

`\crlf`

`\currentdate [...*,...]`

* *inherits from* \date

`\currentheadnumber`

`\date [...,1.,...]` `[...2,...]`
OPTIONAL

1 d = NUMBER
m = NUMBER
y = NUMBER

2 see 2

`\decouplemarking [...]`

* IDENTIFIER

`\define [...]1 \...2 {...3}`
OPTIONAL

1 NUMBER
2 NAME
3 TEXT

`\defineblank [...]1 [...]2`

1 IDENTIFIER
2 *inherits from* \setupblank

`\defineblock [...]`

* IDENTIFIER

`\definebodyfont [...]1,...]` `[...]2` `[...,3.,...]`

1 5pt ... 12pt default
2 rm ss tt mm hw cg
3 tf = FILE
bf = FILE
sl = FILE
it = FILE
bs = FILE
bi = FILE
sc = FILE
ex = FILE
mi = FILE
sy = FILE
ma = FILE
mb = FILE
mc = FILE

`\definebodyfontenvironment [1.] [2.,...]`

```
1 5pt ... 12pt default
2 text      = DIMENSION
  script    = DIMENSION
  scriptscript = DIMENSION
  x          = DIMENSION
  xx         = DIMENSION
  small      = DIMENSION
  big        = DIMENSION
```

`\definebuffer [...]`

`* IDENTIFIER`

`\definecolor [1.] [2.,...]`

```
1 IDENTIFIER
2 r = TEXT
  g = TEXT
  b = TEXT
  c = TEXT
  m = TEXT
  y = TEXT
  k = TEXT
  s = TEXT
  h = TEXT
  t = TEXT
  a = TEXT
  p = TEXT
  e = TEXT
```

`\definecolorgroup [1.] [2.] [x:y:3z=,...]`
OPTIONAL

```
1 IDENTIFIER
2 rgb cmyk gray s
3 TRIPLET
```

`\definecombinedlist [1.] [2.,...] [3.,...]`
OPTIONAL

```
1 IDENTIFIER
2 LIST
3 inherits from \setupcombinedlist
```

`\defineconversion [1.] [2.]`

```
1 IDENTIFIER
2 COMMAND TEXT
```

`\definedescription [1.] [2.,...]`
OPTIONAL

```
1 IDENTIFIER
2 inherits from \setupdescriptions
```

`\defineenumeration [1.,...] [2.] [3.,...]`
OPTIONAL OPTIONAL

```
1 IDENTIFIER
2 IDENTIFIER
3 inherits from \setupenumerations
```

`\definefield [.1.] [.2.] [.3.] [...,4...] [.5.]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 IDENTIFIER
- 4 IDENTIFIER
- 5 IDENTIFIER

`\definefieldstack [.1.] [...,2...] [...,3.,...]`

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 *inherits from* \setupfields

`\definefiguresymbol [.1.] [.2.] [...,3.,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 TEXT
- 3 *inherits from* \externalfigure

`\definefloat [.1.] [.2.]`

- 1 SINGULAR NAME
- 2 PLURAL NAME

`\definefont [.1.] [.2.]`

- 1 IDENTIFIER
- 2 FILE

`\defineframed [.1.] [...,2.,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupframedtexts

`\defineframedtext [.1.] [...,2.,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupframedtexts

`\definehead [.1.] [.2.]`

- 1 IDENTIFIER
- 2 SECTION

`\defineindenting [.1.] [...,2.,...]`

- 1 IDENTIFIER
- 2 *inherits from* \setupindentations

`\defineinteractionmenu [...,1...] [...,2,...]`

OPTIONAL

```
1 left right top bottom IDENTIFIER
2 before          = COMMAND
  after           = COMMAND
  inbetween       = COMMAND
  left            = COMMAND
  right           = COMMAND
  middle          = COMMAND
  state           = start stop none local
  style           =
  color           = IDENTIFIER
  distance        = overlay DIMENSION
  samepage        = yes empty no none
  unknownreference = yes empty no none
  leftoffset      = DIMENSION
  rightoffset     = DIMENSION
  topoffset       = DIMENSION
  bottomoffset    = DIMENSION
  position        = yes no
  inherits from \setupframed
```

`\defineinteractionmenu [...1] [...2] [...,3,...]`

OPTIONAL

OPTIONAL

```
1 left right top bottom IDENTIFIER
2 left right top bottom IDENTIFIER
3 inherits from \setupinteractionmenu
```

`\definelabel [...1] [...,2,...]`

```
1 IDENTIFIER
2 text      = TEXT
  location  = inmargin intext
  way       = bytext bycd:section
  blockway  = yes no
  headstyle =
  headcolor = IDENTIFIER
  before    = COMMAND
  after     = COMMAND
```

`\definelist [...1] [...2] [...,3,...]`

OPTIONAL

OPTIONAL

```
1 IDENTIFIER
2 IDENTIFIER
3 inherits from \setuplist
```

`\definelogo [...1] [...2] [...3] [...,4,...]`

```
1 IDENTIFIER
2 top header footer bottom
3 none page leftedge leftmargin left middle right rightmargin rightedge
4 command = COMMAND TEXT
  state   = start stop
```

`\definemakeup [...1] [...,2,...]`

```
1 IDENTIFIER
2 inherits from \setupmakeup
```

`\definemarking [.1.] [.2.]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\defineoutput [.1.] [...2;...]`

- 1 IDENTIFIER
- 2 IDENTIFIER

`\defineoverlay [...1;...] [.2.]`

- 1 IDENTIFIER
- 2 COMMAND

`\definepalet [.1.] [...2.,...]`

- 1 IDENTIFIER
- 2 IDENTIFIER = IDENTIFIER

`\definepapersize [.1.] [...2.,...]`

- 1 IDENTIFIER
- 2 width = DIMENSION
height = DIMENSION
offset = DIMENSION
scale = NUMBER

`\defineparagraphs [.1.] [...2.,...]`

- 1 IDENTIFIER
- 2 n = NUMBER
rule = on off
height = fit DIMENSION
before = COMMAND
after = COMMAND
inner = COMMAND
distance = DIMENSION
tolerance = verystRICT strict tolerant verytolerant stretch
align =

`\defineprofile [...1;...] [...2.,...]`

- 1 IDENTIFIER
- 2 IDENTIFIER

`\defineprogram [.1.] [.2.] [.3.]`

- 1 IDENTIFIER
- 2 TEXT
- 3 TEXT

`\defineraffont [.1.] [.2.] [...3.,...]`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 FILE
- 3 *inherits from* \setupinterlinespace

`\definereference [.1.] [...,2,...]`

- 1 IDENTIFIER
- 2 REFERENCE

`\definereferenceformat [.1.] [...,2,...]`

- 1 IDENTIFIER
- 2 `left` = TEXT
- `right` = TEXT
- `text` = TEXT
- `label` = IDENTIFIER

`\definereferencelist [.1.] [...,2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupreferencelist

`\defineregister [.1.] [.2.]`

- 1 SINGULAR NAME
- 2 PLURAL NAME

`\definerule [.1.] [...,2,...]`

- 1 IDENTIFIER
- 2 *inherits from* \setuprule

`\definesection [.*.]`

- * IDENTIFIER

`\definesectionblock [.1.] [...,2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupsectionblock

`\definesorting [.1.] [.2.] [.3.]`
OPTIONAL

- 1 SINGULAR NAME
- 2 PLURAL NAME
- 3 COMMAND

`\definestartstop [.1.] [...,2,...]`

- 1 IDENTIFIER
- 2 `before` = COMMAND
- `after` = COMMAND
- `style` =
- `commands` = COMMAND

`\definesubfield [.1.] [.2.] [...3,...]`

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 IDENTIFIER

`\definesymbol [.1.] [.2.]`

- 1 IDENTIFIER
- 2 TEXT

`\definesynonyms [.1.] [.2.] [.3.] [.4.]`
OPTIONAL

- 1 SINGULAR NAME
- 2 PLURAL NAME
- 3 COMMAND
- 4 COMMAND

`\definetabletemplate [.1.] [.2.] [.3.] [.4.]`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 TEXT
- 3 TEXT
- 4 TEXT

`\definetabulate [.1.] [.2.] [.3.]`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 TEXT

`\definetext [.1.] [.2.] [.3.] [.4.] [.5.]`
OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 header footer
- 3 TEXT
- 4 TEXT
- 5 TEXT

`\definetextposition [.1.] [...,2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setuppositioning

`\definetextvariable [.1.] [.2.] [...,3,...]`
OPTIONAL OPTIONAL

- 1 *inherits from* \setuptextvariable
- 2 see 2
- 3 see 3

`\definetype [.1.] [...,2,...]`

- 1 IDENTIFIER
- 2 *inherits from* \setuptype

`\definotyping [.1.] [...,2,...]`

- 1 file typing IDENTIFIER
- 2 *inherits from* \setuptyping

`\defineversion [.1.] [...,2,...]`

- 1 IDENTIFIER
- 2 NUMBER

`\DESCRIPTION {1.} 2.`

- 1 TEXT
- 2 EMPTY

`\determineheadnumber [...]`

- * SECTION

`\determinelistcharacteristics [...,1,...] [...,2,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setuplist

`\disableinteractionmenu [.1.] [...,2,...]`

- 1 left right top bottom IDENTIFIER
- 2 REFERENCE

`\donttest`

`\emptylines [...]`

- * NUMBER

`\ENUMERATION *.`

- * EMPTY

`\externalfigure [.1.] [...,2,...]`

- 1 FILE
- 2 *inherits from* \useexternalfigure

`\field [...]`

* IDENTIFIER

`\fieldstack [...]1 [...]2 [...]3...`
 OPTIONAL OPTIONAL

1 IDENTIFIER

2 IDENTIFIER

3 *inherits from* \setupfields

`\fillinfield [...]1 {...}2`
 OPTIONAL

1 TEXT

2 TEXT

`\fillinline [...]1...2`
 OPTIONAL

1 *inherits from* \setupfillinlines

2 EMPTY

`\fillinrules [...]1 {...}2 {...}3`
 OPTIONAL OPTIONAL

1 *inherits from* \setupfillinrules

2 TEXT

3 TEXT

`\fillintext [...]1 {...}2 {...}3`
 OPTIONAL OPTIONAL

1 *inherits from* \setupfillinrules

2 TEXT

3 TEXT

`\fitfield [...]`

* IDENTIFIER

`\fixedspaces`

`\followprofile {...}1 [...]2`

1 TEXT

2 TEXT

`\followprofileversion {...}1 [...]2 [...]3`

1 TEXT

2 TEXT

3 IDENTIFIER

`\followversion {1.} [2.]`

- 1 TEXT
- 2 TEXT

`\footnote [OPTIONAL1.] {2.}`

- 1 REFERENCE
- 2 TEXT

`\footnotetext [OPTIONAL1.] {2.}`

- 1 REFERENCE
- 2 TEXT

`\forceblocks [...1;...] [...2;...] OPTIONAL`

- 1 IDENTIFIER
- 2 IDENTIFIER

`\fraction {1.} {2.}`

- 1 TEXT
- 2 TEXT

`\framed [...OPTIONAL1.;...] {2.}`

- 1 *inherits from \setupframed*
- 2 TEXT

`\FRAMEDTEXT [...OPTIONAL*.;...]`

- * *inherits from \setupframedtexts*

`\from [...]`

- * REFERENCE

`\getbuffer [...OPTIONAL.]`

- * IDENTIFIER

`\getmarking [1.] [2.]`

- 1 IDENTIFIER
- 2 first last previous both all current

`\godown [...]`

- * DIMENSION

`\goto {1.} {2.} [...3,...]`

- 1 TEXT
- 2 TEXT
- 3 REFERENCE

`\gotobox {1.} [...2,...]`

- 1 TEXT
- 2 REFERENCE

`\graycolor [...]`

- * TEXT

`\grid [...,*,...]`

- * x = NUMBER
- y = NUMBER
- nx = NUMBER
- ny = NUMBER
- dx = NUMBER
- dy = NUMBER
- xstep = NUMBER
- ystep = NUMBER
- offset = yes no
- factor = NUMBER
- scale = NUMBER
- unit = cm pt em mm ex es in
- location = left middle

`\hairline`

`\head [...,*,...]`

OPTIONAL

- * REFERENCE

`\headnumber [...,*,...]`

OPTIONAL

- * SECTION

`\headtext {*.}`

- * TEXT

`\hideblocks [...1,...] [...2,...]`

OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\high {*.}`

- * TEXT

`\h1 [...]`

* NUMBER

`\in {.1.} {.2.} [.3.]`

1 TEXT

2 TEXT

3 REFERENCE

`\INDENTATION ...`

* EMPTY

`\indenting [...,*,...]`

*

`\inframed [...,1,...] {.2.}`
OPTIONAL

1 *inherits from* \setupframed

2 TEXT

`\ininner [.1.] [.2.] {.3.}`
OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\inleft [.1.] [.2.] {.3.}`
OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\inline [...]`

* REFERENCE

`\inmargin [.1.] [.2.] {.3.}`
OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\inotharmargin [.1.] [.2.] {.3.}`
OPTIONAL OPTIONAL

1 + - low

2 REFERENCE

3 TEXT

`\inouter` [¹...] [²...] {...³}
 OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\inright` [¹...] [²...] {...³}
 OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\installlanguage` [¹...] [...,²...,...]

- 1 IDENTIFIER
- 2 spacing = packed broad
 lefthyphenmin = DIMENSION
 righthyphenmin = DIMENSION
 state = start stop
 leftsentence = COMMAND
 rightsentence = COMMAND
 leftsubsentence = COMMAND
 rightsubsentence = COMMAND
 leftquote = COMMAND
 rightquote = COMMAND
 leftquotation = COMMAND
 rightquotation = COMMAND
 default = IDENTIFIER

`\interactionbar` [...,^{*}...,...]

- * inherits from \setupinteractionbar*

`\interactionbuttons` [...,¹...,...] [...,²...,...]
 OPTIONAL

- 1 *inherits from \setupinteractionbar*
- 2 IDENTIFIER

`\item` [...,^{*}...,...]
 OPTIONAL

- * REFERENCE*

`\items` [...,¹...,...] {...²... ..}
 OPTIONAL

- 1 *inherits from \setupitems*
- 2 TEXT

`\its` [...,^{*}...,...]
 OPTIONAL

- * REFERENCE*

`\keepblocks` [...,¹...,...] [...,²...,...]
 OPTIONAL

- 1 IDENTIFIER
- 2 all IDENTIFIER

`\LABELING [...]`

OPTIONAL

* REFERENCE

`\labels [...]`

* IDENTIFIER

`\labeltext {...}`

* TEXT

`\language [...]`

*

`\leftaligned {...}`

* TEXT

`\listsymbol [.1.] {.2.}`

1 IDENTIFIER

2 TEXT

`\loadSORTS`

`\loadSYNONYMS`

`\logfields`

`\lohi [.1.] {.2.} {.3.}`

OPTIONAL

1 low

2 TEXT

3 TEXT

`\low {...}`

* TEXT

`\mainlanguage [...]`

*

`\mar [...,1...] {.2.}`

OPTIONAL

1 REFERENCE

2 TEXT

`\marginrule [.1.] {.2.}`

- 1 NUMBER
- 2 TEXT

`\margintext [.1.] [.2.] {.3.}`
OPTIONAL OPTIONAL

- 1 + - low
- 2 REFERENCE
- 3 TEXT

`\marking [.1.] {.2.}`

- 1 IDENTIFIER
- 2 TEXT

`\markversion`

`\mathematics {...}`

- * TEXT

`\mediaeval {...}`

- * TEXT

`\midaligned {...}`

- * TEXT

`\mirror {...}`

- * TEXT

`\month {...}`

- * TEXT

`\MONTH {...}`

- * TEXT

`\moveongrid [...*,...]`
OPTIONAL

- * top both bottom -top -both -bottom TEXT high middle low page none standard broad fit depth line
DIMENSION

`\name {...}`

- * TEXT

`\nextSECTION`

`\nocap {...}`

* TEXT

`\noheaderandfooterlines`

`\noindenting`

`\nolist {...}`

* TEXT

`\nomarking {...}`

* TEXT

`\nomoreblocks`

`\nomorefiles`

`\nop`

`\nospace`

`\note [...]`

* REFERENCE

`\notopandbottomlines`

`\nowhitespace`

`\numbers {...}`

* TEXT

`\overbar {...}`

* TEXT

`\overbars {... ..}`

* WORD

`\overstrike {...}`

* TEXT

`\overstrikes {... *. ...}`

* WORD

`\packed`

`\page [...*,...]`

* yes makeup no preference bigpreference left right disable last quadruple even odd blank empty reset
start stop

`\pagereference [...]`

* REFERENCE

`\pagetype [...]`

* IDENTIFIER

`\PARAGRAPH`

`\part [...1,...] {..2.}`
OPTIONAL

1 REFERENCE

2 TEXT

`\periods [...]`

* NUMBER

`\placebookmarks [...1,...] [...2,...]`
OPTIONAL OPTIONAL

1 IDENTIFIER

2 IDENTIFIER all

`\placecombinedlist [...1.] [...,2.,...]`
OPTIONAL

1 IDENTIFIER

2 *inherits from* \setupcombinedlist

`\placeCOMBINEDLIST [...1.] [...,2.,...]`
OPTIONAL

1 IDENTIFIER

2 *inherits from* \setupcombinedlist

`\placeFLOAT [...1...] [...2,...] {...3} {...4}`
 OPTIONAL OPTIONAL

- 1 left right here top bottom inleft inright inmargin margin leftmargin rightmargin leftedge rightedge
innermargin outermargin inneredge outeredge inner outer line high low fit page leftpage rightpage
opposite always auto force tall reset line height depth split
- 2 REFERENCE
- 3 TEXT
- 4 TEXT

`\placefootnotes [...,*,...]`
 OPTIONAL

- * inherits from \setupfootnotes

`\placeformula [...1,...] {...2} $$3..$$`
 OPTIONAL OPTIONAL

- 1 REFERENCE
- 2 TEXT
- 3

`\placelegend {...1} {...2}`

- 1 TEXT
- 2 TEXT

`\placelist [...1,...] [...2,...]`
 OPTIONAL

- 1 IDENTIFIER
- 2 inherits from \setuplist

`\placelistofFLOATS`

`\placelistofSORTS`

`\placelistofSYNONYMS`

`\placelocalfootnotes [...,*,...]`
 OPTIONAL

- * inherits from \setupfootnotes

`\placelogos [...,*,...]`
 OPTIONAL

- * IDENTIFIER

`\placeongrid [...1] {...2}`
 OPTIONAL

- 1 inherits from \moveongrid
- 2 TEXT

`\placeontopofeachother {1.} {2.}`

- 1 TEXT
- 2 TEXT

`\placereferencelist [...*...]`

- * IDENTIFIER

`\placeregister [1.] [...2...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \setupregister

`\placeREGISTER [...*...]`
OPTIONAL

- * *inherits from* \setupregister

`\placerule [...]`

- * IDENTIFIER

`\placesidebyside {1.} {2.}`

- 1 TEXT
- 2 TEXT

`\placesubformula [...1...] {2.} $$3.$$`
OPTIONAL OPTIONAL

- 1 REFERENCE
- 2 TEXT
- 3

`\placetextvariable [...]`

- * IDENTIFIER

`\position (...1,...) {2.}`

- 1 POSITION
- 2 TEXT

`\positiontext [1.] {2.}`

- 1 IDENTIFIER
- 2 TEXT

`\processblocks [...1,...] [...2...]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\processpage [...1,...] [...2.]`

1 IDENTIFIER

2 yes no

`\program [...]`

* IDENTIFIER

`\publication [...]`

* REFERENCE

`\quotation {...}`

* TEXT

`\quote {...}`

* TEXT

`\ran {...}`

* TEXT

`\ref [...1] [...2.]`

1 t p r s e

2 REFERENCE

`\reference [...1] {...2.}`

1 REFERENCE

2 TEXT

`\referral [...,*,...]`

* bet = TEXT

ken = TEXT

dat = TEXT

van = TEXT

aan = TEXT

ref = TEXT

`\referraldate`

`\REGISTER [...1] {...+...2+...}`

OPTIONAL

1 TEXT

2 ENTRY

```
\reserveFLOAT [...,1OPTIONAL,...] [...2OPTIONAL] [...3OPTIONAL,...] {...4.}
```

1 height = DIMENSION
width = DIMENSION
frame = on off

2 TEXT

3 REFERENCE

4 TEXT

```
\reset [...,*,...]
```

* IDENTIFIER

```
\resetmarking [...]
```

* IDENTIFIER

```
\resettextcontent [...1.] [...2.] [...3.]OPTIONAL
```

1

2

3

```
\rightaligned {...}
```

* TEXT

```
\romannumerals {...}
```

* TEXT

```
\Romannumerals {...}
```

* TEXT

```
\rotate [...,1OPTIONAL,...] {...2.}
```

1 inherits from \setuprotate

2 TEXT

```
\scale [...,1OPTIONAL,...] {...2.}
```

1 sx = NUMBER
sy = NUMBER

2 TEXT

```
\screen
```

```
\section [...,1OPTIONAL,...] {...2.}
```

1 REFERENCE

2 TEXT

```
\seeREGISTER [...]1 {...}2 {...+...+...}3  
OPTIONAL
```

- 1 TEXT
- 2 TEXT
- 3 ENTRY

```
\selectblocks [...]1,... [...]2,... [...]3.  
OPTIONAL OPTIONAL
```

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 criterium = all SECTION

```
\selectpaper [...],*,...]
```

```
* family = 1 2
```

```
\selectversion
```

```
\settextcontent [...]1 [...]2 [...]3 [...]4 [...]5  
OPTIONAL OPTIONAL OPTIONAL
```

- 1
- 2
- 3
- 4
- 5

```
\settextvariable [...]1 [...]2
```

- 1 IDENTIFIER
- 2 TEXT

```
\setupalign [...]
```

```
* width left right middle inner outer wide broad height bottom line reset hanging nohanging  
hyphenated nothyphenated
```

```
\setuparranging [...],*,...]
```

```
* disable 2*16 2*8 2*4 2*2 2**2 2*2*4 2*4*2 2UP 2DOWN 2SIDE 2TOP mirrored rotated doublesided  
negative background 90 180 270
```

```
\setupbackground [...],*,...]
```

```
* leftoffset = DIMENSION  
rightoffset = DIMENSION  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
before = COMMAND  
after = COMMAND  
state = start stop  
inherits from \setupframed
```

```
\setupbackgrounds [1] [...2...] [...3...]
                        OPTIONAL      OPTIONAL
1  top header TEXT footer bottom page paper lefpage righpage
2  leftedge leftmargin TEXT rightmargin rightedge
3  state = start stop cd:repeat
    inherits from \setupframed
```

```
\setupblackrules [..,.*,..]
```

```
*      width      =  DIMENSION  max
      height      =  DIMENSION  max
      depth       =  DIMENSION  max
      alternative  =  a b
      distance     =  DIMENSION
      n           =  NUMBER
```

`\setupblank [...]`
OPTIONAL

* normal standard line DIMENSION big medium small fixed flexible

$$\backslash\mathrm{setupblock} \left[\dots, \overset{1}{\dots} \right] \left[\dots, \overset{2}{\underline{\dots}}, \dots \right]$$

```

1  IDENTIFIER
2  before  =  COMMAND
   after   =  COMMAND
   inner   =  COMMAND
   style   =
   file    =  FILE

```

`\setupbodyfont [...,*,...]`

```
* IDENTIFIER serif regular roman sans support sansserif mono type teletype handwritten calligraphic 5pt
... 12pt
```

$$\backslash\mathrm{setupbodyfontenvironment} \quad [..^1..] \quad [..,.\underline{\underline{2}}.,..]$$

```
1 inherits from \setupbodyfont
2 inherits from \setupbodyfont
```

`\setupbottom` $[.1.]$ $[..,.\underline{2}.,..]$
OPTIONAL

```
1 inherits from \setupheader
2 inherits from \setupheader
```

`\setupbottomtexts` `[.1.]` `[.2.]` `[.3.]`
 OPTIONAL OPTIONAL OPTIONAL

- 1
- 2
- 3

`\setupbuffer` [1.] [2.],3.,4.]

```

1  IDENTIFIER
2  paragraph = NUMBER
   before   = COMMAND
   after     = COMMAND

```

```
\setupbuttons [...,.*,...]
```

```
* state = start stop
    inherits from \setupframed
```

```
\setupcapitals [...,.*,...]
```

```
* title = yes no
    sc   = yes no
```

```
\setupcaption [.1.] [...,.*.2,...]
```

```
1 IDENTIFIER
2 inherits from \setupcaptions
```

```
\setupcaptions [...,.*,...]
```

```
* location = top bottom none high low middle left middle right lefthanging righthanging leftmargin
            rightmargin innermargin outermargin
width      = fit broad max DIMENSION
minwidth   = fit DIMENSION
headstyle  =
style      =
number     = yes no
inbetween  = COMMAND
align      =
conversion = numbers characters Characters romannumerals Romannumerals
way        = bytext bycd:section
separator  = TEXT
stopper    = TEXT
command    = COMMAND
distance   = DIMENSION
```

```
\setupclipping [...,.*,...]
```

```
* nx      = NUMBER
ny        = NUMBER
x         = NUMBER
y         = NUMBER
width     = DIMENSION
height    = DIMENSION
hoffset   = DIMENSION
voffset   = DIMENSION
mp        = IDENTIFIER
```

```
\setupcolor [...,.*.]
```

```
* IDENTIFIER
```

```
\setupcolors [...,.*,...]
```

```
* state      = start stop global local
conversion   = yes no always
reduction    = yes no
rgb          = yes no
cmyk         = yes no
mpcmyk       = yes no
mpspot       = yes no
textcolor    = IDENTIFIER
split        = c m y k p s no IDENTIFIER
criterium    = all none
```


`\setupcolumns [...,*,...]`

```
*  n          = NUMBER
   ntop       = NUMBER
   rule       = on off
   height     = DIMENSION
   tolerance  = verystRICT  STRICT  tolerant  verytolerant  stretch
   distance   = DIMENSION
   balance    = yes no
   align      = text
   blank      = fixed halfline line flexible big medium small
   option     = background
   direction  = left right
   inherits from \setupframed
```

`\setupcombinations [...,*,...]`

```
*  before     = COMMAND
   inbetween  = COMMAND
   after      = COMMAND
   distance   = DIMENSION
   height     = DIMENSION fit
   width      = DIMENSION fit
   location   = top middle bottom left right
   align      =
   style      =
   color      = IDENTIFIER
```

`\setupcombinedlist [...,1...] [...,2*,...]`

```
1  IDENTIFIER
2  level = 1 2 3 4 SECTION current
   inherits from \setuplist
```

`\setupcomment [...,*,...]`

```
*  state      = start stop
   width      = DIMENSION
   height     = DIMENSION
   color      = IDENTIFIER
   title      = TEXT
   space      = yes no
   symbol     = normal New Balloon Addition Help Paragraph Key IDENTIFIER
   option     = max buffer
   margin     = DIMENSION
   distance   = DIMENSION
```

`\setupdescriptions [...,1...] [...,2*,...]`
OPTIONAL

```
1  IDENTIFIER
2  headstyle  =
   style      =
   color      = IDENTIFIER
   width      = fit broad DIMENSION
   distance   = DIMENSION
   sample     = TEXT
   text       = TEXT
   align      =
   margin     = standard yes no DIMENSION
   location   = left right top serried inmargin inleft inright hanging
   headcommand = COMMAND
   hang       = fit broad NUMBER
   before     = COMMAND
   inbetween  = COMMAND
   after      = COMMAND
   indentnext =
   indenting  =
```

`\setupenumerations [...,1...] [...,2...]`
OPTIONAL

- 1 IDENTIFIER
- 2 *inherits from* \definedescription

`\setupexternalfigures [.*.]`

* option = frame empty test
object = yes no
frames = on off
ymax = NUMBER
xmax = NUMBER
directory = TEXT
location = local global default none
maxwidth = DIMENSION
maxheight = DIMENSION
conversion = TEXT
prefix = TEXT

`\setupfield [...,1...] [...,2...] [...,3...] [...,4...] [...,5...]`

- 1 IDENTIFIER
- 2 label horizontal vertical frame
- 3 *inherits from* \setupfields
- 4 *see* 4
- 5 *see* 5

`\setupfields [...,1...] [...,2...] [...,3...] [...,4...] [...,5...]`

- 1 IDENTIFIER
- 2 reset label horizontal vertical frame
- 3 n = NUMBER
distance = DIMENSION
before = COMMAND
after = COMMAND
inbetween = COMMAND
color = IDENTIFIER
style =
align =
option = readonly required protected sorted unavailable hidden printable
clickin = REFERENCE
clickout = REFERENCE
regionin = REFERENCE
regionout = REFERENCE
afterkey = REFERENCE
format = REFERENCE
validate = REFERENCE
calculate = REFERENCE
fieldoffset = DIMENSION
fieldframecolor = IDENTIFIER
fieldbackgroundcolor = IDENTIFIER
inherits from \framed
- 4 *see* 4
- 5 *see* 5

`\setupfillinlines [...,*,...]`

* width = DIMENSION
margin = DIMENSION
distance = DIMENSION
before = COMMAND
after = COMMAND

```
\setupfillinrules [...,*,...]
```

```
* width           = fit broad DIMENSION
  distance        = DIMENSION
  before          = COMMAND
  after           = COMMAND
  style           =
  n               = NUMBER
  interlinespace  = small medium big
  separator       = TEXT
```

```
\setupfloat [...,1..2,...]
```

```
1 IDENTIFIER
2 height          = DIMENSION
  width           = DIMENSION
  maxheight       = DIMENSION
  maxwidth        = DIMENSION
  minwidth        = DIMENSION
  default         = IDENTIFIER
  pageboundaries  = LIST
  leftmargindistance = DIMENSION
  rightmargindistance = DIMENSION
  location        = left middle right
  inherits from \setupframed
```

```
\setupfloats [...,*,...]
```

```
* location        = left right middle
  width           = fit DIMENSION
  before          = COMMAND
  after           = COMMAND
  margin          = DIMENSION
  spacebefore     = small medium big none
  spaceafter      = small medium big none
  sidespacebefore = small medium big none
  sidespaceafter  = small medium big none
  indentnext      =
  ntop            = NUMBER
  nbottom         = NUMBER
  nlines          = NUMBER
  default         = IDENTIFIER
  tolerance       = 0 1 2
  leftmargindistance = DIMENSION
  rightmargindistance = DIMENSION
  sidealign       = normal line
  numbering       = yes nocheck
  inherits from \setupframed
```

```
\setupfloatsplitting [...,*,...]
```

```
* conversion = numbers characters Characters romannumerals Romannumerals
  lines      = NUMBER
```

```
\setupfooter [...,1..2,...]
```

OPTIONAL

```
1 inherits from \setupheader
2 inherits from \setupheader
```

```
\setupfootertexts [...,1..2..3]
                  OPTIONAL OPTIONAL OPTIONAL
```

```
1
2
3
```

`\setupfootnotedefinition [...,.*,...]`

* *inherits from* \definedescription

`\setupfootnotes [...,.*,...]`

* conversion = numbers characters Characters romannumerals Romannumerals
way = bytext bycd:section
location = page TEXT columns firstcolumn lastcolumn high none
rule = on off
before = COMMAND
after = COMMAND
width = DIMENSION
height = DIMENSION
bodyfont = 5pt ... 12pt small big
style =
distance = DIMENSION
columndistance = DIMENSION
margindistance = DIMENSION
n = NUMBER
numbercommand = \...#1
textcommand = \...#1
split = tolerant strict verystRICT NUMBER
textstyle =
textcolor = IDENTIFIER
interaction = yes no
factor = NUMBER
inherits from \framed

`\setupforms [...,.*,...]`

* method = HTML FDF

`\setupformulae [...,.*,...]`

* location = left right
left = TEXT
right = TEXT
align =
option = middle
strut = yes no
distance = DIMENSION
margin = DIMENSION standard yes no
align = flushleft flushright middle center
leftmargin = DIMENSION
rightmargin = DIMENSION
indentnext =
alternative = IDENTIFIER
spacebefore = DIMENSION
after = DIMENSION
separator = TEXT
conversion = numbers characters Characters romannumerals Romannumerals TEXT

`\setupframed [...,*.,...]`

```
* height          = fit broad DIMENSION
width             = fit broad fixed local DIMENSION
autowidth        = yes no force
offset           = none overlay default DIMENSION
location         = depth hanging high lohi low top middle bottom keep
option           = none empty
strut            = yes no global local
align            =
bottom           = COMMAND
top              = COMMAND
frame            = on off none overlay
topframe         = on off
bottomframe      = on off
leftframe        = on off
rightframe       = on off
frameoffset      = DIMENSION
framedepth       = DIMENSION
framecorner      = round rectangular
frameradius      = DIMENSION
framecolor       = IDENTIFIER
background       = screen color none foreground IDENTIFIER
backgroundscreen = NUMBER
backgroundcolor  = IDENTIFIER
backgroundoffset = frame DIMENSION
backgrounddepth  = DIMENSION
backgroundcorner = round rectangular
backgroundradius = DIMENSION
depth           = DIMENSION
corner          = round rectangular
radius          = DIMENSION
empty           = yes no
foregroundcolor  = IDENTIFIER
foregroundstyle  =
rulethickness    = DIMENSION
```

`\setupframedtexts [...,*.,...]`

```
* bodyfont        = 5pt ... 12pt small big
style            =
left             = COMMAND
right            = COMMAND
before           = COMMAND
after            = COMMAND
inner            = COMMAND
linecorrection   = on off
depthcorrection  = on off
margin           = standard yes no
location         = left right middle none
indenting        =
inherits from \setupframed
```

`\setuphead [...1,...] [...2,...]`

```
1 SECTION
2 style =
textstyle =
numberstyle =
color = IDENTIFIER
textcolor = IDENTIFIER
numbercolor = IDENTIFIER
number = yes no
ownnumber = yes no
page = left right yes
continue = yes no
header = none empty high nomarking
text = none empty high nomarking
footer = none empty high nomarking
before = COMMAND
inbetween = COMMAND
after = COMMAND
alternative = normal inmargin middle TEXT
hang = none broad fit line NUMBER
command = \...#1#2
numbercommand = \...#1
textcommand = \...#1
deepnumbercommand = \...#1
deeptextcommand = \...#1
prefix = + - TEXT
placehead = yes no empty
incrementnumber = yes no LIST FILE
resetnumber = yes no
file = IDENTIFIER
expansion = yes no command
margintext = yes no
inherits from \setupheads
```

`\setupheader [...1.] [...2.,...]`

OPTIONAL

```
1 TEXT margin edge
2 state = normal stop start empty high none nomarking IDENTIFIER
strut = yes no
style =
leftstyle =
rightstyle =
leftwidth = DIMENSION
rightwidth = DIMENSION
before = COMMAND
after = COMMAND
```

`\setupheadertexts [...1.] [...2.] [...3.]`

OPTIONAL OPTIONAL OPTIONAL

```
1
2
3
```

`\setupheadnumber [...1.] [...2.]`

```
1 SECTION
2 NUMBER +cd:number -cd:number
```

`\setupheads [...,*,...]`

```
*  sectionnumber = yes  NUMBER  no
   alternative   = normal  margin  middle  TEXT  paragraph
   separator     = TEXT
   stopper       = TEXT
   align         =
   aligntitle    = yes  float  no
   tolerance     = verystRICT  STRICT  tolerant  verytolerant  stretch
   indentnext    =
   command       = \...#1#2
   margin        = DIMENSION
```

`\setupheadtext [.1.] [.2.]`
OPTIONAL

```
1
2  IDENTIFIER = TEXT
```

`\setuphyphenmark [.*.]`

```
*  sign = -- --- - ~ ( ) = /
```

`\setupindentations [...,1...] [...,2...]`
OPTIONAL

```
1  IDENTIFIER
2  style      =
   headstyle  =
   width      = fit  DIMENSION
   text       = TEXT
   sample     = TEXT
   before     = COMMAND
   after      = COMMAND
   distance   = DIMENSION
   separator  = TEXT
```

`\setupindenting [...,*,...]`

```
*
```

`\setupinmargin [.1.] [...,2...]`
OPTIONAL

```
1  left  right  NUMBER
2  location = left  right  both
   style    =
   before   = COMMAND
   after    = COMMAND
   align    =
   line     = NUMBER
   distance = DIMENSION
   separator = TEXT
   width    = DIMENSION
   distance = DIMENSION
   stack    = yes  no
   inherits from \setupframed
```

`\setupinteraction [...,*,...]`

```
* state      = start stop
menu         = on off
page         = yes no
click        = yes no
split        = yes no
display      = new
openaction   = REFERENCE
closeaction  = REFERENCE
openpageaction = REFERENCE
closepageaction = REFERENCE
calculate    = IDENTIFIER
strut        = yes no
width        = DIMENSION
height       = DIMENSION
depth        = DIMENSION
style        =
color        = IDENTIFIER
contrastcolor = IDENTIFIER
symbolset    = IDENTIFIER
title        = TEXT
subtitle     = TEXT
author       = TEXT
date         = TEXT
keyword      = TEXT
fieldlayer   = auto IDENTIFIER
```

`\setupinteractionbar [...,*,...]`

```
* state      = start stop
alternative  = a b c d e f g
symbol       = yes no
width        = DIMENSION height fit
height       = DIMENSION height fit
depth        = DIMENSION
color        = IDENTIFIER
step         = NUMBER small medium big
inherits from \setupframed
```

`\setupinteractionscreen [...,*,...]`

```
* width      = DIMENSION fit max
height       = DIMENSION fit max
backspace    = DIMENSION
topspace     = DIMENSION
horoffset    = DIMENSION
veroffset    = DIMENSION
option       = max fit doublesided bookmark
delay        = NUMBER none
```

`\setupinterlinespace [...*]`
OPTIONAL

```
* reset small medium auto big on off
```

`\setupinterlinespace [...,*,...]`

```
* height = NUMBER
depth    = NUMBER
line     = DIMENSION
top      = NUMBER
bottom   = NUMBER
```



```

\setupitemgroup [.1.] [.2.] [...,3...] [...,4_,...]
                        OPTIONAL      OPTIONAL      OPTIONAL

1 IDENTIFIER
2 NUMBER each
3 standard broad serried packed unpacked nowhite before after stopper joinedup atmargin inmargin
  autointro loose repeat SECTION paragraph intext random
4 margin      = no standard DIMENSION
  leftmargin  = no standard DIMENSION
  rightmargin = no standard DIMENSION
  width       = DIMENSION
  distance    = DIMENSION
  factor      = NUMBER
  items       = NUMBER
  start       = NUMBER
  before      = COMMAND
  inbetween   = COMMAND
  after       = COMMAND
  left        = TEXT
  right       = TEXT
  beforehead  = COMMAND
  afterhead   = COMMAND
  headstyle   =
  marstyle    =
  symstyle    =
  stopper     = TEXT
  n           = NUMBER
  symbol      = NUMBER
  align       =
  indentnext  =

```

```

\setupitems [...,*_,...]

* location = left right inmargin top bottom
  symbol   = 1 2 ... n a ... TEXT none
  width     = DIMENSION
  n         = NUMBER unknown
  before    = COMMAND
  inbetween = COMMAND
  align     =
  after     = COMMAND

```

```

\setuplabeltext [.1.] [.2.]
                        OPTIONAL

```

```

1
2 IDENTIFIER = TEXT

```

```

\setuplanguage [.1.] [...,2_,...]

```

```

1
2 inherits from \installlanguage

```

`\setuplayout [...,*.,...]`

```
*   width           = DIMENSION   fit   middle
    height          = DIMENSION   fit   middle
    backspace       = DIMENSION
    topspace        = DIMENSION
    margin           = DIMENSION
    leftmargin       = DIMENSION
    rightmargin      = DIMENSION
    header           = DIMENSION
    footer           = DIMENSION
    top              = DIMENSION
    bottom           = DIMENSION
    leftedge         = DIMENSION
    rightedge        = DIMENSION
    headerdistance   = DIMENSION
    footerdistance   = DIMENSION
    topdistance      = DIMENSION
    bottomdistance   = DIMENSION
    leftmargindistance = DIMENSION
    rightmargindistance = DIMENSION
    leftedgedistance = DIMENSION
    rightedgedistance = DIMENSION
    horoffset        = DIMENSION
    veroffset        = DIMENSION
    style            =
    color            = IDENTIFIER
    marking           = on off color screen TEXT
    location          = left middle right bottom top singlesided doublesided
    scale            = DIMENSION
    nx               = NUMBER
    ny               = NUMBER
    dx               = DIMENSION
    dy               = DIMENSION
    lines            = NUMBER
    columns           = NUMBER
    columndistance   = DIMENSION
    grid             = yes no
    bottomspace       = DIMENSION
    cutspace         = DIMENSION
    textdistance      = DIMENSION
    textwidth        = NUMBER
    textmargin       = DIMENSION
    clipoffset        = DIMENSION
    page             = IDENTIFIER
    paper            = IDENTIFIER
```

`\setuplegend [...,*.,...]`

```
*   n               = NUMBER
    distance         = DIMENSION
    inbetween        = COMMAND
    width            = DIMENSION
    height           = DIMENSION
    location          = right bottom
    bodyfont         = 5pt ... 12pt small big
```

`\setuplinenumbering [...,*.,...]`

```
*   conversion       = numbers characters Characters romannumerals Romannumerals TEXT
    start            = NUMBER
    step             = NUMBER
    width            = DIMENSION
    location          = intext inmargin
    style            =
    prefix           = TEXT
    referencing       = on off
```

`\setuplines [...,.*,...]`

```
* before      = COMMAND
  after       = COMMAND
  inbetween   = COMMAND
  indenting   =
  space       = yes no
```

`\setuplinewidth [...]`

```
* DIMENSION
```

`\setuplist [...,1...] [...,2,...]`

```
1 IDENTIFIER
2 state      = start stop
  alternative = a b c ... none command
  coupling    = on off
  criterium   = SECTION local previous current all
  pageboundaries = LIST
  style       =
  numberstyle =
  textstyle   =
  pagestyle   =
  color       = IDENTIFIER
  command     = \...#1#2#3
  numbercommand = \...#1
  textcommand  = \...#1
  pagecommand  = \...#1
  interaction  = cd:sectionnumber TEXT pagenumber all
  before      = COMMAND
  after       = COMMAND
  inbetween   = COMMAND
  left        = TEXT
  right       = TEXT
  label       = yes no
  prefix      = yes no none
  pagenumber  = yes no
  headnumber  = yes no
  cd:sectionnumber = yes no
  aligntitle  = yes no
  margin      = DIMENSION
  width       = DIMENSION fit
  height      = DIMENSION fit broad
  depth       = DIMENSION fit broad
  distance    = DIMENSION
  separator   = TEXT
  stopper     = TEXT
  symbol      = none 1 2 3 ...
  expansion   = yes no command
  maxwidth    = DIMENSION
inherits from \framed
```

`\setuplistalternative [...,1] [...,2,...]`

```
1 a b c
2 command = COMMAND
  width   = DIMENSION
  stretch = DIMENSION
  distance = DIMENSION
```

`\setupmakeup [1.] [2.,...]`

```
1 IDENTIFIER
2 width      = DIMENSION
  height     = DIMENSION
  voffset    = DIMENSION
  hoffset    = DIMENSION
  page       = left yes right
  commands   = COMMAND
  doublesided = yes no empty
  headerstate = normal stop start empty none nomarking
  footerstate = normal stop start empty none nomarking
  textstate   = normal stop start empty none nomarking
  topstate    = stop start
  bottomstate = stop start
  pagestate   = stop start
  color       = IDENTIFIER
```

`\setupmarginblocks [...,*,...]`

```
* location = inmargin left middle right
  style    =
  width    = DIMENSION
  align    =
  top      = COMMAND
  inbetween = COMMAND
  bottom   = COMMAND
  left     = COMMAND
  right    = COMMAND
  before   = COMMAND
  after    = COMMAND
```

`\setupmarginrules [.*.]`

```
* level          = NUMBER
  rulethickness  = DIMENSION
```

`\setupmarking [1.] [2.]`

```
1 IDENTIFIER
2 state      = start stop
  separator  = COMMAND
  expansion  = yes no
```

`\setupnarrower [...,*,...]`

```
* left  = DIMENSION
  right = DIMENSION
  middle = DIMENSION
```

`\setupnumbering [...,*,...]`

```
* way = bytext bycd:section
  state = start stop
```

`\setupoppositeplacing [.*.]`

```
* state      = start stop
  before     = COMMAND
  inbetween  = COMMAND
  after      = COMMAND
```

```
\setupoutput [...,*,...]
```

```
* IDENTIFIER
```

```
\setuppagenumber [...,*,...]
```

```
* number = NUMBER  
state = start stop keep
```

```
\setuppagenumbering [...,*,...]
```

```
* alternative = singlesided doublesided  
location = header footer left right middle margin marginedge inleft inright  
conversion = numbers characters Characters romannumerals Romannumerals  
style =  
left = TEXT  
right = TEXT  
way = bytext bycd:section  
text = TEXT  
numberseparator = TEXT  
textseparator = TEXT  
cd:sectionnumber = yes no  
separator = TEXT  
strut = yes no  
state = start stop  
width = DIMENSION  
command = \...#1
```

```
\setuppagetransitions [...,*,...]  
OPTIONAL
```

```
* reset NUMBER
```

```
\setuppalet [...*...]
```

```
* IDENTIFIER
```

```
\setuppaper [...,*,...]
```

```
* paper = IDENTIFIER  
page = IDENTIFIER  
nx = NUMBER  
ny = NUMBER  
width = DIMENSION  
height = DIMENSION  
topspace = DIMENSION  
backspace = DIMENSION  
option = max fit
```

```
\setuppapersize [...1,...] [...2,...]  
OPTIONAL
```

```
1 A3 A4 A5 A6 letter ... CD IDENTIFIER landscape mirrored rotated 90 180 270  
2 A3 A4 A5 A6 letter ... IDENTIFIER landscape mirrored rotated negative 90 180 270
```

```
\setupparagraphnumbering [...,*,...]
```

```
* state = start stop reset line  
style =  
distance = DIMENSION
```

```
\setupparagraphs [.1.] [.2.] [..3.,...]  
                                OPTIONAL
```

```
1 IDENTIFIER  
2 NUMBER each  
3 style      =  
  width      = DIMENSION  
  height     = DIMENSION  
  align      =  
  tolerance  = verystRICT STRICT tolerant verytolerant stretch  
  distance   = DIMENSION  
  before     = COMMAND  
  after      = COMMAND  
  inner      = COMMAND  
  command    = COMMAND  
  rule       = on off
```

```
\setuppositioning [..*.,...]
```

```
* state = start overlay  
  unit  = cm pt em mm ex es in  
  factor = NUMBER  
  scale = NUMBER  
  offset = yes no  
  xstep  = absolute relative  
  ystep  = absolute relative
```

```
\setupprofiles [..*.,...]
```

```
* option = test
```

```
\setupprograms [..*.,...]
```

```
* directory = TEXT
```

```
\setuppuplications [..*.,...]
```

```
* alternative = apa normal  
  inherits from \setupenumerations
```

```
\setupquote [..*.,...]
```

```
* before = COMMAND  
  after  = COMMAND  
  style  =  
  color  = IDENTIFIER  
  location = TEXT margin
```

```
\setupreferencelist [...,1...] [...,2.,...]
```

```
1 IDENTIFIER  
2 state      = start stop  
  criterium  = SECTION local previous all  
  command    = COMMAND  
  before     = COMMAND  
  after      = COMMAND
```

`\setupreferencing [...,*.,...]`

```
* state = start stop
cd:sectionnumber = yes no
prefix = + - TEXT
interaction = label TEXT all symbol
width = DIMENSION
left = COMMAND
right = COMMAND
convertfile = yes no small big
separator = TEXT
autofile = yes no page
global = yes no
```

`\setupregister [.1.] [.2.] [...,3.,...]`
OPTIONAL

```
1 SINGULAR NAME
2 IDENTIFIER
3 n = NUMBER
balance = yes no
align =
style =
pagestyle =
textstyle =
indicator = yes no
coupling = yes no
cd:sectionnumber = yes no
criterium = SECTION local all
distance = DIMENSION
symbol = 1 2 ... n a ... none
interaction = pagenumber TEXT
expansion = yes no command
referencing = on off
command = \...#1
location = left middle right
maxwidth = DIMENSION
unknownreference = empty none
alternative = a b A B
prefix = both first none
compress = no yes
deeptextcommand = \...#1
```

`\setuprotate [...,*.,...]`

```
* rotation = NUMBER
location = normal high fit broad depth
inherits from \setupframed
```

`\setuprule [.1.] [...,2.,...]`

```
1 IDENTIFIER
2 depth = DIMENSION
height = DIMENSION
width = DIMENSION
spacebefore = DIMENSION
spaceafter = DIMENSION
color = IDENTIFIER
```

`\setupscreens [...,*.,...]`

```
* method = dot rule external
resolution = NUMBER
factor = NUMBER
screen = NUMBER
```

`\setupsection [..1.] [..2.] [..3=.,...]`
OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER
- 3 conversion = numbers characters Characters romannumerals Romannumerals
previousnumber = yes no

`\setupsectionblock [..1.] [..2=.,...]`

- 1 IDENTIFIER
- 2 number = yes no
page = yes right
before = COMMAND
after = COMMAND

`\setupsorting [..1.] [..2=.,...]`

- 1 IDENTIFIER
- 2 before = COMMAND
after = COMMAND
command = \...#1
state = start stop
criterium = all used
style =
expansion = yes no command

`\setupspacing [..*.]`

- * broad packed

`\setupstrut [..*.]`

- * yes no cap TEXT

`\setupsubpagenumber [..*=.,...]`

- * way = bytext bycd:section
state = start stop none

`\setupsymbolset [..*.]`

- * IDENTIFIER

`\setupsynchronization [..*=.,...]`

- * state = start stop

`\setupsynchronizationbar [..*=.,...]`

- * alternative = page local
width = DIMENSION height fit
height = DIMENSION
style =
color = IDENTIFIER
inherits from \setupframed

`\setupsynonyms [.1.] [...,2,...]`

```
1 IDENTIFIER
2 textstyle      =
  synonymstyle   =
  location       = left right top serried inmargin inleft inright
  width          = DIMENSION
  state          = start stop
  criterium      = all used
  conversion     = yes no
  expansion      = yes no command
  command        = \...#1#2#3
```

`\setupsystem [...,*.,...]`

```
* resolution = NUMBER
  file        = TEXT
  directory   = TEXT
  random      = normal small medium big NUMBER
```

`\setuptab [...,*.,...]`

```
* sample = TEXT
  width   = DIMENSION
  headstyle =
  location = left right
```

`\setuptables [...,*.,...]`

```
* distance      = small medium big
  bodyfont      = 5pt ... 12pt small big
  HL            = NUMBER small medium big none
  VL            = NUMBER small medium big none
  depth         = NUMBER strut
  height        = NUMBER strut
  rulethickness = DIMENSION
  rulecolor     = IDENTIFIER
  align         =
  commands     = COMMAND
  align        =
  background    = screen color none
  backgroundscreen = NUMBER
  backgroundcolor = IDENTIFIER
  bodyfont      = 5pt ... 12pt small big
```

`\setuptabulate [.1.] [...,2,...]`
OPTIONAL

```
1 IDENTIFIER
2 unit      = DIMENSION
  indenting =
  before    = COMMAND
  after     = COMMAND
  inner     = COMMAND
  EQ        = TEXT
  rulecolor = IDENTIFIER
  align     =
  rulethickness = DIMENSION
  distance  = blank grid depth DIMENSION small medium big none
  bodyfont  = 5pt ... 12pt small big
  rule      = normal line
  split     = yes no
```

`\setuptext [...,2,...]`
OPTIONAL

```
1 inherits from \setupheader
2 inherits from \setupheader
```

`\setuptextposition [.1.] [...,.2.,...]`

- 1 IDENTIFIER
- 2 *inherits from* \setuppositioning

`\setuptextrules [...,*.,...]`

- * location = left inmargin
- before = COMMAND
- after = COMMAND
- inbetween = COMMAND
- width = DIMENSION
- distance = DIMENSION
- bodyfont = 5pt ... 12pt small big
- color = IDENTIFIER
- style =
- rulecolor = IDENTIFIER

`\setuptexttexts [.1.] [.2.] [.3.]`
OPTIONAL OPTIONAL OPTIONAL

- 1
- 2
- 3

`\setuptextvariable [.1.] [...,.2.,...]`

- 1 IDENTIFIER
- 2 left = TEXT
- right = TEXT
- distance = DIMENSION
- command = \...#1
- strut = yes no cap TEXT

`\setupthinrules [.*.]`

- * interlinespace = small medium big
- n = NUMBER
- before = COMMAND
- inbetween = COMMAND
- after = COMMAND
- color = IDENTIFIER
- backgroundcolor = IDENTIFIER
- height = DIMENSION max
- depth = DIMENSION max
- alternative = a b c d
- rulethickness = DIMENSION
- color = IDENTIFIER
- background = color
- backgroundcolor = IDENTIFIER

`\setuptolerance [...,*.,...]`

- * horizontal vertical stretch space verystrict strict tolerant verytolerant

`\setuptop [.1.] [...,.2.,...]`
OPTIONAL

- 1 *inherits from* \setupheader
- 2 *inherits from* \setupheader

`\setuptoptexts` [¹.] [².] [³.]
 OPTIONAL OPTIONAL OPTIONAL

1
2
3

`\setuptype` [...,*,...]

* space = on off
 option = slanted normal none
 style =
 color = IDENTIFIER

`\setuptyping` [¹.] [...,².,...]
 OPTIONAL

1 file typing IDENTIFIER
2 space = on off
 page = yes no
 option = slanted normal commands color none
 text = yes no
 icommand = COMMAND
 vcommand = COMMAND
 ccommand = COMMAND
 before = COMMAND
 after = COMMAND
 margin = DIMENSION standard yes no
 evenmargin = DIMENSION
 oddmargin = DIMENSION
 blank = DIMENSION small medium big standard halfline line
 escape =
 space = on off
 tab = NUMBER yes no
 page = yes no
 indentnext =
 style =
 color = IDENTIFIER
 palet = IDENTIFIER
 lines = yes no hyphenated
 empty = yes all no
 numbering = line file no

`\setupunderbar` [...,*,...]

* alternative = a b c
 rulethickness = DIMENSION
 bottomoffset = DIMENSION
 topoffset = DIMENSION
 rulecolor = IDENTIFIER

`\setupurl` [...,*,...]

* style =
 urlalternative = none both before after
 urlspace = yes no

`\setupversions` [...,*,...]

* number = NUMBER
 style =

`\setupwhitespace` [...*]
 OPTIONAL

* none small medium big line fixed fix DIMENSION

`\showbodyfont [...,*,...]`

** inherits from \setupbodyfont*

`\showbodyfontenvironment [...,*,...]`

** inherits from \setupbodyfont*

`\showcolor [...]`

** IDENTIFIER*

`\showcolorgroup [...1...] [...2,...]`

1 IDENTIFIER

2 horizontal vertical name value NUMBER

`\showexternalfigures [...,*,...]`
OPTIONAL

** alternative = a b c*

`\showfields [...,*,...]`
OPTIONAL

** IDENTIFIER*

`\showframe [...]`
OPTIONAL

** TEXT margin edge*

`\showgrid [...1,...]{2.}`
OPTIONAL

1 reset top bottom none all lines frame nonumber right left

2 TEXT

`\showlayout`

`\showmakeup`

`\showpalet [...1...] [...2,...]`

1 IDENTIFIER

2 horizontal vertical name value

`\showprint [...1,...][...2,...][...3,...]`

1 inherits from \setuppapersize

2 inherits from \setuppapersize

3 inherits from \setuplayout

`\showsetups`

`\showstruts`

`\showsymbolset [...]`

* IDENTIFIER

`\someline [...]`

* REFERENCE

`\somewhere {.1.} {.2.} [.3.]`

1 TEXT

2 TEXT

3 REFERENCE

`\SORT [.1.] {.2.}`

1 TEXT

2 TEXT

`\space`

`\splitfloat [...,1...] {.2.} {.3.}`
OPTIONAL

1 *inherits from* \setupfloatsplitting

2 TEXT

3 TEXT

`\startalignment [...]` ... `\stopalignment`
OPTIONAL

* *inherits from* \setupalign

`\startbackground`

`\startBUFFER [...]` ... `\stopBUFFER`
OPTIONAL

* IDENTIFIER

`\startcolor [...]` ... `\stopcolor`

* IDENTIFIER

`\startcolumns [...,*...] ... \stopcolumns`
OPTIONAL

* *inherits from* \setupcolumns

`\startcombination [...]` ... `\stopcombination`

* N*M

`\startcomment [...]` OPTIONAL `[...2...]` OPTIONAL ... `\stopcomment`

1 IDENTIFIER

2 *inherits from* `\setupcomment`

`\startcomponent ...` ... `\stopcomponent`

*

`\startDESCRIPTION {...}` ... `\stopDESCRIPTION`

* TEXT

`\startdocument [...]` ... `\stopdocument`

* IDENTIFIER

`\startENUMERATION`

`\startenvironment ...` ... `\stopenvironment`

*

`\startfact ...1 ...2 ...3 ...` `\stopfact`

1 EMPTY

2 EMPTY

3 EMPTY

`\startfigure [...]` OPTIONAL `[...3...]` OPTIONAL ... `\stopfigure`

1 IDENTIFIER

2 FILE

3 `factor = NUMBER`
`frame = on off`

`\startFLOATtext [...]` OPTIONAL `[...]` OPTIONAL `{...3...}` `{...4...}` ... `\stopFLOATtext`

1 left right high middle low offset tall

2 REFERENCE

3 TEXT

4 TEXT

`\startFORMULA`

`\startFRAMEDTEXT` [¹...] [OPTIONAL...,²OPTIONAL...,...] ... `\stopFRAMEDTEXT`

- 1 left right middle none
- 2 *inherits from* \setupframedtexts

`\starthiding`

`\startinteractionmenu` [...]`\stopinteractionmenu`

- * IDENTIFIER

`\startITEMGROUP` [¹...] [OPTIONAL...,²...,] [OPTIONAL...,³OPTIONAL...,] ... `\stopITEMGROUP`

- 1 IDENTIFIER
- 2 a A KA n N m r R KR NUMBER continue standard broad serried packed stopper joinedup atmargin
inmargin intro columns text paragraph repeat
- 3 *inherits from* \setupitemgroup

`\startlegend` [¹...] [OPTIONAL...²...³...⁴...]`\stoplegend`

- 1 two
- 2 EMPTY
- 3 EMPTY
- 4 EMPTY

`\startline` [...]`\stopline`

- * REFERENCE

`\startlinecorrection`

`\startlinenumbering` [...]`\stoplinenumbering`

- * continue

`\startlines`

`\startlocal`

`\startlocalenvironment`

`\startlocalfootnotes`

`\startmakeup` [¹...] [OPTIONAL...,²...,] ... `\stopmakeup`

- 1 IDENTIFIER
- 2 *inherits from* \setupmakeup

`\startmarginblock`

`\startmarginrule [...] ... \stopmarginrule`

`* NUMBER`

`\startNAMEmakeup`

`\startnarrower [...*...] ... \stopnarrower`
OPTIONAL

`* left middle right`

`\startopposite`

`\startoverlay {...1} {...2} ... \stopoverlay`

`1 TEXT`

`2 TEXT`

`\startoverview [...*...] ... \stopoverview`

`* IDENTIFIER`

`\startpacked [...] ... \stoppacked`
OPTIONAL

`* blank`

`\startPARAGRAPH`

`\startpositioning`

`\startpostponing`

`\startproduct *... \stopproduct`

`*`

`\startprofile [...*...] ... \stopprofile`

`* IDENTIFIER`

`\startproject *... \stopproject`

`*`

`\startquotation [...*...] ... \stopquotation`

* left middle right

`\startREGISTER [...1.] {...+.2+...}`
OPTIONAL

1 TEXT

2 ENTRY

`\startsymbolset [...*] ... \stopsymbolset`

* IDENTIFIER

`\startsynchynchronization`

`\starttable [...*] ... \stoptable`

* TEXT IDENTIFIER

`\starttables [...*] ... \stoptables`

* TEXT IDENTIFIER

`\startTABULATE [...1.] [...,2,...] ... \stopTABULATE`
OPTIONAL OPTIONAL

1 TEXT

2 *inherits from* \useexternalfigure

`\starttextrule [...1.] {...2.} ... \stoptextrule`
OPTIONAL OPTIONAL

1 top bottom

2 TEXT

`\startTYPING`

`\startunpacked`

`\startversion [...*...] ... \stopversion`

* NUMBER

`\stretched {...*}`

* WORD

`\sub [...*...] ...`
OPTIONAL

* REFERENCE

`\subject [...1...] {..2.}`
 OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\subsection [...1...] {..2.}`
 OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\subsubject [...1...] {..2.}`
 OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\subsubsection [...1...] {..2.}`
 OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\subsubsubject [...1...] {..2.}`
 OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\switchtobodyfont [...*,...]`

* 5pt ... 12pt small big global

`\switchtorawfont [...*]`

* IDENTIFIER

`\sym {..*.}`

* TEXT

`\symbol [...1.] [...2.]`
 OPTIONAL OPTIONAL

- 1 IDENTIFIER
- 2 IDENTIFIER

`\synchronizationbar [...1.] [...,..2.,...]`

- 1 IDENTIFIER
- 2 alternative = page local
 inherits from \setupsynchronizationbar

`\synchronize`

`\SYNONYM [.1.] {.2.} {.3.}`
OPTIONAL

- 1 TEXT
- 2 TEXT
- 3 TEXT

`\tab {.1.} .2.`

- 1 TEXT
- 2 EMPTY

`\tex {...}`

- * TEXT

`\textreference [.1.] {.2.}`

- 1 REFERENCE
- 2 TEXT

`\textrule [.1.] {.2.}`
OPTIONAL OPTIONAL

- 1 top bottom
- 2 TEXT

`\textvariable [...]`

- * IDENTIFIER

`\thinrule`

`\thinrules [...]`
OPTIONAL

- * inherits from \setupthinrules

`\title [...;...] {.2.}`
OPTIONAL

- 1 REFERENCE
- 2 TEXT

`\tooltip [.1.] {.2.} {.3.}`
OPTIONAL

- 1 left right middle
- 2 TEXT
- 3 TEXT

`\translate [...,*,...]`

- * IDENTIFIER = TEXT

`\typ {...}`

* TEXT

`\type {...}`

* TEXT

`\typebuffer [...]`

* IDENTIFIER

`\typefile [...1] {...2}`
OPTIONAL

1 IDENTIFIER

2 TEXT

`\underbar {...}`

* TEXT

`\underbars {...* ...}`

* WORD

`\useblocks [...1,...] [...2,...]`
OPTIONAL

1 IDENTIFIER

2 IDENTIFIER

`\usecommands {...}`

* TEXT

`\usedirectory [...*,...]`

* IDENTIFIER reset

`\useencoding [...*,...]`

* IDENTIFIER

`\useexternaldocument [...1] [...2] [...3]`

1 IDENTIFIER

2 file

3 TEXT

```

\useexternalfigure [1...] [2...] [3...,3...,...]
                  OPTIONAL  OPTIONAL      OPTIONAL

1  IDENTIFIER
2  FILE
3  scale    = NUMBER
   yscale   = NUMBER
   yscale   = NUMBER
   factor   = max fit broad
   wfactor  = NUMBER max broad fit
   hfactor  = NUMBER max broad fit
   width    = DIMENSION
   height   = DIMENSION
   frame    = on off
   preset   = yes no
   display  = FILE
   preview  = yes no
   repeat   = yes no
   object   = yes no
   type     = eps mps pdf tif png jpg mov cd:tex
   method   = eps mps pdf tif png jpg mov cd:tex

```

```

\useexternalfile [1...] [2...] [3...] [4...,4...,...]

1  IDENTIFIER
2  IDENTIFIER
3  FILE
4  bodyfont = 5pt ... 12pt small big

```

```

\useexternalfiles [1...] [2...,2...,...]

1  IDENTIFIER
2  bodyfont = 5pt ... 12pt small big
   file     = FILE

```

```

\useexternalsoundtrack [1...] [2...]

1  IDENTIFIER
2  FILE

```

```

\usemodule [...*,...]

*  IDENTIFIER

```

```

\userreferences [...*,...]

*  FILE

```

```

\usespecials [...*,...]

*  reset IDENTIFIER

```

```

\usesymbols [...*]

*  IDENTIFIER

```

\useURL [.1.] [.2.] [.3.] [.4.]

- 1 IDENTIFIER
- 2 TEXT
- 3 file
- 4 TEXT

\version [...]

- * final concept temporary

\vl [...]

- * NUMBER

\weekday {...}

- * TEXT

\WEEKDAY {...}

- * TEXT

\whitespace

\Word {...}

- * WORD

\WORD {...}

- * WORD

\wordright {...}

- * TEXT

\WORDS {... ..}

- * WORD

\Words {... ..}

- * WORD

\writebetweenlist [.1.] {...}

- 1 SECTION IDENTIFIER
- 2 TEXT

\writetolist [..¹.] {..².} {..³.}

- 1 SECTION IDENTIFIER
- 2 TEXT
- 3 TEXT

\writetoreferencelist [..¹.] {..².} {..³.}

- 1 IDENTIFIER
- 2 TEXT
- 3 TEXT

\writetoregister [..¹.] [OPTIONAL..².] {..³.+..³.+..³.}

- 1 SINGULAR NAME
- 2 TEXT
- 3 ENTRY



PRAGMA ADE
Ridderstraat 27
8061GH Hasselt NL
www.pragma-ade.com